

Product Name: Cyberoam CR500iNG-XP Firewall

Manufacturer: -

Model Number: CR500iNG-XP

Please Note: This product has been discontinued. Please see the Sophos XG Firewall XG430 Appliance.

# Cyberoam CR500iNG-XP Firewall

The Cyberoam CR500iNG-XP Firewall features 8×10/100/1000 Ethernet ports, 18000 Mbps Firewall Throughput and comes with 2 Flexi Slots for add-on port modules of (8 Copper/8 x 1GbE Fiber/4 x 10GbE Fiber). Features

ï¿1/2 8×10/100/1000 Ethernet ports

� 18000 Mbps Firewall Throughput

ï¿⅓ 3250 Mbps NGFW Throughput

� 1650 Mbps Fully Protected Throughput

าั¿½ Layer 8 Identity-based Security / Application Visibility & Control

� Web Filtering / Web Application Firewall

Cyberoam CR500iNG-XP Firewall - Technical Specifications Interfaces

17.1/2 Maximum number of Available Ports 24

ï¿1/2 Fixed Copper GbE Ports 8

i¿1/2 Number of Slots for FleXi Ports Module 2

آذِ1⁄2 Port options per FleXi Ports Module\*\*\* 8 / 8 / 4

� (GbE Copper/GbE Fiber/10GbE Fiber)

� Console Ports (RJ45) 1

� Configurable Internal/DMZ/WAN Ports Yes

� USB Ports 2

ï¿1/2 # Hardware Bypass Segment 2

# System Performance\*

آزا Firewall Throughput (UDP) (Mbps) 18,000

تز1/2 Firewall Throughput (TCP) (Mbps) 16,000

� New sessions/second 100,000

� Concurrent sessions 2,500,000

i¿1/2 IPSec VPN Throughput (Mbps) 1,500

ï¿1/2 No. of IPSecTunnels 1,000

ï¿⅓ SSLVPN Throughput (Mbps) 650

� WAF Protected Throughput (Mbps) 1,500

i¿½ Anti-Virus Throughput (Mbps) 3,500

آذِرُ IPS Throughput (Mbps) 4,500

ï¿1/2 NGFW Throughput (Mbps)\*\*\*\* 3,250

าั¿1/2 Fully Protected Throughput (Mbps)\*\*\*\*\* 1,650

#### Stateful Inspection Firewall

� Layer 8 (User - Identity) Firewall

ï¿.½ Multiple Security Zones

ī¿½ Location-aware and Device-aware Identity-based AccessControl Policy

Ti. Maccess Control Criteria (ACC): User-Identity, Source and Destination Zone, MAC and IP



#### address, Service

- าั¿½ Security policies IPS, Web Filtering, ApplicationFiltering, Anti-virus, Anti-spam and QoS
- � Country-based Traffic Control
- ï¿1/2 Access Scheduling
- า๊¿½ Policy based Source and Destination NAT, Gateway
- ï¿⅓ Specific NAT Policy
- H.323, SIP NAT Traversal
- � DoS and DDoS attack prevention
- ï¿1/2 MAC and IP-MAC filtering
- ï¿⅓ Spoof Prevention

### Intrusion Prevention System

- ï¿1/2 Signatures: Default (4500+), Custom
- រី¿½ IPS Policies: Pre-configured Zone-based multiple policies, Custom
- آذِيًّ Filter based selection: Category, Severity, Platform and Target (Client/Server)
- � IPS actions: Recommended, Allow Packet, Drop Packet, Disable, Drop Session, Reset, Bypass Session
- � User-based policy creation
- าั¿½ Automatic signature updates via Cyberoam ThreatResearch Labs
- � Protocol Anomaly Detection
- ī¿½ SCADA-aware IPS with pre-defined category for ICS and SCADA signatures

# Gateway Anti-Virus & amp; Anti-Spyware

- เช่น Virus, Worm, Trojan Detection and Removal
- � Spyware, Malware, Phishing protection
- ï¿1/2 Automatic virus signature database update
- آزئ Scans HTTP, HTTPS, FTP, SMTP/S, POP3, IMAP, IM, VPN Tunnels
- � Customize individual user scanning
- ï¿⅓ Self Service Quarantine area
- ï¿1/2 Scan and deliver by file size
- ï¿⅓ Block by file types

# Gateway Anti-Spam

- ï¿⅓ Inbound and Outbound Scanning
- تز½ Real-time Blacklist (RBL), MIME header check
- า๊ะ่% Filter based on message header, size, sender, recipient
- � Subject line tagging
- าั¿½ Language and Content-agnostic spam protection using RPD Technology
- � Zero Hour Virus Outbreak Protection
- ï¿1/2 Self Service Quarantine area
- ï¿1/2 IP address Black list/White list-
- � Spam Notification through Digest
- ï¿1/2 IP Reputation based Spam filtering

### Web Filtering

- � On-Cloud Web Categorization
- 12.1/2 Controls based on URL, Keyword and File type
- าั¿½ Web Categories: Default (89+), External URL Database, Custom
- ï¿1/2 Protocols supported: HTTP, HTTPS-
- 12.1/2 Block Malware, Phishing, Pharming URLs
- ï¿⅓ Block Java Applets, Cookies, Active X, Google Cachepages



- � CIPA Compliant
- าั¿½ Data leakage control by blocking HTTP and HTTPSupload
- 17:1/2 Schedule-based access controlCustom Denied Message per Web Category
- تزير Safe Search enforcement, YouTube for Schools

#### Application Filtering

- تزاري Layer 7 (Applications) & Layer 8 (User Identity) Control and Visibility
- � Inbuilt Application Category Database
- า๊¿½ Control over 2,000+ Applications classified in 21Categories
- ī¿1/2 Filter based selection: Category, Risk Level, Characteristics and Technology
- � Schedule-based access control
- ī సై Visibility and Controls for HTTPS based Micro-Apps like Facebook chat, Youtube video upload
- ï¿1/2 Securing SCADA Networks
- าั¿1/2 SCADA/ICS Signature-based Filtering for Protocols
- � Modbus, DNP3, IEC, Bacnet, Omron FINS, Secure
- � DNP3, Longtalk
- � Control various Commands and Functions

#### Web Application Firewall

- ï¿1/2 Positive Protection model
- ī¿½ Unique "Intuitive Website Flow Detector" technology
- าั¿½ Protection against SQL Injections, Cross-site Scripting (XSS), Session Hijacking, URL Tampering, CookiePoisoning etc.
- � Support for HTTP 0.9/1.0/1.1
- � Back-end servers supported: 5 to 300 servers

#### Virtual Private Network

- آذِرُ IPSec, L2TP, PPTPEncryption 3DES, DES, AES, Twofish, Blowfish, Serpent
- ï¿1/2 Hash Algorithms MD5, SHA-1
- า๊¿1/2 Authentication: Preshared key, Digital certificates
- ï¿⅓ IPSec NAT Traversal
- � Dead peer detection and PFS support
- $\ddot{i}$ ¿½ Diffie Hellman Groups 1, 2, 5, 14, 15, 16
- � External Certificate Authority support
- ï¿⅓ Export Road Warrior connection configuration
- � Domain name support for tunnel end points
- � VPN connection redundancy
- � Overlapping Network support
- ï¿1/2 Hub & Spoke VPN support
- تز½ Threat Free Tunnelling (TFT) Technology

#### SSL VPN

- ï¿1/2 TCP & amp; UDP Tunnelling
- آزا Authentication Active Directory, LDAP, RADIUS, Cyberoam (Local)
- រ៉ុះ/ Multi-layered Client Authentication Certificate, Username/Password
- � User & Group policy enforcement
- ï¿1/2 Network access Split and Full tunnelling
- � Browser-based (Portal) Access Clientless access
- 121/2 Lightweight SSL VPN Tunnelling Client
- � Granular access control to all the enterprise networkresources



፲¿½ Administrative controls - Session timeout, Dead PeerDetection, Portal customization ፲¿½ TCP based Application Access - HTTP, HTTPS, RDP, TELNET, SSH

#### Wireless WAN

- ï¿1/2 USB port 3G/4G and WiMAX Support
- � Primary WAN link
- ï¿1/2 WAN Backup link

### **Bandwidth Management**

- ī¿½ Application, Web Category and Identity based Bandwidth Management
- i¿1/2 Guaranteed & Burstable bandwidth policy
- า๊¿½ Application & Traffic Discovery User Identity based Traffic Discovery
- 12/2 Data Transfer Report for multiple Gateways

#### Networking

- � WRR based Multilink Load Balancing
- � Automated Failover/Failback
- آذِ1/2 Interface types: Alias, Multiport Bridge, LAG (port trunking), VLAN, WWAN, TAP
- � DNS-based inbound load balancing
- าั¿½ IP Address Assignment Static, PPPoE (with ScheduleManagement), L2TP, PPTP & Description ( In the content of the conten
- DDNS, Client, Proxy ARP, Multiple DHCP Servers support, DHCP relay
- 17.1/2 Supports HTTP Proxy, Parent Proxy with FQDN
- آذِ Dynamic Routing: RIP v1& v2, OSPF, BGP, PIM-SIM, Multicast Forwarding
- ī¿½ Support of ICAP to integrate third-party DLP, WebFiltering and AV applications
- � Discover mode for PoC Deployments
- آزٰ½ IPv6 Support:
- าั¿½ Dual Stack Architecture: Support for IPv4 and IPv6Protocols
- � Management over IPv6
- ï¿⅓ IPv6 Route: Static and Source
- ï¿1/2 IPv6 tunneling (6in4, 6to4, 6rd, 4in6)
- ï¿1/2 Alias and VLAN
- าั¿½ DNSv6 and DHCPv6 ServicesFirewall security over IPv6 traffic
- ï¿⅓ High Availability for IPv6 networks

# High Availability

- ï¿⅓ Active-Active
- 17.1/2 Active-Passive with state synchronization
- 12/2 Stateful Failover with LAG Support

# Administration & System Management

- า๊¿⅓ Web-based configuration wizard
- ï¿1/2 Role-based Access control
- ï¿⅓ Support of API
- ï¿⅓ Firmware Upgrades via Web UI
- � Web 2.0 compliant UI (HTTPS)
- � UI Color Styler
- 17.1/2 Command Line Interface (Serial, SSH, Telnet)
- ï¿⅓ SNMP (v1, v2c)
- าั¿1/2 Multi-lingual: English, Chinese, Hindi, French, Japanese
- � Cyberoam Central Console (Optional)



#### User Authentication

- ï¿1/2 Internal database
- ï¿1/2 AD Integration and OU-based Security Policies
- آز 4 Automatic Windows/RADIUS Single Sign On
- าั¿½ External LDAP/LDAPS/RADIUS database Integration
- ï¿⅓ Thin Client support
- � 2-factor authentication: 3rd party support\*\*
- � SMS (Text-based) Authentication
- � Layer 8 Identity over IPv6
- ï¿1/2 Secure Authentication AD, LDAP, Radius
- � Clientless Users
- � Authentication using Captive Portal

#### Logging/Monitoring

- � Real-time and historical Monitoring
- าั¿½ Log Viewer IPS, Web filter, WAF, Anti-Virus, Anti-Spam, Authentication, System and Admin Events
- าั¿½ Forensic Analysis with quick identification of networkattacks and other traffic anomalies
- ï¿⅓ Syslog support
- � 4-eye Authentication

#### On-Appliance Cyberoam-iView Reporting

- ï¿1/2 Integrated Web-based Reporting tool
- � 1,200+ drilldown reports
- آذِر Compliance reports HIPAA, GLBA, SOX, PCI, FISMA
- � Zone based application reports
- ï¿⅓ Historical and Real-time reports
- آزٰ Default Dashboards: Traffic and Security
- īപ് Username, Host, Email ID specific Monitoring Dashboard
- آذِ½ Reports Application, Internet & Usage, Mail Usage, Attacks, Spam, Virus, Web Usage, Mail Usage, Attacks, Spam, Virus,
- Search Engine, User ThreatQuotient (UTQ) for high risk users and more
- า๊¿½ Client Types Report including BYOD Client Types
- � Multi-format reports tabular, graphical
- � Export reports in PDF, Excel, HTML
- � Email notification of reports
- īస్ట్ Report customization (Custom view and custom logo)
- � Supports 3rd party PSA Solution ConnectWise

### IPSec VPN Client\*\*\*

- 17:1/2 Inter-operability with major IPSec VPN Gateways
- ï¿⅓ Import Connection configuration

#### Certification

- ï¿1/2 Common Criteria EAL4+
- ï¿1/2 ICSA Firewall Corporate
- � Checkmark Certification
- � VPNC Basic and AES interoperability
- ï¿1/2 IPv6 Ready Gold Logo
- าั¿1/2 Global Support Excellence ITIL compliance (ISO 20000)



### Hardware Specifications

� Memory 4GB � Compact Flash 4GB � HDD 250GB or higher

# Compliance

ϊ¿½ CE ϊ¿½ FCC ϊ¿½ UL

# **Dimensions**

� H x W x D (inches) - 1.7 x 17.3 x 11.85 � H x W x D (cms) - 4.4 X 43.9 X 30.1 � Weight - 5.1 kg, 11.24 lbs

### Power

� Input Voltage - 100-240 VAC� Consumption - 208W� Total Heat Dissipation (BTU) - 345

### Environmental

� Operating Temperature - 0 to 40 °C� Storage Temperature - 0 to 70 °C� Relative Humidity (Non condensing) - 10 to 90%

# **Please Enquire**