

Cyberoam CR500iNG-XP Firewall



Product Name: Cyberoam CR500iNG-XP Firewall

Manufacturer: -

Model Number: CR500iNG-XP

Please Note: This product has been discontinued. Please see the Sophos XG Firewall XG430 Appliance.

Cyberoam CR500iNG-XP Firewall

The Cyberoam CR500iNG-XP Firewall features 8x10/100/1000 Ethernet ports, 18000 Mbps Firewall Throughput and comes with 2 Flexi Slots for add-on port modules of (8 Copper/8 x 1GbE Fiber/4 x 10GbE Fiber).Features

- 8x10/100/1000 Ethernet ports
- 18000 Mbps Firewall Throughput
- 3250 Mbps NGFW Throughput
- 1650 Mbps Fully Protected Throughput
- Layer 8 Identity-based Security / Application Visibility & Control
- Web Filtering / Web Application Firewall

Cyberoam CR500iNG-XP Firewall - Technical Specifications
Interfaces

- Maximum number of Available Ports 24
- Fixed Copper GbE Ports 8
- Number of Slots for Flexi Ports Module 2
- Port options per Flexi Ports Module*** 8 / 8 / 4
- (GbE Copper/GbE Fiber/10GbE Fiber)
- Console Ports (RJ45) 1
- Configurable Internal/DMZ/WAN Ports Yes
- USB Ports 2
- # Hardware Bypass Segment 2

System Performance*

- Firewall Throughput (UDP) (Mbps) 18,000
- Firewall Throughput (TCP) (Mbps) 16,000
- New sessions/second 100,000
- Concurrent sessions 2,500,000
- IPSec VPN Throughput (Mbps) 1,500
- No. of IPSecTunnels 1,000
- SSLVPN Throughput (Mbps) 650
- WAF Protected Throughput (Mbps) 1,500
- Anti-Virus Throughput (Mbps) 3,500
- IPS Throughput (Mbps) 4,500
- NGFW Throughput (Mbps)**** 3,250
- Fully Protected Throughput (Mbps)***** 1,650

Stateful Inspection Firewall

- Layer 8 (User - Identity) Firewall
- Multiple Security Zones
- Location-aware and Device-aware Identity-based AccessControl Policy
- Access Control Criteria (ACC): User-Identity, Source andDestination Zone, MAC and IP

Cyberoam CR500iNG-XP Firewall

address, Service

- ½ Security policies - IPS, Web Filtering, Application Filtering, Anti-virus, Anti-spam and QoS
- ½ Country-based Traffic Control
- ½ Access Scheduling
- ½ Policy based Source and Destination NAT, Gateway
- ½ Specific NAT Policy
- ½ H.323, SIP NAT Traversal
- ½ DoS and DDoS attack prevention
- ½ MAC and IP-MAC filtering
- ½ Spoof Prevention

Intrusion Prevention System

- ½ Signatures: Default (4500+), Custom
- ½ IPS Policies: Pre-configured Zone-based multiple policies, Custom
- ½ Filter based selection: Category, Severity, Platform and Target (Client/Server)
- ½ IPS actions: Recommended, Allow Packet, Drop Packet, Disable, Drop Session, Reset, Bypass Session
- ½ User-based policy creation
- ½ Automatic signature updates via Cyberoam Threat Research Labs
- ½ Protocol Anomaly Detection
- ½ SCADA-aware IPS with pre-defined category for ICS and SCADA signatures

Gateway Anti-Virus & Anti-Spyware

- ½ Virus, Worm, Trojan Detection and Removal
- ½ Spyware, Malware, Phishing protection
- ½ Automatic virus signature database update
- ½ Scans HTTP, HTTPS, FTP, SMTP/S, POP3, IMAP, IM, VPN Tunnels
- ½ Customize individual user scanning
- ½ Self Service Quarantine area
- ½ Scan and deliver by file size
- ½ Block by file types

Gateway Anti-Spam

- ½ Inbound and Outbound Scanning
- ½ Real-time Blacklist (RBL), MIME header check
- ½ Filter based on message header, size, sender, recipient
- ½ Subject line tagging
- ½ Language and Content-agnostic spam protection using RPD Technology
- ½ Zero Hour Virus Outbreak Protection
- ½ Self Service Quarantine area
- ½ IP address Black list/White list-
- ½ Spam Notification through Digest
- ½ IP Reputation based Spam filtering

Web Filtering

- ½ On-Cloud Web Categorization
- ½ Controls based on URL, Keyword and File type
- ½ Web Categories: Default (89+), External URL Database, Custom
- ½ Protocols supported: HTTP, HTTPS-
- ½ Block Malware, Phishing, Pharming URLs
- ½ Block Java Applets, Cookies, Active X, Google Cache pages

Cyberoam CR500iNG-XP Firewall

- CIPA Compliant
- Data leakage control by blocking HTTP and HTTPS upload
- Schedule-based access control Custom Denied Message per Web Category
- Safe Search enforcement, YouTube for Schools

Application Filtering

- Layer 7 (Applications) & Layer 8 (User - Identity) Control and Visibility
- Inbuilt Application Category Database
- Control over 2,000+ Applications classified in 21 Categories
- Filter based selection: Category, Risk Level, Characteristics and Technology
- Schedule-based access control
- Visibility and Controls for HTTPS based Micro-Apps like Facebook chat, Youtube video upload
- Securing SCADA Networks
- SCADA/ICS Signature-based Filtering for Protocols
- Modbus, DNP3, IEC, Bacnet, Omron FINS, Secure
- DNP3, Longtalk
- Control various Commands and Functions

Web Application Firewall

- Positive Protection model
- Unique "Intuitive Website Flow Detector" technology
- Protection against SQL Injections, Cross-site Scripting (XSS), Session Hijacking, URL Tampering, Cookie Poisoning etc.
- Support for HTTP 0.9/1.0/1.1
- Back-end servers supported: 5 to 300 servers

Virtual Private Network

- IPSec, L2TP, PPTP Encryption - 3DES, DES, AES, Twofish, Blowfish, Serpent
- Hash Algorithms - MD5, SHA-1
- Authentication: Preshared key, Digital certificates
- IPSec NAT Traversal
- Dead peer detection and PFS support
- Diffie Hellman Groups - 1, 2, 5, 14, 15, 16
- External Certificate Authority support
- Export Road Warrior connection configuration
- Domain name support for tunnel end points
- VPN connection redundancy
- Overlapping Network support
- Hub & Spoke VPN support
- Threat Free Tunnelling (TFT) Technology

SSL VPN

- TCP & UDP Tunnelling
- Authentication - Active Directory, LDAP, RADIUS, Cyberoam (Local)
- Multi-layered Client Authentication - Certificate, Username/Password
- User & Group policy enforcement
- Network access - Split and Full tunnelling
- Browser-based (Portal) Access - Clientless access
- Lightweight SSL VPN Tunnelling Client
- Granular access control to all the enterprise network resources

Cyberoam CR500iNG-XP Firewall

- Administrative controls - Session timeout, Dead PeerDetection, Portal customization
- TCP based Application Access - HTTP, HTTPS, RDP, TELNET, SSH

Wireless WAN

- USB port 3G/4G and WiMAX Support
- Primary WAN link
- WAN Backup link

Bandwidth Management

- Application, Web Category and Identity based Bandwidth Management
- Guaranteed & Burstable bandwidth policy
- Application & User Identity based Traffic Discovery
- Data Transfer Report for multiple Gateways

Networking

- WRR based Multilink Load Balancing
- Automated Failover/Failback
- Interface types: Alias, Multiport Bridge, LAG (port trunking), VLAN, WWAN, TAP
- DNS-based inbound load balancing
- IP Address Assignment - Static, PPPoE (with ScheduleManagement), L2TP, PPTP &
- DDNS, Client, Proxy ARP, Multiple DHCP Servers support, DHCP relay
- Supports HTTP Proxy, Parent Proxy with FQDN
- Dynamic Routing: RIP v1 & v2, OSPF, BGP, PIM-SIM, Multicast Forwarding
- Support of ICAP to integrate third-party DLP, WebFiltering and AV applications
- Discover mode for PoC Deployments
- IPv6 Support:
- Dual Stack Architecture: Support for IPv4 and IPv6 Protocols
- Management over IPv6
- IPv6 Route: Static and Source
- IPv6 tunneling (6in4, 6to4, 6rd, 4in6)
- Alias and VLAN
- DNSv6 and DHCPv6 Services Firewall security over IPv6 traffic
- High Availability for IPv6 networks

High Availability

- Active-Active
- Active-Passive with state synchronization
- Stateful Failover with LAG Support

Administration & System Management

- Web-based configuration wizard
- Role-based Access control
- Support of API
- Firmware Upgrades via Web UI
- Web 2.0 compliant UI (HTTPS)
- UI Color Styler
- Command Line Interface (Serial, SSH, Telnet)
- SNMP (v1, v2c)
- Multi-lingual : English, Chinese, Hindi, French, Japanese
- Cyberoam Central Console (Optional)

Cyberoam CR500iNG-XP Firewall

User Authentication

- ½ Internal database
- ½ AD Integration and OU-based Security Policies
- ½ Automatic Windows/RADIUS Single Sign On
- ½ External LDAP/LDAPS/RADIUS database Integration
- ½ Thin Client support
- ½ 2-factor authentication: 3rd party support**
- ½ SMS (Text-based) Authentication
- ½ Layer 8 Identity over IPv6
- ½ Secure Authentication ‐ AD, LDAP, Radius
- ½ Clientless Users
- ½ Authentication using Captive Portal

Logging/Monitoring

- ½ Real-time and historical Monitoring
- ½ Log Viewer - IPS, Web filter, WAF, Anti-Virus, Anti-Spam, Authentication, System and Admin Events
- ½ Forensic Analysis with quick identification of network attacks and other traffic anomalies
- ½ Syslog support
- ½ 4-eye Authentication

On-Appliance Cyberoam-iView Reporting

- ½ Integrated Web-based Reporting tool
- ½ 1,200+ drilldown reports
- ½ Compliance reports - HIPAA, GLBA, SOX, PCI, FISMA
- ½ Zone based application reports
- ½ Historical and Real-time reports
- ½ Default Dashboards: Traffic and Security
- ½ Username, Host, Email ID specific Monitoring Dashboard
- ½ Reports ‐ Application, Internet & Web Usage, Mail Usage, Attacks, Spam, Virus, Search Engine, User Threat Quotient (UTQ) for high risk users and more
- ½ Client Types Report including BYOD Client Types
- ½ Multi-format reports - tabular, graphical
- ½ Export reports in - PDF, Excel, HTML
- ½ Email notification of reports
- ½ Report customization ‐ (Custom view and custom logo)
- ½ Supports 3rd party PSA Solution ‐ ConnectWise

IPSec VPN Client***

- ½ Inter-operability with major IPSec VPN Gateways
- ½ Import Connection configuration

Certification

- ½ Common Criteria - EAL4+
- ½ ICSA Firewall - Corporate
- ½ Checkmark Certification
- ½ VPNC - Basic and AES interoperability
- ½ IPv6 Ready Gold Logo
- ½ Global Support Excellence - ITIL compliance (ISO 20000)

Cyberoam CR500iNG-XP Firewall

Hardware Specifications

• Memory 4GB
• Compact Flash 4GB
• HDD 250GB or higher

Compliance

• CE
• FCC
• UL

Dimensions

• H x W x D (inches) - 1.7 x 17.3 x 11.85
• H x W x D (cms) - 4.4 X 43.9 X 30.1
• Weight - 5.1 kg, 11.24 lbs

Power

• Input Voltage - 100-240 VAC
• Consumption - 208W
• Total Heat Dissipation (BTU) - 345

Environmental

• Operating Temperature - 0 to 40 °C
• Storage Temperature - 0 to 70 °C
• Relative Humidity (Non condensing) - 10 to 90%

Please Enquire