

## ZYCOO CooFone-D60 IP Phone



Product Name: ZYCOO CooFone-D60 IP Phone

Manufacturer: -

Model Number: CooFone-D60

Please Note: This item has been discontinued. Please see ZYCOO CooFone-H81 IP Phone for an alternative.

### ZYCOO CooFone-D60 IP Phone

The ZYCOO CooFone-D60 is advanced IP Phone. The D60 features. Programmable Softkeys and function keys allow you to define more features easily and enhance your productivity. With HD codec G722, and echo cancellation, you can enjoy the excellent voice quality in the ever constant communication environment.

#### Features

- 4 line keys defined as multi-line with screen display, or used as SIP line keys
- Softkeys/ Function keys programmable
- 8 DSS keys
- IAX2 line key
- SIP authentication (none, basic, MD5)
- Phonebook 500 records
- 9 kinds of ring type and 5 user-defined music ring
- Incoming calls /outgoing calls /missing calls(100 records for each).

### ZYCOO CooFone-D60 - Technical Specification

#### Phone Features

- Call forward/ Caller ID
- Call transfer (blind/attended)
- Call holding/waiting
- Flexible dial map
- Empty calling no. reject service
- Black list/ White list
- BLF/ No disturb/ Speed dial/ SMS
- 4 line keys defined as multi line with screen display, or used as SIP line keys
- Softkeys/ Function keys programmable
- 8 DSS keys
- IAX2 line key
- SIP authentication (none, basic, MD5)
- Phonebook 500 records
- 9 kinds of ring type and 5 user-defined music ring
- Incoming calls /outgoing calls /missing calls(100 records for each).

#### Advanced Features

- XML phonebook/browser
- Code synchronization via IP PBX/IMS
- Click to dial via web phone book
- Action URL/Active URI
- Voice codec setting for each SIP line
- Hands-free headset ringing choice
- Signal tone parameters customized
- Voice codec setting for each SIP line

## ZYCOO CooFone-D60 IP Phone

- Keypad lock, and emergency call during the keypad lock.
- Ring play via headset or speaker setting
- Code synchronization via IP PBX/IMS
- Click to dial via web phone book/ Group listening

### IP Phone System Integration

- Conference call park
- Call pickup
- Paging and intercom
- Redial and unredial
- Click to dial
- Secondary dialing automatically
- CLIR (reject the anonymous call)
- CLIP (make a call with anonymous)
- Dial without register

### Codec & Voice

- Wideband codec: G.722.1
- Narrowband codec: G.711a/u, G.723.1 high/low, G.729a/b, G.726
- Echo cancellation: G.168
- Compliance in LEC, additional acoustic echo cancellation(AEC) can reach 96ms max filter length in hands-free mode
- Full duplex hands-free speakerphone
- Voice Gain Setting, VAD, CNG
- EXT DSS consoles with 5max

### Network Features

- WAN/LAN: 10/100M Ethernet ports
- Route and Bridge mode.
- Bridge working as hub(optional)
- PPPoE for xDSL
- DTMF: SIP info, DTMF Relay, RFC2833
- SIP 2.0 (RFC3261) and correlative RFCs
- VLAN(voice vlan/data vlan)/ 802.1
- Basic NAT and NAPT
- NAT transverse: STUN client
- DHCP client on WAN
- DHCP server on LAN
- Peer to Peer

### Security

- Main DNS and secondary DNS server.
- DNS Relay, SNTP Client, Firewall
- VPN (L2TP/OPENVPN) and DMZ
- QoS with DiffServ
- Network tools in telnet server:
- including ping, trace route, telnet client

### Maintenance and Management

- Web, telnet and keypad management with different account right

## ZYCOO CooFone-D60 IP Phone

- 1/2 HTTP, FTP or TFTP server
- 1/2 Auto provisioning: DHCP option66
- 1/2 Telnet remote management/upload/download setting file
- 1/2 Safe mode provide reliability
- 1/2 Auto Provisioning via HTTPS/FTPS(optional)
- 1/2 TR-069(optional)/ Syslog

### Specifications

- 1/2 WAN: 10/100Base-T RJ-45 for WAN
- 1/2 LAN: 10/100Base-T RJ-45 for PC
- 1/2 Power Adapter: Input:100-240V
- 1/2 Output:5V/1A
- 1/2 Power Consumption: Idle: 2.5W/Active: 2.8W
- 1/2 LCD Size: 80\*43mm/ 128\*64 pixel graphic LCD
- 1/2 Operation Temperature: 0-40
- 1/2 Relative Humidity: 10-65%
- 1/2 Main Chipset: Broadcom
- 1/2 SDRAM: 128Mbits
- 1/2 Flash: 32Mbits

**Price: £70.80**