

## OpenVox A400E PCI Express Asterisk Card



Product Name: OpenVox A400E PCI Express Asterisk Card

Manufacturer: -

Model Number: A400E

### OpenVox A400E PCI Express Asterisk Card

Please Note: The OpenVox A400E contains 4 module banks. Each bank supports one analog interface. The module banks may be filled with up to 4 FXO or FXS modules enabling the creation of any combination of ports. Please select your required modules above.

Please Note: This is a PCI Express Card. Please make sure your motherboard/server is compatible with this product.

[View PCI vs PCI-Express example](#)

The OpenVox A400E is a PCI Express analog card. The A400E delivers great voice quality for telephony systems. The OpenVox A400E is designed to be fully compatible with the TDM400P Asterisk Analog Telephony card. Key Features and benefits of the OpenVox A400E

- Up to 4 ports through a combination of FXS and FXO modules
- Caller ID and Call Waiting Caller ID
- ADSI Telephones
- Loopstart Signaling Support
- Up to 4 Simultaneous PSTN Calls
- Scalable: Just add additional cards to extend the system.

OpenVox A400E delivers great voice quality in the telephony systems. With interchangeable FXS/FXO modules, it can eliminate the requirement for separate channel banks or access gateways. The OpenVox A400P contains 4 module banks. Each bank supports one analog interface. The module banks may be filled with up to 4 FXO or FXS modules enabling the creation of any combination of ports. Scaling of an analog card solution is accomplished by simply adding additional cards.

### Technical Specifications

- Up to 4 ports through a combination of FXS and FXO modules
- 4 RJ-11 interfaces on a single PCI bracket
- 32 bit 33MHz PCI and fully PCI 2.2 compliant
- 32 bit bus master DMA data exchanges across PCI interface at 132 Mbytes/sec
- Autosense compatibility with 5 V and 3.3 V PCI busses compatible
- Firmware accelerate I/O access to achieve high stability

### Power

- 2.77W Minimum, 11.6W Maximum

### Operation temperature

- 0°C to 50°C

### Storage temperature

- -40°C to 125°C

## OpenVox A400E PCI Express Asterisk Card

### Interface

1x PCI-E

### Dimension

1x 136.3mm\*111.5mm\*16mm

### Minimum Hardware Requirement

1x 800-Mhz Pentium III

1x 128MB RAM

### Operating Systems

1x Linux (all versions, releases and distributions from 1.0 up)

### Certifications

1x RoHS Compliant

1x Certificates: FCC, CE and LVD

### Weight

1x 88g

### Please Enquire

Options available for OpenVox A400E PCI Express Asterisk Card :

#### Module 1

[OpenVox FXS-100 Module \(+£42.94\)](#), [Not Required](#), [OpenVox FXO-100 Module \(+£42.94\)](#).

#### Module 2

[OpenVox FXO-100 Module \(+£42.94\)](#), [OpenVox FXS-100 Module \(+£42.94\)](#), [Not Required](#).

#### Module 3

[OpenVox FXO-100 Module \(+£42.94\)](#), [OpenVox FXS-100 Module \(+£42.94\)](#), [Not Required](#).

#### Module 4

[OpenVox FXO-100 Module \(+£42.94\)](#), [OpenVox FXS-100 Module \(+£42.94\)](#), [Not Required](#).