Created on: Thursday 14 August, 2025



Snom M15 SC DECT Phone

O.	
1 - 2 - 2 - 4 - 3 - 4 - 2 - 3 - 4 3 - 4 	
NOT	

Product Name: Snom M15 SC DECT Phone Manufacturer: -Model Number: M15SC-UK

Please Note: This product has been discontinued. For an alternative, please see the other Snom Wireless IP Phones.

Snom M15 SC DECT Phone

The Snom M15 SC is a high-performance, cordless DECT VoIP phone to be used with single-cell bases. This modern DECT telephone is easy to use and perfect for everyday business needs. With a wide 1.7 inch panoramic display, illuminated keypad, and excellent voice transmission, the snom M15 SC is a hardworking device with numerous functions. Snom M15 SC Key Features

� Up to 7 days battery life in stand-by and 7 hours talk time
� Voicemail LED notification light
� Illuminated keypad
� Integrated belt clip
� 2.5mm headphone jack
� GAB compatible

The snom M15 SC is the perfect choice for small/home offices as it meets all the requirements of the modern day working environment at an affordable price. Snom M15 SC - Technical Specifications Hardware

ï¿¹/₂ Backlit graphic LCD display 90 x 65 pixels

ï¿1/2 2.5mm headphone jack wire

ï¿1/2 Speakerphone

ï¿1/2 Up to 7 days battery life in stand-by

ï¿1/2 Up to 7 hours talk time

ï¿1/2 Voicemail LED notification light

ï¿1/2 Illuminated keypad

ï¿1/2 Integrated belt clip

Features

ï¿1/2 Call history lists

- ï¿1/2 Local directory and network
- � Call forwarding

ï¿1∕2 Call divert

ï¿⅓ Hold function

i¿1/2 Intercom function between cordless devices connected to the M200 SC base

ï¿1∕₂ Mute function

 \ddot{i}_{2} Up to 10 numbers with speed dial

ï¿1/2 Range up to 50 m indoors

 $\ddot{\imath} \grave{\imath} \rlap{k} 2$ Compatible with GAB bases

ï¿1/2 Over-the-air software updates

Interoperability

ï¿1/2 Broadsoft® BroadWorks

ï¿1/2 Asterisk based platforms



Snom M15 SC DECT Phone

� Metaswitch networks

ï¿1/2 Genband™

Specifications

- ï¿1/2 Dimensions: 174 x 49 x 31 mm
- ï¿1/2 Batteries: 2.4V / 550 mAh Ni-MH
- ï¿1/2 Input voltage: 6V
- ï¿1/2 Wall mountable charger base
- ï¿1/2 Acoustic device supports (HAC)
- ï¿¹/₂ Environmental conditions:

ï¿¹/₂ Operating temperature: from -5°C to 45°C

- i¿1/2 Non-operating temperature: from -5°C to 60°C
- ï¿1/2 Humidity: up to 95% (non-condensing)

ï¿1/2 Included in the package:

� Cordless M15 SC � Charger base � Wire for charger base � Batteries � Quick start guide (QIG)

ï¿1/2 Colour: Black ï¿1/2 Manufacturer warranty: 2 years

Compliance

ï¿1⁄2 CE Marking ï¿1∕2 IEC60950 safety

Protocols

i¿½ SIP (RFC3261) i¿½ DHCP, NTP i¿½ HTTP / HTTPS / TFTP i¿½ LDAP (Directory) i¿½ Dual Stack IPv4 / IPv6

Compatibility

�

Comprehensive features only in conjunction with the M200 SC base station

Please Enquire



Snom M15 SC DECT Phone

Options available for Snom M15 SC DECT Phone :

Need Product Setup / Training / Support?

Required - 30 minutes (+£40.00), Not Required, Required - 1 Hour (+£65.00).