

Grandstream GVC3210 Video Conferencing Endpoint



Product Name: Grandstream GVC3210 Video Conferencing Endpoint

Manufacturer: Grandstream

Model Number: GVC3210

Grandstream GVC3210 Video Conferencing Endpoint

The Grandstream GVC3210 is an innovative video conferencing endpoint ideal for small to medium businesses who seek an easy-to-use yet powerful video conferencing solution. By supporting top-tier video resolutions up to 4K Ultra HD, the Grandstream GVC3210 turns any video conference into a powerful, clear, enhancing experience.

Grandstream GVC3210 Key Features

- Sharp HD video resolutions up to 4k Ultra HD
- Built-in Bluetooth for use with Bluetooth speakers/ microphones, keyboards, data exchange, etc.
- Integrated dual band WiFi to pair with video and web conferencing service
- Built-in 4-MIC array with beam-forming, support for external audio equipment and innovative Noise Shield technology
- Advanced camera with 16M pixel CMOS sensor, 90 FOV wideangle lens and ePTZ for easy camera view adjustments
- Integrated 1x HDMI in, 2x HDMI out, and 2x USB

Designed to allow users to customise their solution according to their specific communication needs, the Grandstream GVC3210 can be paired with most video and web conferencing services to create a fully-featured multi-point conferencing system. Compatible with Major SIP-Based Platforms This powerful yet easy-to-use video conferencing device works with many third-party SIP-based platforms, including Broadsoft and Asterisk, and runs on the Android operating system, allowing use of popular applications such as Skype and Google Hangouts.

Grandstream GVC3210 - Technical Specifications

General

- Protocols / Standards: SIP RFC3261, BFCP, TIP, RTP/RTCP, HTTP/HTTPS, ARP, ICMP, DNS (A record, SRV, NAPTR), DHCP, PPPoE, SSH, TFTP, NTP, STUN, LLDP-MED, LDAP, TR-069 (pending), 802.1x, TLS, SRTP, TCP/IP/UDP, IPv6, H.323
- Camera: 1/2.3" and 16 Megapixel CMOS, 4K (2160p) Output
- Lens: 90° field of view, ePTZ
- Network Interface: 1 × RJ45 10/ 100/ 1000 Mbps
- WiFi: Integrated dual-band 802.11 a/b/g/n/ac (2.4GHz & 5GHz)
- Bluetooth: Integrated Bluetooth 4.0 + EDR
- Video Outputs: 2x HDMI 1.4 up to 4K (2160p) with CEC
- Video Input: 1x HDMI 1.4 with resolution up to 1080p
- MIC/Speaker: Built-in 4x MIC array
- Remote Control: Bluetooth and infrared remote control with multi-touch touchpad
- Auxiliary Ports: 2x USB 2.0, micro-SD, Reset
- Voice Codecs: Support for G.711 μ-law, G.722 (wide-band), iLBC, Opus, G.722.1, G.722.1c, G.729A/B, in-band and out-of-band DTMF (In audio, RFC2833, SIP INFO)
- Video Codecs: HEVC(H.265) and H.264 BP/MP/HP, video resolution up to 4K (2160p), frame rate up to 30 fps, bitrate up to 16Mbps
- Video Resolutions: 4K (2160p@30fps) from 4096Kbps, 1080p@30fps from 1024Kbps, 720p@30fps from 512 Kbps, 4SIF/4CIF from 128 Kbps, SIF/CIF from 64 Kbps
- 4K Capability:
 - 1. When the GVC3210 is using 4K resolution during video call, EPTZ is not supported. The GVC3210 supports 90° field of view. Please install GVC3210 at the position that suits the best conference view if you plan to use 4K resolution.
 - 2. When the GVC3210 is using 4K resolution, local recording is not supported.

Grandstream GVC3210 Video Conferencing Endpoint

- 3. When the GVC3210 is using 4K resolution, HDMI Out Port 2 is not supported. Users can only use HDMI Out Port 1 for one display.

- Content Resolutions (screen sharing):

- Input: VGA, SVGA, XGA, 1280×600, WXGA, WXGA, SXGA, 1440×900, XGA+, 720p, 1600×1200, 1080p (HDMI), up to 60fps

- Encoding: 800×600, 1024×768, 1280×1024, 1280×720, 1920×1080

- Output: 720p, 1080p

- Dual-Stream: BFCP, video resolution (up to 4K 2160p@30fps) + content resolution (up to 1080p@15fps)

- Audio Features: AEC, ANS, AGC, Noise Shield, PLC, CNG/VAD

- Video Features: FEC, dynamic display layout, picture-in-picture, picture-outside-picture, digital caption

- Telephony Features: Hold, forward (unconditional/no-answer/busy), downloadable phone book (XML, LDAP), call waiting, call history, flexible dial plan, personalised music ringtones, server redundancy & fail-over

- Sample Applications: Skype, Google Hangouts, Microsoft Lync, Web browser, Adobe Flash, Facebook, Twitter, YouTube, Google calendar, mobile phone data import/export via Bluetooth, etc. API/SDK available for advanced custom application development

- Applications Deployment: Allow various Android operation system 6.0 compliant applications to be developed, downloaded and run in the embedded device with provisioning control

- QoS: Layer 2 QoS (802.1Q, 802.1p) and Layer 3 (ToS, DiffServ, MPLS) QoS

- Security: User and administrator level passwords, MD5 and MD5-sess based authentication, 256-bit AES encrypted configuration file, TLS, 128/256-bit SRTP, HTTPS, 802.1x media access control

- Multi-Language: English, German, Italian, French, Spanish, Portuguese, Russian, Turkish, Polish, Chinese, Korean, Japanese, and more

- Upgrade/Provisioning: Firmware upgrade via TFTP / HTTP / HTTPS or local HTTP upload, mass provisioning using AES encrypted XML configuration file

- Power & Green Energy Efficiency: Input - 100~240Vac 50/60hz; output - 12V/2A 24W

- Package Content: GVC3210 video conference endpoint, remote control, 4 AAA batteries, universal power supply, network cable (1.5 meters), 2 HDMI cables (1.5-meter and 5-meter), lens cleaning cloth, mounting kit, quick installation guide, GPL license

- Dimensions: 80mm (H) x 46.5mm (W) x 270mm (L)

- Temperature and Humidity: Operation- 0°C to 40°C, Storage: -10°C to 60°C, Humidity- 10% to 90% Non-condensing

- Compliance:

- FCC: FCC Part 15B; FCC Part 15C; FCC Part 15E; UL 60950 (power adapter)

- CE: EN 55032; EN 55024; EN 61000-3-2; EN 61000-3-3; EN 60950-1; EN 301 489-1/17; EN 300 328; EN 301 893; EN 62311; EN 62479; RoHS

- RCM: AS/NZS C

Price: £608.00