

# Polycom VVX D60 DECT Wireless Handset & Base Station



Product Name: Polycom VVX D60 DECT Wireless Handset & Base Station

Manufacturer: -

Model Number: 2200-17821-015

Please Note: This item has been discontinued. See the Poly VVX D230 for an alternative.

Polycom VVX D60 DECT Wireless Handset & Dec Station

The Polycom VVX D60 DECT Wireless Handset & December 2015. Station is an ideal solution for small businesses, retail environments, and administrative staff that are required to work while on the move. The VVX D60 DECT solution offers the same SIP features as the VVX desk phones, making it incredibly practical for any business.

Polycom VVX D60 DECT Wireless Handset & Base Station Key Features

� SIP Protocol support

า๊¿½ High-resolution colour display with HD voice quality

� Multiple lines support - 5 Lines per handset

� Up to 5 registered phones per base station

آذِر Voice Range: 50m (165ft) indoor/ 300m (980ft) outdoor

آزا 10 hours talk time, 100 hours standby time

The VVX D60 DECT solution can allow up to 4 concurrent calls when 5 Polycom VVX D60 handsets are registered to the VVX D60 base station. Each Polycom VVX D60 handset also features multiple line support, offering a flexible, fully-featured solution that is suitable for any environment.

Polycom VVX D60 DECT Wireless Handset & Station - Technical Specifications Included

� VVX D60 wireless handset

� VVX D60 wireless base station

� Network (LAN) cable

� Wireless handset belt clip

าั¿1/2 Wireless handset 2.5 mm to 3.5 mm headset adapter

� Battery pack

� Quick start guide

� Power adapter

## Handset User Interface Features

12.1/2 2 in color TFT LCD display (resolution 178 x 220 pixel)

� Voicemail support

� Unicode UTF-8 character support

T¿½ Multilingual user interface including: Chinese, Danish, Dutch, English (Canada/US/UK), French, German, Italian, Japanese, Korean, Norwegian, Polish, Portuguese, Russian, Slovenian, Spanish and Swedish

#### Handset Audio Features

าั¿½ Full-duplex conversations, acoustic echo cancellation and background noise suppression

� Frequency response – 150 Hz – 7 kHz for handset, optional headset and handsfree speakerphone models

آذِيً Narrowband Codecs: G.711 (A-law andμ-law), G.729AB

� Wideband Codec: G.722

ī¿½ Individual volume settings with visual feedback for each audio path



# Polycom VVX D60 DECT Wireless Handset & Base Station

- 12.1/2 Voice activity detection
- � Comfort noise generation
- าั¿½ DTMF tone generation (RFC2833, in-band and SIP INFO)
- � Low-delay audio packet transmission
- ï¿1/2 Adaptive jitter buffers
- ï¿1/2 Packet loss concealment

## Handset Call Handling Features

- i¿½ Multiple Lines Support for Handsets (5 lines per HS)
- � Up to 4 simultaneous calls
- � Up to 5 handsets
- ï¿1/2 Shared call/ bridged line appearance
- า๊¿½ Distinctive incoming call treatment/call waiting
- � Call timer and call waiting
- تز1/2 Call transfer, hold, divert (forward), pickup
- � Called, calling, connected party information
- � Local 3-way audio conferencing
- � 1-touch speed dial, redial
- � Remote missed call notification
- � Do not disturb function
- ï¿⅓ Intercom

# Headset and Handset Compatibility

- ï¿1/2 Dedicated 2.5 mm headset port
- آذِ 1/2 External 2.5 mm to 3.5 mm headset adapter
- تزير Compliant with ADA Section 508 Subpart B1194.23 (all)
- ī¿½ Hearing aid compatible handset for magnetic coupling to hearing aids

## Handset Power

า๊¿½ (Separate) External universal AC adapter (5V 6W DC)

# Handset Battery

- تزير 1 Ni-MH 800 –mAh (2.4V) AAA battery (rechargeable)
- � 10 hours talk time
- ï¿1/2 100 hours standby time

#### Range

� Indoor: 165ft (50m) � Outdoor: 980ft (300m)

# Security

- าั¿1/2 802.1X authentication and EAPOL
- � Media encryption via SRTP
- � Transport layer security
- 12.1/2 Encrypted configuration files
- � Digest authentication
- � Password login
- آذِرُ Support for URL syntax with password for boot server address
- ï¿⅓ HTTPS secure provisioning



# Polycom VVX D60 DECT Wireless Handset & Base Station

## � Support for signed software executables

### Frequency

Ϊ¿½ 1920-1930 MHz

ï¿⅓ 1880-1900 MHz

ï¿⅓ 1880-1895 MHz

� 1896-1903 MHz

ï¿1/2 1910-1920 MHz (post FCS)

ϊ¿½ 1921-1930 MHz (post FCS)

ī¿½ 1786-1791 MHz (post FCS) investments - deploy VVX D60 business media phones on your existing network without needing to upgrade your call control platform

### Size

 $i \gtrsim \frac{1}{2}$  Base station size: 6.3 x 2.75 x 5.0 in (16 x 7 x 12.5 cm) (W x H x D)

� Handset size: 2 x 6.7 x 1 in (5 x 17 x 2.5 cm) (W x H x D)

� Handset charger size: 3.75 x 2.20 x 3.35 in (9.5 x 5.5 x 8.5 cm) (W x H x D)

### **Operating Conditions**

ī¿½ Temperature: 0 to 40°C (+32 to 104°F)

تزير Relative humidity: 25% to 90%, noncondensing

� Storage Temperature: -40 to +65 °C (-40 to +149°F)

Price: £184.50

Options available for Polycom VVX D60 DECT Wireless Handset & Base Station:

## **Power Supply Required?**

Required (+£15.60), Not Required.