

Yealink W41P DECT Desk Phone



Product Name: Yealink W41P DECT Desk Phone Manufacturer: -Model Number: W41P

Please Note: This product is end of life. For an alternative, see the Yealink DECT Phones.

Yealink W41P DECT Desk Phone The Yealink W41P is a great complement to businesses who have or need Yealink DECT solution. Key Features

ï¿1/2 DECT Technology

ï¿1/2 2.7" 192x64-pixel graphical LCD with backlight

- ï¿1/2 HD voice: HD handset, HD speaker
- ï¿1/2 4 context-sensitive "soft" keys
- ï¿1/2 15 paperless DSS key
- ï¿1/2 5 features keys: message, headset, mute, redial, hands-free speakerphone
- � 6 line keys with LED
- ï¿1/2 Compatible with Yealink DECT IP base station
- ï¿1/2 Headset, EHS support

The W41P DECT Desk Phone is equipped with 2.7" 192x64-pixel graphical LCD with backlight, offering you an intuitive visual experience. It offers HD and crystal clear audio, making your conversation as natural and vivid as communication should be.

Yealink DECT Solution Ecosystem

The Yealink DECT phone solution enhances communication productivity and flexibility for on-the-move employees in various business segments. The W41P is a package of T41S, W60B and DECT dongle DD10K; it offers the user a delightful interface and exceptional HD voice quality in addition to the ease of deployment that reduces IT department workload. It's time to equip your office with Yealink's scalable, feature-rich and HD DECT IP phone solution so that you can enjoy absolute flexibility in your business communications. Yealink W41P - Technical Specifications Audio Features

ï¿1/2 HD voice: HD handset, HD speaker

ï¿1/2 Hearing aid compatible (HAC) handset

� DTMF

ï¿1/2 Full-duplex hands-free speakerphone with AEC

- ï¿1/2 Wideband codec: Opus, AMR-WB (optional), G.722
- ï¿1/2 Narrowband codec: PCMU, PCMA, G.723, G.726, G.729, iLBC

Phone Features

- ï¿1/2 Up to 2 simultaneous calls per handset
- � Intercom
- ï¿1/2 Switching between calls
- ï¿1/2 Speed dial, voicemail, silence
- ï¿1/2 Local phonebook up to 800 entries (store in the base)
- ï¿1/2 Keypad lock
- � Redial
- ï¿1/2 Call forward
- � Call waiting
- ï¿1/2 Call transfer



Yealink W41P DECT Desk Phone

� Call hold

� Mute

ï¿¹/₂ DND3-way conference call

ï¿1/2 Direct IP call without SIP proxy

ï¿1/2 Ring tone selection

ï¿1/2 Emergency call

ï¿1/2 Set date time manually or automatically

ï¿1/2 Dsskey: Line, SpeedDial, Retrieve Park

ï¿1/2 Visual voice mail

ï¿1/2 Anonymous call, anonymous call rejection

Directory

i¿1/2 Black list i¿1/2 XML/LDAP remote phonebook i¿1/2 Call history: dialed/received/missed

Display and Indicator

ï¿1/2 2.7" 192x64-pixel graphical LCD with backlight

 $i_{i_{1}}i_{2}$ LED for call and message waiting indication

ï¿1/2 Notification Light: voice mail and missed call is signaled via display and illuminated power indicator

i¿1/2 Dual-color (red or green) illuminated LEDs for line status information

ï¿1/2 Multilingual user interface

Feature keys

ï¿1/2 6 line keys with LED

ï¿1/2 6 line keys can be programmed up to 15 paperless DSS keys (3-page view)

ï¿1/2 5 features keys: message, headset, mute, redial, hands-free speakerphone

ï¿1/2 4 context-sensitive "soft" keys

- ï¿1/2 6 navigation keys
- ï¿1/2 2 volume control keys

ï¿1/2 Illuminated mute key

ï¿1/2 Illuminated headset key

ï¿1/2 Illuminated hands-free speakerphone key

Interface

 $i \downarrow 2 \times RJ45 10/100M$ Ethernet ports $i \downarrow 2 \times RJ45 10/100M$ Ethernet ports $i \downarrow 2$ Power over Ethernet (IEEE 802.3af), Class 2 $i \downarrow 2 \times I \times USB$ port (2.0 compliant, connected to DD10K) $i \downarrow 2 \times RJ9$ (4P4C) handset port $i \downarrow 2 \times RJ9$ (4P4C) headset port

Other Physical Features

� Colour: Classic Grey

ï¿1/2 Stand with 2 adjustable angles

ï¿1/2 Wall mountable

ï¿1/2 External Yealink AC adapter (optional): AC 100~240V input and DC 5V/1.2A output

 $\ddot{\imath}_{{\dot{c}}}{}^{1\!\!/_{\!\!2}}$ Power consumption (PSU): 1.3-3.0W

ï¿1/2 Power consumption (PoE): 1.7-3.8W

ï¿1/2 Dimension (W*D*H*T): 212mm*189mm*175mm*54mm



Yealink W41P DECT Desk Phone

� Operating humidity: 10~95% � Operating temperature: -10~50°C (+14~122°F)

Management

i¿1/2 Phone lock for personal privacy protection i¿1/2 Reset to factory, reboot

DECT

� Frequency bands:- 1880 – 1900 MHz (Europe)- 1920 – 1930 MHz (US)
� DECT Standards: CAT-iq2.0
� DECT Phone upgrade: Over-The-Air (only supported when connected to W60B)
� DECT Range: - 50 meters indoor - 300 meters outdoor

Package Features

i¿½ Package content:- W60B Base Station- Two Stands (one for W60B, the other for T41S)- Two Power Adapters (one for W60B, the other for T41S)- Two Ethernet Cables- Quick Start Guides (W60B/T41S/DD10K)- DD10K DECT Dongle- Yealink SIP-T41S IP phone- Handset with handset cord- Wall Mount Bracket (Optional) i¿½ Qty/CNT: 4 PCS i¿½ Giftbox size: 228mm*195mm*257mm i¿½ Carton meas: 470mm*407mm*268mm i¿½ N.W: 7.4 kg i¿½ G.W: 8.5 kg

Please Enquire

Options available for Yealink W41P DECT Desk Phone :

Power Supply Required?

UK-PSU-5V-2A (+£6.30), Not Required.

Need Product Setup / Training / Support?

Required - 1 Hour (+£65.00), Required - 30 minutes (+£40.00), Not Required.

Wired Headset

YHS34-LITE-MONO (+£17.90), YHS34-MONO (+£19.40), Not Required, YHS34-DUAL (+£28.70).

Wireless Headset

WH62-MONO (+£114.40), WH62-DUAL-TEAMS (+£115.60), Not Required.