

Draytek Vigor 2762ac ADSL or VDSL Router/Firewall with WiFi 802.11ac (V2762AC-K)



Product Name: Draytek Vigor 2762ac ADSL or VDSL Router/Firewall with WiFi 802.11ac (V2762AC-K)
Manufacturer: -
Model Number: V2762AC-K

Please Note: This product has been discontinued. Please see the Draytek Router range.

Draytek Vigor 2762ac ADSL or VDSL Router/Firewall with WiFi 802.11ac (V2762AC-K)
The Draytek Vigor 2762ac is an ADSL/VDSL2, Ethernet, or 3G/4G router, that is ideal for small/home office deployments. It provides connectivity to your PCs or other Internet-connected devices (laptops, tablets, games consoles, smartphones) via its 4 built-in Gigabit Ethernet ports, or using Wireless LAN (on 'n' & 'ac' models).
Draytek Vigor 2762ac Key Features

- Supports VDSL2, ADSL, and Ethernet-based Broadband
- Four Gigabit LAN Ethernet Port
- DrayTek Firewall with huge flexibility
- Content Filtering (by keyword, data type or category)
- Centrally Managed by VigorACS
- IPv4/IPv6 Dual-Stack

Comprehensive FirewallThe DrayTek object-based firewall feature allows even more setup flexibility than ever, enabling you to create combinations of Firewall rules and Content Filtering to the whole network, only specified devices, or just the network that guests can connect to. The Vigor 2762ac also allows selective direction firewall rules of LAN to WAN, WAN to LAN or LAN to VPN.
Next Generation Internet RoutingThe Vigor 2762ac supports IPv6 - the successor to the current IPv4 addressing system that has been used since the Internet was first created. The advanced networking features of the Vigor 2762ac, such as the object-based Firewall, Quality of Service, Content Filtering, and VLANs, support both IPv4 and IPv6 networks.
Draytek Vigor 2762ac - Technical Specifications
Physical Interfaces

• LAN Ports (Switch):

• 4 X Gigabit Ethernet (1000Mb/s) Ports LAN Port 4 Switchable with WAN2

• WAN Ports:

- WAN1 : ADSL/VDSL, RJ11
- WAN2 : Gigabit Ethernet (1000Mb/s) Ethernet
- WAN3 : 3G/4G Modem (not supplied) via USB 2.0 Port

Performance

- Firewall: Up to 300Mb/s max
- IPSec VPN: Up to 60Mb/s max
- NAT Sessions: 50,000

Wireless LAN Features ('n' and 'ac' Models Only)

Draytek Vigor 2762ac ADSL or VDSL Router/Firewall with WiFi 802.11ac (V2762AC-K)

- 802.11g/b/n and 802.11ac (Vigor 2762ac only)
- Backward Compatibility for 802.11b/g
- Wireless Features on Vigor 2762ac:

- 802.11a
- 802.11ac (5Ghz)
- 2x2 SU-Mimo (5Ghz)
- Up to 2 Spatial Streams
- 866Mb/s Link Rate (5Ghz) + 300Mb/s (2.4Ghz)
- Dual-band (2.4/5Ghz) simultaneous wireless
- Extended DFS frequency range

- Multiple SSID : Create up to 4 virtual wireless LANs (independent or joined)
- Switchable Hidden SSID
- Restricted access list for clients (by MAC address)
- Time Scheduling (WLAN radio can be disabled at certain times of day)
- Time Scheduling for individual SSIDs
- Active Client list in Web Interface
- Wireless LAN Isolation (from VLAN groups and wired Ethernet interfaces)
- Station Control, limit wireless client access time per day
- Wireless Rate-Control
- Airtime Fairness
- Band Steering
- Wireless Router-assisted Client Mobility
- 64/128-bit WEP Encryption
- WPA/WPA2 Encryption
- Packet Aggregation and Channel Bonding
- Access Point Discovery
- WDS (Wireless Distribution system) for WLAN Bridging and Repeating
- Wireless LAN On/Off button
- 802.11e WMM (Wi-Fi Multimedia)
- Optional Higher Gain or directional aerials available

Firewall & Security Features

- CSM (Content Security Management):

- URL Keyword Filtering - Whitelist or Blacklist specific sites or keywords in URLs
- Block Web sites by category (e.g. Adult, Gambling etc. Subject to subscription)
- Prevent accessing of web sites by using their direct IP address (thus URLs only)
- Blocking automatic download of Java applets and ActiveX controls
- Blocking of web site cookies
- Block http downloads of file types :

- Binary Executable : .EXE / .COM / .BAT / .SCR / .PIF
- Compressed : .ZIP / .SIT / .ARC / .CAB/ .ARJ / .RAR
- Multimedia : .MOV / .MP3 / .MPEG / .MPG / .WMV / .WAV / .RAM / .RA / .RM / .AVI / .AU

- Time Schedules for enabling/disabling the restrictions
- Block popular P2P (Peer-to-Peer) file sharing programs

Draytek Vigor 2762ac ADSL or VDSL Router/Firewall with WiFi 802.11ac (V2762AC-K)

ï½ Block Instant Messaging programs (e.g. IRC, Skype/Yahoo Messenger etc.)

ï½ DNS Filter: Use DNS to enforce categorisation

ï½ DMZ Host

ï½ 40 Port Redirection rules

ï½ 40 Open Port rules (10 port ranges per rule)

ï½ Policy-Based Firewall

ï½ MAC Address Filter

ï½ SPI (Stateful Packet Inspection) with FlowTrack Mechanism

ï½ DoS / DDoS Protection

ï½ IP Address Anti-spoofing

ï½ E-Mail Alert and Logging via Syslog

ï½ Bind IP to MAC Address

Bandwidth Management

ï½ Temporary (5 minute) Quick Blocking of any LAN Client

ï½ Bandwidth Limit (Shared or individual limit)

ï½ Smart Bandwidth Limitation (Triggered by Traffic / Session)

ï½ Session Limit

Quality of Service (QoS)

ï½ Guaranteed Bandwidth for VoIP

ï½ Class-based Bandwidth Guarantee by User-Defined Traffic Categories

ï½ Layer 2&3 (802.1p & TOS/DCSP)

ï½ DiffServ Code Point Classifying

ï½ 4-level Priority for each Direction (Inbound / Outbound)

ï½ Bandwidth Borrowing

ï½ App QoS: Classify traffic by Application

ï½ Automatic prioritisation of SIP/RTP Voice over IP (VoIP)

LAN-to-LAN Dial-Out VPN Facilities

ï½ 2 Concurrent active VPN Tunnels

ï½ Tunnelling Protocols:

ï½ PPTP

ï½ IPsec

ï½ L2TP

ï½ L2TP over IPsec

ï½ DrayTek SSL

ï½ IPsec Main and Aggressive modes

ï½ IKE Phase 1 Diffie-Hellman Groups 1,2,5 & 14

ï½ IKE Phase 2 Diffie-Hellman Groups 1,2,5 & 14 (will match phase 1 selection)

ï½ IPsec IKEv1 & IKEv2

ï½ Encryption : MPPE, DES / 3DES (168bits) and Hardware-Based AES (128/192/256bits)

ï½ Authentication : Hardware-Based MD5, SHA-1 and SHA-256

ï½ IKE Authentication : Pre-shared Key or X.509 Digital Signature

ï½ NAT-Traversal (NAT-T)

Draytek Vigor 2762ac ADSL or VDSL Router/Firewall with WiFi 802.11ac (V2762AC-K)

- Dead Peer Detection (DPD)
- VPN Pass-Through
- Virtual IP Mapping, map a remote IP subnet/range to another range to resolve IP subnet/range conflicts

Teleworker Dial-In SSL VPN Facilities

- 2 Concurrent active VPN
- Tunnels Tunneling Protocols:

- DrayTek SSL

- MOTP (Mobile One Time Password) for two factor authentication (2FA)
- Free DrayTek Smart VPN Client software available for Windows, Android, macOS & iOS

Network Features

- 2 LAN (IPv4 & IPv6) Subnets
- LAN Clients : Up to 253 per subnet
- Multi Subnet DHCP Servers with DHCP Relay
- Port-Based VLAN (Inclusive/Exclusive Groups)
- 802.1q VLAN Tagging
- Custom DHCP Option support
- Port Mirroring
- Dynamic DNS
- DNSSEC support
- DNS Transparent Proxy
- DNS Caching
- LAN DNS (supports CNAME)
- NTP Client (Synchronise Router Time)
- Microsoft®; UPnP Support
- Maximum MTU 1534

Network/Router Management

- Web-Based User Interface (HTTP / HTTPS)
- CLI (Command Line Interface) / Telnet / SSH
- Web Console: Access CLI through Web Interface
- Administration Access Control
- Configuration Backup / Restore
- Configuration Import from Vigor 2760
- Built-in Diagnostic Function
- Firmware Upgrade via Web Interface, TFTP, VigorACS
- Logging via Syslog
- SNMP v2 & v3 Management with MIB-II
- TR-069
- TR-104
- Access Point Management: Centrally Manage 2 DrayTek VigorAP wireless access points

WAN Failover Features

- WAN Connection Fail-over

Draytek Vigor 2762ac ADSL or VDSL Router/Firewall with WiFi 802.11ac (V2762AC-K)

• WAN1 PPPoE/PPPoA Fallback account, used if the primary details are unable to establish a working connection

• WAN Budget - gives notification or switches to failover WAN interface if data usage quota exceeded

WAN Protocols

• DHCP Client

• Static IP

• PPPoE

• PPTP/L2TP (Ethernet WAN only)

ADSL & VDSL Compatibility

• BT Infinity Option 1 & Option 2 Compatible

• BT SIN 498 MCT Approved

• Support for G.INP & Vectoring

• ADSL Standards:

• ANSI T1.413 Issue2

• ITU-T G.992.1 G.dmt (ADSL)

• ITU-T G.992.2 G.lite

• ITU-T G.992.3 ADSL2

• ITU-T G.992.5 ADSL2+

• Annex L (READSL)

• Annex A

• Annex M

• ANFP Issue 3 Compliant/Certified (for Annex A & Annex M)

• DSL Forum : TR-048/67 & TR-100

• VDSL Standards:

• ITU-T VDSL2 G.993.2

• ITU-T G.993.1, G.997.1

• Band Plan: G.998, G.997

• Annex A, Annex B, Annex C

• VDSL2 Profile: 8a, 8b, 8c, 8d, 12a, 12b, 17a, 30a

• OLR, UPBO, DPBO Supported

• US0 Supported

• Loop Diagnostic Mode

• DSL Forum WT-114

• ATM Protocols:

• RFC-2684/RFC-1483 Multiple Protocol over AAL5

• RFC-2516 PPP over Ethernet

• RFC-2364 PPP over AAL5

• PPPoE pass through LAN/WLAN

• PPPoE/PPPoA Relay

• Transparent bridge for MPoA

• Multiple PVC support for Triple Play Applications (up to 8 simultaneous)

Draytek Vigor 2762ac ADSL or VDSL Router/Firewall with WiFi 802.11ac (V2762AC-K)

• Support for RFC4638 for MTU up to 1500

Operating Requirements

• Wall Mountable

• Operating Temperature : 0°C ~ 45°C

• Storage Temperature : -25°C ~ 70°C

• Humidity 10% ~ 90% (non-condensing)

• Power Consumption: 24 Watt Max.

• Dimensions: Length: 207mm, Width: 131mm, Height: 39mm

• Weight: 440g (without antenna)

• Operating Power: DC 12V (via external PSU, supplied)

• Power Requirements : 220-240VAC

Price: Â£143.20
