

Netgear ProSafe GSM7212F-100NES - M4100-12GF Managed Switch



Product Name: Netgear ProSafe GSM7212F-100NES - M4100-12GF Managed Switch

Manufacturer: -

Model Number: GSM7212F

Please Note: This product has been discontinued. For an alternative, please see the other Netgear Routers and Switches.

Netgear ProSafe M4100-12GF Managed Switch

The Netgear ProSafe M4100-12GF Managed Switch is ideal for all organisations considering reliable, affordable and simple access layer switching with CLI, advanced scripting capabilities and Layer 3 routing. Netgear ProSafe M4100-12GF Managed Switch Key Features

- 1/2 Port-based/ VLAN-based/Subnet-based "static routing" Layer 2+ versions

- 1/2 12 x SFP version for aggregation, Layer 2+

- 1/2 12 shared 1000Base-T

- 1/2 Internal PSU with RPS

- 1/2 4 ports PoE+ with 150W budget

As a cost-effective component of converged voice, video and data networking solutions, the M4100-12GF delivers a secure edge in commercial buildings and campus LAN environments: The M4100-12GF is perfect for Wireless access points, IP telephony and IP surveillance deployments. Layer 2+ with static routing

M4100-12GF comes with Port-based / VLAN-based / Subnet-based "static routing" Layer 2+ versions and L3 fixed routes to the next hop towards the destination network are added to the routing table and the L3 routing is wire-speed in M4100 series hardware with 64 static routes (IPv4).

Engineered for convergence

The Automatic multi-vendor Voice over IP prioritisation is based on SIP, H323 and SCCP protocol.

They also have Voice VLAN and LLDP-MED for automatic IP phones QoS and VLAN configuration and Advanced classifier-based hardware for L2, L3, L4 security and prioritisation. In addition, M4100-12GF includes Advanced Multicast filtering with IGMP and MLD snooping and querier modes.

High-value performance and IPv6 ready

The M4100-12GF features 16K MAC addresses; up to 100Gbps switching fabric; 9K jumbo frames; Green Ethernet as well as IPv4/IPv6 ingress traffic filtering (ACLs) and prioritization (QoS - DiffServ).

Netgear ProSafe M4100-12GF Managed Switch - Technical Specification

Physical Interfaces

- 1/2 Auto-sensing RJ45 10/100/1000: 12

- 1/2 Auto-sensing SFP ports 100/1000Base-X: 12 (shared)

- 1/2 Console port (selectable): Mini-USB

- 1/2 Storage Port: 1 z USB Firmware, Configuration Files

- 1/2 Power Supply: Fixed, internal

- 1/2 RPS/ EPS connector: 1

- 1/2 Console port (selectable): Serial RS232 DB9

- 1/2 1 Kensington Lock Slot

- 1/2 Gigabit: 12 ports total

Power over Ethernet

Netgear ProSafe GSM7212F-100NES - M4100-12GF Managed Switch

• PoE+ ports 802.3at: 4
• Internal PoE budget: 150W
• IEEE 802.3at (up to 30W per port)
• IEEE 802.3at Layer 2 (LLDP) method
• IEEE 802.3at 2-event classification

Processor/ Memory

• Processor (CPU): Broadcom BCM53003 @ 600MHz
• System memory (RAM): 123MB
• Code storage (flash): 32 MB, Dual firmware image, dual configuration file
• Packet Buffer Memory: 12 MB, Dynamically shared across only used ports

Performance Summary

• Switching Fabric: 24 Gbps
• Throughput: 17,857 Mpps
• Forwarding mode: Store-and-forward
• Latency(64-byte frames, 100 Mbps, Copper): <10.194 μs
• Latency (64-byte frames, 1 Gbps, Copper): <3.91μs
• Addressing: 48-bit MAC address
• Address database size: 16,000 MAC addresses
• Number of VLANs: 1,024 VLANs (802.1Q) simultaneously
• Number of multicast groups filtered (IGMP): 1K
• Number of Link Aggregation Groups (LAGs- 802.3ad): 12 LAGs with up to 8 ports per group
• Number of hardware queues for QoS: 8 queues
• Number of static routes (IPv4) 64
• Number of P interfaces(port of VLAN): 64
• Jumbo frame support: up to 9k packet size
• Acoustic noise (ANSI-S10.12) @ 25 °C ambient (77 °F): <30 dB
• Heat Dissipation: 548 Btu/hr
• Mean Time Between Failures(MTBF) : 670,956 hours (~76.6 years)190,562 hours (~21.8 years)ion Manual

Physical Specifications

• Dimensions: 328 x 169 x 43.2 mm (12.91 x 6.65 x 1.7 in)
• Weight: 3.665 kg (8.08 lb)

Environmental Specifications

• Operating temperature: 32° to 122°F (0° to 50°C)
• Operating Humidity: 90% maximum relative humidity, non-condensing
• Operating altitude: 10,000 ft (3,000 m) maximum
• Storage temperature: -4° to 158°F (-20° to 70°C)
• Storage humidity: 95% maximum relative humidity, non-condensing
• Storage altitude: 10,000 ft (3,000 m) maximum

Warranty

• ProSafe Lifetime Hardware Warranty: Included, lifetime
• 90 days of technical support via phone and email: Included, 90 days after purchase
• Lifetime Technical support through online chat: Included, lifetime

Netgear ProSafe GSM7212F-100NES - M4100-12GF Managed Switch

• Lifetime Next Business Day Hardware replacement: Included, lifetime

LEDs

• Per port: Speed, Link, Activity, PoE

• Per device: Power, Fan, RPS or PD Mode, Max or PoE

Safety

• CE mark, commercial

• CSA certified (CSA 22.2 #950)

• UL listed (UL 1950)/cUL IEC 950/EN 60950

• CB

• CCC

Package content

• ProSAFE® M4100 series switch

• Power cord

• Rubber footpads for tabletop installation

• Rubber caps for the SFP sockets

• Mini-USB console cable with one Mini B connector and one type A connector

• Resource CD with links to online documentation: USB drivers for the Mini-USB console; Switch MIB; ProSAFE M4100 Managed

Switch Quick Installation Guide; ProSAFE M4100 Hardware Installation Guide; ProSAFE Managed Switch Command-Line Interface

• (CLI) User Manual; ProSAFE M4100 and M7100 Managed Switches Administration Manual

Please Enquire