

Netgear ProSafe JGS516PE 16PT GE POE Smart Managed Plus Switch



Product Name: Netgear ProSafe JGS516PE 16PT GE POE Smart Managed Plus Switch

Manufacturer: -Model Number: -

Please Note: This product has been discontinued. Please see the other Netgear Routers and Switches for an available alternative.

Netgear ProSafe JGS516PE 16PT GE POE Smart Managed Plus Switch
The Netgear ProSafe JGS516PE 16PT GE POE Smart Managed Plus Switch provides
fundamental network features such as VLANs, QoS, and IGMP Snooping that will help optimise
the performance of business networks. The JGS516PE is the perfect upgrade from the
plug-and-play unmanaged switch, delivering essential networking features at a very affordable
price. Netgear GS116E 16PT Gigabit Smart Managed Plus Switch Key Features

آز½ VLAN support for traffic segmentation

آزئ Quality of Service (QoS) for traffic prioritization

آذِ½ Auto "denial-of-service" (DoS) prevention

� Troubleshoot connection issues via cable test

� Loop detection and broadcaststorm controls

With the ability to set up and configure QoS, the Netgear ProSafe JGS516PE 16PT GE POE Smart Managed Plus Switch an detect different types of network traffic and assign the desired priority to latency-sensitive traffic, such as voice and video. This helps improve the delivery quality of related applications such as VoIP, multimedia broadcasting, and video conferencing. The JGS516PE 16PT has a simple, yet useful network set-up on top of plug-and-play connectivity with flexible management via easy-to-use web browser-based management GUI or using the PC-Based Utility application.

The 16PT Gigabit Smart Managed Plus Switches can help divide big networks into smaller more manageable groups and have resources dedicated for one or several groups rather than making the same resources open to all. This feature improves overall network performance, adds security to network traffic, and makes more efficient use of network resources.

The JGS516PE comes with a cable diagnostic feature that enables users to easily find out the health status of their network cables. If there are any problems, this feature helps quickly locate the point where the cabling fails; allowing connectivity issues to be fixed much faster, potentially saving technicians hours of troubleshooting.

Netgear ProSafe JGS516PE 16PT GE POE Smart Managed Plus Switch - Technical Specification Product Specifications

ï¿⅓ Gigabit Ports: 16

� Number of PoE ports: 8

� Total PoE power budget (watts): 85

� Max MAC entries: 16k � Buffer size 768KB

� Energy Efficient Ethernet (IEEE 802.3az) compliant

Performance Specifications

17.1/2 Forwarding modes: Store-and-forward

ï¿. ½ Bandwidth: 32 Gbps

រ៉េ្យ Priority queuing: Weighted Round Robin (WRR), Strict Priority, or both

12.1/2 Jumbo frame support: Up to 9k per packet



Netgear ProSafe JGS516PE 16PT GE POE Smart Managed Plus Switch

ï¿1/2 Acoustic noise (dB) (ANSI-S10.12): 24.5

آذِ1/2 Mean Time Between Failures (MTBF) (hrs): 840,354

Environmental Specifications

آزا 2 Operating temperature: 32° to 122°F (0° to 50°C)

ī¿½ Operating Humidity: 90% maximum relative humidity, non-condensing

า๊¿½ Operating Altitude: 10,000 ft (3,000 m) maximum

تزن Storage temperature: – 4° to 158°F (–20° to 70°C)

īస్ట్ Storage Humidity: 95% maximum relative humidity, non-condensing

T¿1/2 Storage Altitude: 10,000 ft (3,000 m) maximum

IEEE Network Protocol

ï¿1/2 IEEE 802.3 Ethernet

� IEEE 802.3ab 1000BASE-T

ï¿1/2 IEEE 802.1Q VLAN Tagging

ï¿1/2 IEEE 802.3i 10BASE-T

� IEEE 802.1p Class of Service

ï¿1/2 IEEE 802.3x Full-duplex Flow Control

� IEEE 802.3u 100BASE-T • IEEE 802.3af (PoE)

Management

ï¿⅓ System password

ï¿1/2 Web browser based management GUI

� PC Utility

ï¿⅓ Port Mirroring

آذا Max number of source ports allowed (many to 1): 15

� Many-to-one Port Mirroring

� Cable Test Utility

آزٰ FW upgrade thru Plus Utility (TFTP)

า๊¿½ Cofnig download (to Switch) thru Plus Utility

� Cofnig upload (to Server)

Package contents

ï¿⅓ Smart Managed Plus Switch

� Power cord or power adapter

� Quick Install Guide

ï¿1/2 Resource CD with PC Utility software

� Rackmount kit

Warranty

� Switch Lifetime

� Power adapter: 2 years

Safety

� CE mark, commercial

ï¿1/2 CSA certified (CSA 22.2 #950)

� UL listed (UL 1950)/cUL IEC 950/EN 60950



Netgear ProSafe JGS516PE 16PT GE POE Smart Managed Plus Switch

Physical Specifications

ï¿1/2 Dimensions (mm):328x170x43

ï¿1/2 Weight (kg): 1.67

آز½ Fan: 1

L2 Services - VLANS

� VLAN (# Supported): 100 � IEEE 802.1Q VLAN Tagging

� Port-based VLAN

L2 Services - Availability

าั¿½ Link Aggregation/ Port Trunking: Static Manual LAGs only

ī సైస్ట్ Number of static LAGs and # of members: 8 LAGs and 2 to 4 members

L2 Services - Multicast Filtering

ï¿⅓ IGMP Snooping (v1, v2 and v3

ï¿⅓ Block unknown Multicast

ï¿⅓ Supported Multicast groups: 64

L3 Services - DHCP

� DHCP Client

Quality of Service

ï¿1/2 Rate limiting

ï¿⅓ IEEE 802.1p COS

� Port-based VLAN

Xنï والك

ï¿1/2 WRR (Weighted Round Robin)

ï¿1/2 Strict Priority queue technology

Micellaneous features

� Loop detection

� DoS Prevention

ï¿1/2 Broadcast Storm Control

� Energy Efficient Ethernet (EEE)

LEDs

ï¿1/2 Per Port: Speed, Link, Activity

ï¿1/2 Per device: Power, Fan and PoE Status

Power Consumption (When all ports used, line-rate traffic and max POE

تزير Worst case, all ports used, line-rate traffic, max PoE (W): 110.0

īస్ట్ Heat Dissipation Max/ Standby(BTU/hr): Max: 34.2, Min: 14.4



Netgear ProSafe JGS516PE 16PT GE POE Smart Managed Plus Switch

Please Enquire