

## Fanvil PA2 SIP paging gateway

Product Name: Fanvil PA2 SIP paging gateway



Manufacturer: -

Model Number: SIP-PA2

**Please Note:** This product has been discontinued. Please see the Fanvil PA2S SIP Video Intercom & Paging Gateway for an available alternative.

### Fanvil PA2 SIP paging gateway

The Fanvil PA2 SIP paging gateway is a SIP video intercom and paging device for industry application. The media stream transmission adopts standard IP/RTP/RTSP protocol. It inherits the advantages of the stability and the sound quality of FANVIL VOIP Phone and is compatible with current SIP IPPBX /IMS platforms, such as Asterisk, 3CX and Elastix.

#### Fanvil PA2 SIP paging gateway Key Features

- ½ Small and exquisite, can be embedded in the internal installation
- ½ Emergency call button interface, active call
- ½ Interact with IPC camera, you can make a video phone call
- ½ 1 speaker interface and 1 microphone interface
- ½ 1 audio in, 1 audio out interface
- ½ NVR video recording, standard RJ45 interface
- ½ Recording output, 3.5mm standard audio interface
- ½ 10W-30W adaptive output power
- ½ System online maintenance and management

#### Applications

- ½ Offices
- ½ Prisons
- ½ Care Homes

The PA2 has various functions and interfaces such as intercom, broadcast, video, security, recording.

#### Fanvil PA2 SIP paging gateway Technical Specification

##### Intercom

- ½ Two SIP lines, supporting SIP 2.0 (RFC3261) and related RFC
- ½ Supports two lines RTSP
- ½ Voice broadcast IP address
- ½ Button or remote volume adjustment
- ½ Switch signal input and output
- ½ Talkback recording output
- ½ Handsfree talking
- ½ Default auto answer
- ½ Dynamic multicast function
- ½ Supports DC or POE power supply
- ½ Support for Function key interface
- ½ Support monophonic active speakers
- ½ Network time synchronization
- ½ Action URL / Active URI remote control
- ½ Supports SRTP
- ½ Support for HTTP / HTTPS web pages

## Fanvil PA2 SIP paging gateway

- Support QoS: 802.1p / q, DSCP
- Support MD5 authentication
- Supports Web Filter
- Supports DHCP / static / PPPoE
- Supports STUN

### Physical Specifications

- 2 RJ45 interface: Yellow: WAN port 10 / 100M adaptive, support POE PoE: 802.3af (Class 3: 6.49 ~ 12.95W) Black: LAN port (Only connected to the original camera) Cable: Super five lines or better
- 1 blue indicator (SIP status and network status)
- 2 volume plus or minus key
- 1 restore factory settings key
- 1 recording output interface: 3.5mm standard audio interface 15 Ohm impedance
- 1 ground screw
- 1 way passive speaker interface: Output power: 4&Omega;, POE / 10W, 12V / 10W, 18V / 20W, 24V / 30W; related to supply voltage. Wire diameter: 18 AWG or larger diameter, Interface:Pluggable terminal block
- 1 headset speaker&#65306; Output: 32 Ohm 1.2V interface:Pluggable terminal block
- 1 DSS key interface (4 lines): Indicator: Output 5.0V 5mA Interface:pluggable terminal block
- 1 way microphone input interface: Recommendation: Use an electret condenser microphone Sensitivity: -38dB, Impedance 2.2 K Ohm bias voltage 2.2V Interface:Pluggable terminal block
- 1 short circuit input and output interface (built-in relay): Relay: MAX DC30V / 1A, AC125V / 0.5A, Interface:pluggable terminal block
- 2 parallel power input interface: 12V-24V / 2A DC 1 road for the 5.5mm DC power seat 1 road way 2Pin pluggable terminal block
- Standby power consumption: DC12V 1.32W / POE 1.78W
- Housing material: aluminum alloy shell
- Installation: Indoor installation
- Operating temperature: -30 ~ 70 &#8451;
- Storage temperature: -40 ~ 70 &#8451;
- Relative humidity: 10% - 95%
- Equipment size: 113x83x28mm
- Packing size: 138x108x77mm
- Equipment weight: 250g

### Audio

- Narrowband speech coding: G.711a / u, G.723.1, G.726-32K, G.729AB
- Broadband speech coding: G.722
- Half Duplex Echo Cancellation (AEC)
- DTMF: In-band, out-of-band DTMF (RFC2833) / SIP Info

### Networking Protocols

- Supports PoE (802.3af)
- Primary and secondary DNS servers are supported
- Support VLAN
- Supports SNTP client
- Support VPN L2TP / PPTP / IPSec

**Price: £107.00**

## Fanvil PA2 SIP paging gateway

---

Options available for Fanvil PA2 SIP paging gateway :

### **Support Required**

Not Required, [VoIPon Premium Support Starter \(+£75.00\)](#).