

Swissvoice CP2502 SIP Phone



Product Name: Swissvoice CP2502 SIP Phone

Manufacturer: Swissvoice

Model Number: CP5202

Swissvoice CP2502 SIP Phone

The Swissvoice CP2502 is a SIP Phone with a large colour display and an intuitive interface so that information is clearly displayed and access to a wide variety of business functions can be enjoyed. The CP2502 also has HD sound, meaning that users can benefit from distinct conversations and a crystal clear communication experience. For users who need hands free communication, or work in a noisy atmosphere, a headset can be connected if needed.

Swissvoice CP2502 Key Features

- 2.8" TFT Colour display for easy access to a variety of business functions through a vivid and intuitive interface
- Access to large local and network phonebooks for enhanced contact management
- Full duplex hands-free to ease your conference calls
- Headset and EHS* support for convenient conversations in office environments
- Embedded VPN client for secure remote connections

In addition, the CP2502 is easy to use with 4 customisable soft keys to smoothly handle your phones, as well as supporting BLF feature where the backlight of the two keys allows to know at a glance the status of the lines.

Swissvoice CP2502 Technical Specification

General

- 2.8", 320x240 TFT colour display
- 2 sip accounts
- Power over Ethernet
- Full duplex hands-free
- Wideband audio
- RJ9 headset port and headset key
- *EHS support for Plantronics headsets through ADP-80
- Call log: 100 entries (received, dialled, missed)
- Phonebook: local (500 entries, downloadable), XML
- LDAP, black and white lists
- Caller ID (name & number)
- Multiple built-in languages on WUI and phone MMI

Function Support

- Call waiting, call swap, up to 10 call handling
- 2 programmable line/function keys with BLF support
- 4 customisable softkeys
- Programmable shortcuts
- Visual indicators (LED or on/screen: incoming call, MWI, mute, headset, no service)
- Mute, hold, transfer, call forward, call deflection, redial
- 3-way conference
- 9 built-in melodies
- Do Not Disturb (per line and per phone), keypad lock
- Auto answer (per line)
- Volume control (handset, speakerphone, headset and ringers)
- Peer-to-peer mode, IP Call
- Dial plans, prefix replacement, call barring
- Anonymous call, ACR

Swissvoice CP2502 SIP Phone

- XML browser, action URLs, click to talk
- Keypad lock

IP PBX Integration

- Voicemail access, MWI
- Network conference
- BLF (list/extension)
- DND&CF sync, SCA
- Intercom, music on hold, multicast paging
- Call park, pickup
- Call completion
- Country call progress tones
- Distinctive Ringing
- VIP melodies

Keypad

- 4 customisable softkeys
- 2 programmable line/function keys with BLF support
- 5-way navigation key (configurable shortcuts for idle mode)
- Redial, access to voicemail key
- Mute, hands-free and headset keys
- Volume up and down (on navigation keys)

Technical

- VoIP Protocol Support: SIPv2 (RFC3261)
- Voice Features:
 - G722, G711A, G711u, G723.1, G726-32, G729ab
 - Wideband audio
- Voice Activity Detection, Comfort Noise Generation, Acoustic Echo Cancellation, Packet Loss Concealment, Adaptive Jitter Buffer (300ms), AGC
- Full duplex hands-free with AEC, 96ms tail length
- DIn-band band, RFC2833, SIP Info
- Network Features:
 - DHCP/Static/PPPoE
 - DNS Srv, STUN, NTP
 - 802.1x, LLDP
 - Port mirroring
 - QoS 802.1p/Q, ToS/DSCP
- Security Features:
 - TLS, SRTP, HTTPS
 - VPN: L2TP (Basic Unencrypted) / OpenVPN
 - Config file AES encryption

Swissvoice CP2502 SIP Phone

- 2 level access privileges (user/admin)
- Password dial and certificate management

- Industrial Standard Certifications: CE

Configuration & Management

- IP address Assignment: DHCP, static IP, PPPoE
- Configuration:
 - Keypad
 - Web browser management (Admin/User), HTTP/HTTPS
 - Autoprovision with PnP, HTTP/HTTPS/TFTP/FTP, APRT support
 - One-click config file generation, config restore
 - TR069
 - Pcap tracing, Syslog

Physical & Environmental

- Mounting:
 - Adjustable multiposition foot stand: 2
 - Desktop and wall mountable
- Power over Ethernet: 802.3af
- Power Adaptor: AC100-240V input, 5Vdc/1000mA output (not included, order separately)
- Power Consumption: 1.1-1.8W
- Operating temperature: From 0°C to 40°C
- Operating Humidity: 10% to 60% non-condensing
- Storage temperature: Up to 50°C

Interfaces

- 2 RJ-45 autosensing 10/100Mbps (LAN/PC)
- 1 RJ-9 port for handset connection
- 1 RJ-9 port for headset connection
- 5Vdc power jack

Price: £50.90