

## 2N Indoor Talk Answering Unit - Black Version



Product Name: 2N Indoor Talk Answering Unit - Black Version

Manufacturer: 2N Telecommunications

Model Number: 91378401

Please Note: This product requires 91378800 for installation

### 2N Indoor Talk Answering Unit - Black Version

The 2N Indoor Talk has a design that will suit every flat or home. The aesthetic appearance of this product was achieved by using a glass surface and striking backlighting of its icons. However, 2N has placed particular emphasis on selecting the highest-quality audio components in order to achieve a high-quality sound. This means you can talk to visitors outside as if they were standing right next to you. Invite them in and press the icon to open the door from the comfort of your home.

#### 2N Indoor Talk Key Features

- Luxury design and materials
- HD quality sound with high volume
- Concierge call
- Parental Lock
- Modification to your requirements
- Precision installation box
- Doorbell Button Support

The 2N Indoor Talk uses a HD audio codec and innovative speaker output design, which allows it to achieve a high volume and excellent audio clarity. Use the 2N Indoor Talk to make calls to not only a 2N IP intercom, but to other corresponding answering units in your home, or to reception in your apartment building. In addition, it's easy to prevent your children from accidentally letting strangers into your home when playing. Simply press and hold the buttons to activate a parental lock.

#### Example of typical connection

### 2N Indoor Talk Technical Specification

#### Power Supply

- Type: 10 to 30 V, up to 12 W or PoE 802.3af
- Recommended power supply: 12 V/1A
- Reverse polarity protection: yes

#### User interface

- Controls: 7 capacitive buttons with RGB LED backlight
- Operation: Press and hold the RESET button to restore factory settings, 3 LED status indicators

#### Audio

- Microphone: integrated
- Speaker: integrated, 2W
- Induction loop output: 600 mV RMS

#### Interface

## 2N Indoor Talk Answering Unit - Black Version

• LAN: 10/100BaseT, RJ-45; Cat5e or better  
• Socket: for doorbell connection  
• Type of input: switch contact (button/relay)  
• Contact type: normally open (NO)  
• Contact parameters: up to 50 V / 5 mA, DC

### Mechanical Properties

• Dimensions (W x H x D): 185 x 128 x 48.2 mm  
• Weight: 387 g  
• Operating temperature: 0 to 50 °C  
• Relative operating humidity: 10 to 90 % (non-condensing)  
• Storage temperature: -20 to 70 °C  
• Recommended Altitude: 0 – 2000 m

**Price: £246.60**

---