



Product Name: Snom D735 IP Phone - White (D735W)

Manufacturer: Snom Model Number: D735W

Snom D735 IP Phone - White (D735W)

The Snom D735W white IP Phone is on the cutting edge, both technically and in terms of appearance. The high-resolution 2.7" colour display is surrounded by eight multicoloured function keys that you can label yourself. In order to constantly show the user all the important information they could need, the Snom D735W has a built-in motion sensor – the first VoIP telephone in the world to have such a feature!

Snom D735W Key Features

าั¿1/2 High-resolution 2.7" graphical TFT display

� 32 self-labelling function keys (8 physical)

ï¿1/2 Sensor technology enables responsive UI

i¿½ Wideband hands-free talking (speakerphone)

� Digital Signal Processor (DSP) enhanced audio quality

� 2-port Gigabit Ethernet switch (RJ45)

� Power over Ethernet IEEE 802.3af, Class 2

ï¿1/2 USB headset ready

� D7 Expansion Module ready

ï¿1/2 Support for USB WiFi stick

រី¿½ Electronic Hook Switch (EHS) support for wireless headsets

i¿1/2 Dual-angle footstand: 46° and 28°

ï¿1/2 Stylish white version

As soon as the user's hand approaches the display or the function keys, the display springs to life and automatically shows all the relevant key assignment information. When you move your hand away again, the display reverts to its normal mode. This smart sensor expands the functionality of the D735W enormously and supports the user in their day to day activities. Of course, the Snom D735W also benefits from the tried and tested HD audio quality that has become standard for our telephones. Thanks to this quality, you would be excused for thinking that the person you're talking to was sitting right next to you! This is made possible due to the integrated 'Digital Signal Processors' (DSP), which optimise sound quality in real time, filter out background noise and do so much more. Three-way conferences are also possible with next to no effort.

The Snom D735W also has an integrated gigabit switch with Power over Ethernet (PoE) functionality, as well as a USB port so you can swiftly connect accessories, like USB headsets, to the device.

The Snom D735W is a compact all-rounder and is perfect for all possible uses thanks to its modern and smart functions, as well as the timeless design and colour variants. The new optimised firmware allows each user to forward calls at the touch of a button, initiate conference calls or mute the telephone temporarily.

Snom D735W - Technical Specifications Features

آذِ 12 SIP identities / accounts

� XML browser

ï¿1/2 Call lists for dialled, received, missed calls

i¿1/2 Local directory with 1000 entries

� Multiple language support

17.1/2 DTMF in-band / out-of-band / SIP-INFO

� Interoperable with all major IP PBX platforms



#### Call Features

- ï¿1/2 Speed dialling
- تز½ URL Dialling
- � Local dial plan
- � Automatic redial on busy
- � Call completion (busy/unreachable)(
- � Caller identification
- � Call waiting
- � Call blocking (deny list)
- ï¿⅓ Auto answer
- Hold ½٪ H
- ï¿1/2 Music on hold
- ï¿⅓ Blind and attended transfer
- � Call forwarding
- � 3-way conferencing on the phone
- � Extension monitoring, call pickup
- � Call park, call unpark
- ï¿⅓ Multicast paging
- � DND mode (do not disturb)
- � Keyboard lock
- � Client matter code (CMC)
- ï¿⅓ Unified Communications ready

#### Audio

#### � Codecs:

- � G.711 A-law, µ-law
- ï¿⅓ G.722 (wideband) ·
- G.726, G.729AB, GSM 6.10 (FR)
- ï¿⅓ Built-in assignable ringtones
- ï¿1/2 Comfort Noise Generator (CNG)
- � Voice Activity Detection (VAD)

#### Setup

- � Configurable through a web interface
- � Provisioning: Automatic loading of settings via HTTP/HTTPS/TFTP
- � DHCP Options 66/67
- ï¿⅓ Snom Redirection Service
- ï¿1/2 Remote management via TR-069 / TR-111

### Protocols

- � SIP (RFC3261)
- � DHCP, NTP
- � HTTP / HTTPS / TFTP
- ï¿1/2 LDAP (Directory
- ï¿1/2 Dual Stack IPv4 / IPv6

#### User Interface



- � Localisation (language, time, dial tone)
- i¿1/2 Red LED for call indication/message waiting
- ï¿1/2 4 context-sensitive keys
- าั¿½ 32 (8 physical )programmable line/function keys with multicolour LEDs
- īస్ట్ Dedicated keys for Message, DND, Directory, Menu, Transfer, Hold, Page
- آزا Audio keys with LED indication: Mute, Speakerphone, Headset
- ï¿⅓ Volume key
- � 5-way navigation key
- � OK and Cancel keys
- ï¿1/2 Sensor-assisted user interface

#### Security

- � 802.1X authentication and EAPOL
- � Transport layer security (TLS)
- ï¿⅓ SRTP (RFC3711), SIPS, RTCP
- ï¿⅓ HTTPS server/client
- � password-protected web interface
- آزٰ½ VPN-support
- � VLAN (IEEE 802.1Q)
- � LLDP-MED, RTCP-XR

#### Type Approvals

- � CE Mark
- ï¿1/2 Safety IEC 60950

#### Phone Features

- � Dimensions (approx.):
- � 205 x 185 x 40 mm (LxWxD) w/o foot stand
- าั¿½ 205 x 185 x 200/220 mm (LxWxD) with foot stand
- � Weight (approx.): device 450g, footstand 120g
- ï¿⅓ Input voltage: 5Vdc (SELV)
- � Power supply: PoE or 5Vdc power adapter(1), 10 Watts
- ï¿1/2 Handset: 4P4C
- � Headset: 4P4C; Support for Snom EHS Advanced
- ï¿1/2 Hearing-aid compatible (HAC) handset
- � 1 x USB 2.0 host port, Type A
- � Environmental conditions:
- آذِالِدُ Ambient temperature: 0°C to 35°C (32°F to 95°F)
- T¿1/2 Storage temperature: -10°C to 45°C (14°F to 113°F)
- � Humidity: 5% to 95% (non-condensing)
- ī¿½ Included in delivery: Phone unit, Footstand, Handset with cord, Ethernet cable, Quick Start

Guide, Colour: black or white i; 1/2 Warranty: 2 Years

Price: £98.20

Options available for Snom D735 IP Phone - White (D735W):



## **Need Product Setup / Training / Support?**

Required - 1 Hour (+£65.00), Required - 30 minutes (+£40.00), Not Required.

## **Power Supply Required?**

Not Required, 1 x UK Power Supply Required (+£10.00).

## **Snom A100D Wideband Binaural Headset**

Not Required, Required (+£49.10).

### **Snom A100M Wideband Monaural Headset**

Not Required, Required (+£43.90).

### **Snom A170 Wireless DECT Headset**

Not Required, Required (+£183.10).

### **Snom D7 Expansion Module White**

Not Required, Required (+£105.25).