Snom D715 IP Phone - White (D715W)



Product Name: Snom D715 IP Phone - White (D715W)
Manufacturer: Snom
Model Number: D715W

Please Note: This product is on Pre-Order. Please see the Snom D715 IP Phone for an alternative.

Please Note: snom IP Phones do not include a mains power supply. If mains power is required, this can be added via the drop down menu above.

Snom D715 IP Phone - White (D715W)

The Snom D715W provides high-speed connectivity thanks to its Gigabit Ethernet switch. The Snom D715W comes complete with 4 SIP accounts, Gigabit switch and a USB port.
Snom D715W Key features

ï¿½ 4 SIP accounts
ï¿½ Gigabit switch
ï¿½ USB port
ï¿½ Wideband audio
ï¿½ 5 configurable function keys with LEDs

Featuring a four-line black and white graphical display, the Snom D715W also has four context-sensitive keys and an intuitive, user-friendly menu. Five programmable keys with built-in LEDs for visual call indication give the user flexibility with each function key configurable for a variety of one-touch telephony functions such as speed dial, busy lamp field, or presence indication.
Snom D715W - Technical Specifications
Benefits

ï¿½ Backlit graphical display, 4 lines
ï¿½ Dual-angle foot stand: 46° and 28°
ï¿½ Wall mountable (1)
ï¿½ Wideband hands-free talking (speakerphone)
ï¿½ Digital signal processor (DSP) enhanced audio quality
ï¿½ 2-port 1-Gigabit Ethernet switch (RJ45)
ï¿½ Power over Ethernet IEEE 802.3af, Class 2
ï¿½ USB headset-ready
ï¿½ D7 Expansion module-ready (1)
ï¿½ USB WiFi stick support (RT2070/RT3070 chipsets) (1)
ï¿½ Support for wireless headsets via Electronic hook switch (EHS) (1)

Features

ï¿½ 12 SIP identities / accounts
ï¿½ XML browser
ï¿½ Call lists for dialed, received, missed calls
ï¿½ Local directory with 1000 entries
ï¿½ Multiple language support
ï¿½ DTMF in-band / out-of-band / SIP-INFO
ï¿½ Interoperable with all major IP-PBX platforms

Snom D715 IP Phone - White (D715W)

Call Features

ï¿½ Speed dialing
ï¿½ URL Dialling
ï¿½ Local dial plan
ï¿½ Automatic redial on busy
ï¿½ Call completion (busy/unreachable) (3)
ï¿½ Caller identification
ï¿½ Call waiting
ï¿½ Call blocking (deny list)
ï¿½ Auto answer
ï¿½ Hold
ï¿½ Music on hold (3)
ï¿½ Handling of up to 12 simultaneous calls
ï¿½ Blind attend and transfer
ï¿½ Call forwarding
ï¿½ 3-way conferencing on the phone
ï¿½ Extension monitoring, call pickup (3)
ï¿½ Call park, call unpark (3)
ï¿½ Multicast paging
ï¿½ DND mode (do not disturb)
ï¿½ Keyboard lock
ï¿½ Client matter code (CMC) (3)

Audio

ï¿½ Codecs:G.711 A-law, µ-lawG.722 (wideband)G.726, G.729AB, GSM 6.10 (FR)
ï¿½ Built-in assignable ringtones
ï¿½ Comfort noise generator (CNG)
ï¿½ Voice activity detection (VAD)

Set-up

ï¿½ Configurable through web interface
ï¿½ Provisioning:
ï¿½ Automatic loading of settings via HTTP/HTTPS/TFTP
ï¿½ DHCP Options 66/67
ï¿½ snom Redirection Service
ï¿½ Remote management via TR-069 / TR-111
ï¿½ Unified Communications ready

Protocols

ï¿½ SIP (RFC3261)
ï¿½ DHCP, NTP
ï¿½ HTTP / HTTPS / TFTP
ï¿½ LDAP (Directory)
ï¿½ Dual Stack IPv4 / IPv6

User Interface

ï¿½ Localization (language, time, dial tone)
ï¿½ Red LED for call indication/message waiting
ï¿½ 4 context-sensitive keys
ï¿½ 5 programmable function keys with green LEDs

Snom D715 IP Phone - White (D715W)

ï¿½ Paper inlay for labeling of function keys
ï¿½ Dedicated message key
ï¿½ Audio keys with LED indication: Mute, speakerphone, headset
ï¿½ Volume key
ï¿½ 4-way navigation key, OK and cancel keys
ï¿½ Menu-driven user interface

Security

ï¿½ HTTPS server/client
ï¿½ Transport layer security (TLS)
ï¿½ SRTP (RFC3711), SIPS, RTCP
ï¿½ VLAN (IEEE 802.1x)
ï¿½ LLDP-MED, RTCP-XR
ï¿½ VPN support
ï¿½ Web interface password protection

Phone features

ï¿½ Dimensions in millimetres (approx.):
ï¿½ 205 x 185 x 40 (LxWxD) w/o foot stand (8.1”x7.3”x1.6”)
ï¿½ 205 x 185 x 200/220 mm (LxWxD) with foot stand (8.1”x7.3”x7.9”/8.7”)
ï¿½ Weight (approx.): device 440g, foot stand 120g
ï¿½ Input voltage: 5V DC (SELV)
ï¿½ Power supply: PoE or 5V DC 10 Watts power adapter (2)
ï¿½ Handset: 4P4C connector
ï¿½ Headset connectors:
ï¿½ Wired: 4P4C connector or USB connector
ï¿½ Wireless: USB connector or proprietary 4-pin connector for snom EHS Advanced (1)
ï¿½ Hearing aid compatible (HAC) handset
ï¿½ 1 x USB 2.0 host port, type A, Hi/Full/Low-Speed
ï¿½ Environmental conditions:
ï¿½ Ambient temperature: 0°C to 35°C (32°F to 95°F)
ï¿½ Storage temperature: -10°C to 45°C (14°F to113°F)
ï¿½ Humidity: 5% to 95% (non-condensing)
ï¿½ Included in delivery:Base phone unit
ï¿½ Foot stand
ï¿½ Handset with cord
ï¿½ Ethernet cable
ï¿½ Quick Start Guide
ï¿½ Colour: White
ï¿½ Warranty: 2 years

Type Approval

ï¿½ CE Mark
ï¿½ FCC Class B
ï¿½ Safety IEC 60950, CB

Notes

ï¿½ (1) Optional accessory (see below for part number)
ï¿½ (2) Available separately
ï¿½ (3) If supported by PBX

Snom D715 IP Phone - White (D715W)

Price: £82.90

Options available for Snom D715 IP Phone - White (D715W) :

Need Product Setup / Training / Support?

Required - 30 minutes (+£40.00), Not Required, Required - 1 Hour (+£65.00).

Power Supply Required?

Not Required, 1 x UK Power Supply Required (+£10.00).

Snom A100D Wideband Binaural Headset

Required (+£49.10), Not Required.

Snom A100M Wideband Monaural Headset

Required (+£43.90), Not Required.

Snom A170 Wireless DECT Headset

Required (+£183.10), Not Required.

Snom D7 Expansion Module White

Required (+£105.25), Not Required.