

Snom D715 IP Phone - White (D715W)



Product Name: Snom D715 IP Phone - White (D715W)

Manufacturer: Snom

Model Number: D715W

Please Note: This product is on Pre-Order. Please see the Snom D715 IP Phone for an alternative.

Please Note: snom IP Phones do not include a mains power supply. If mains power is required, this can be added via the drop down menu above.

Snom D715 IP Phone - White (D715W)

The Snom D715W provides high-speed connectivity thanks to its Gigabit Ethernet switch. The Snom D715W comes complete with 4 SIP accounts, Gigabit switch and a USB port. Snom D715W Key features

- 4 SIP accounts
- Gigabit switch
- USB port
- Wideband audio
- 5 configurable function keys with LEDs

Featuring a four-line black and white graphical display, the Snom D715W also has four context-sensitive keys and an intuitive, user-friendly menu. Five programmable keys with built-in LEDs for visual call indication give the user flexibility with each function key configurable for a variety of one-touch telephony functions such as speed dial, busy lamp field, or presence indication.

Snom D715W - Technical Specifications
Benefits

- Backlit graphical display, 4 lines
- Dual-angle foot stand: 46° and 28°
- Wall mountable (1)
- Wideband hands-free talking (speakerphone)
- Digital signal processor (DSP) enhanced audio quality
- 2-port 1-Gigabit Ethernet switch (RJ45)
- Power over Ethernet IEEE 802.3af, Class 2
- USB headset-ready
- D7 Expansion module-ready (1)
- USB WiFi stick support (RT2070/RT3070 chipsets) (1)
- Support for wireless headsets via Electronic hook switch (EHS) (1)

Features

- 12 SIP identities / accounts
- XML browser
- Call lists for dialed, received, missed calls
- Local directory with 1000 entries
- Multiple language support
- DTMF in-band / out-of-band / SIP-INFO
- Interoperable with all major IP-PBX platforms

Snom D715 IP Phone - White (D715W)

Call Features

- Speed dialing
- URL Dialling
- Local dial plan
- Automatic redial on busy
- Call completion (busy/unreachable) (3)
- Caller identification
- Call waiting
- Call blocking (deny list)
- Auto answer
- Hold
- Music on hold (3)
- Handling of up to 12 simultaneous calls
- Blind attend and transfer
- Call forwarding
- 3-way conferencing on the phone
- Extension monitoring, call pickup (3)
- Call park, call unpark (3)
- Multicast paging
- DND mode (do not disturb)
- Keyboard lock
- Client matter code (CMC) (3)

Audio

- Codecs: G.711 A-law, G.711 μ-law, G.722 (wideband), G.726, G.729AB, GSM 6.10 (FR)
- Built-in assignable ringtones
- Comfort noise generator (CNG)
- Voice activity detection (VAD)

Set-up

- Configurable through web interface
- Provisioning:
 - Automatic loading of settings via HTTP/HTTPS/TFTP
 - DHCP Options 66/67
 - snom Redirection Service
 - Remote management via TR-069 / TR-111
 - Unified Communications ready

Protocols

- SIP (RFC3261)
- DHCP, NTP
- HTTP / HTTPS / TFTP
- LDAP (Directory)
- Dual Stack IPv4 / IPv6

User Interface

- Localization (language, time, dial tone)
- Red LED for call indication/message waiting
- 4 context-sensitive keys
- 5 programmable function keys with green LEDs

Snom D715 IP Phone - White (D715W)

- Paper inlay for labeling of function keys
- Dedicated message key
- Audio keys with LED indication: Mute, speakerphone, headset
- Volume key
- 4-way navigation key, OK and cancel keys
- Menu-driven user interface

Security

- HTTPS server/client
- Transport layer security (TLS)
- SRTP (RFC3711), SIPS, RTCP
- VLAN (IEEE 802.1x)
- LLDP-MED, RTCP-XR
- VPN support
- Web interface password protection

Phone features

- Dimensions in millimetres (approx.):
- 205 x 185 x 40 (LxWxD) w/o foot stand (8.1"x7.3"x1.6")
- 205 x 185 x 200/220 mm (LxWxD) with foot stand (8.1"x7.3"x7.9"/8.7")
- Weight (approx.): device 440g, foot stand 120g
- Input voltage: 5V DC (SELV)
- Power supply: PoE or 5V DC 10 Watts power adapter (2)
- Handset: 4P4C connector
- Headset connectors:
- Wired: 4P4C connector or USB connector
- Wireless: USB connector or proprietary 4-pin connector for snom EHS Advanced (1)
- Hearing aid compatible (HAC) handset
- 1 x USB 2.0 host port, type A, Hi/Full/Low-Speed
- Environmental conditions:
- Ambient temperature: 0°C to 35°C (32°F to 95°F)
- Storage temperature: -10°C to 45°C (14°F to 113°F)
- Humidity: 5% to 95% (non-condensing)
- Included in delivery: Base phone unit
- Foot stand
- Handset with cord
- Ethernet cable
- Quick Start Guide
- Colour: White
- Warranty: 2 years

Type Approval

- CE Mark
- FCC Class B
- Safety IEC 60950, CB

Notes

- (1) Optional accessory (see below for part number)
- (2) Available separately
- (3) If supported by PBX

Snom D715 IP Phone - White (D715W)

Price: £82.90

Options available for Snom D715 IP Phone - White (D715W) :

Need Product Setup / Training / Support?

[Required - 1 Hour \(+£65.00\)](#), [Required - 30 minutes \(+£40.00\)](#), [Not Required](#).

Power Supply Required?

[Not Required](#), [1 x UK Power Supply Required \(+£10.00\)](#).

Snom A100D Wideband Binaural Headset

[Not Required](#), [Required \(+£49.10\)](#).

Snom A100M Wideband Monaural Headset

[Not Required](#), [Required \(+£43.90\)](#).

Snom A170 Wireless DECT Headset

[Not Required](#), [Required \(+£183.10\)](#).

Snom D7 Expansion Module White

[Not Required](#), [Required \(+£105.25\)](#).