

## Yealink DECT Repeater RT30

Nealink	****

Product Name: Yealink DECT Repeater RT30 Manufacturer: Yealink Model Number: RT30-REPEATER

#### Yealink DECT Repeater RT30

The Yealink RT30 is designed in accordance with Digital Enhanced Cordless Telecommunication (DECT) standard. It is characterised by easy installation and a user-friendly display concept. The repeater can be deployed to extend the DECT radio coverage of Yealink W60B base station significantly in all directions, and when working with W60B, it supports two RT30 cascaded. Clear LED indicators are used to distinguish different DECT statuses. What's more, its elegant design and easy installations are typically suitable to be used in the ambience of modern business environments.

Yealink RT30 Key Features

- i¿1/2 Compatible with Yealink W60B/W52 DECT IP Base Station
- ï¿1/2 Up to 6 repeaters per base station
- ï¿1/2 Star connection
- ï¿1/2 Up to 2 repeaters can be arranged in cascade
- ï¿1/2 Auto association
- � HD voice
- ï¿1/2 Plug & amp; play setup
- ï¿1/2 Clear status LED display
- ï¿1/2 Elegant design
- ï¿1/2 Wall mountable

Yealink RT30 Technical Specification General

ï¿1/2 Extending the DECT coverage

- ï¿1/2 Supports automatic handover of calls between RT30
- ï¿<sup>1</sup>/<sub>2</sub> Up to 2 simultaneous calls per repeater
- ï¿1/2 Up to 6 repeaters per base station
- ï¿1/2 Up to 2 repeaters can be arranged in cascade (only when connected to W60B)
- ï¿1/2 Auto association
- ï¿1/2 Base Link Reset
- ï¿1/2 LED Display: Led Power On, LED 2 DECT Link, LED 3 Active Relay
- ï¿1/2 Compatible with Yealink W60B (version 77.81.0.35 or later)
- ï¿1/2 Compatible with Yealink W52 Base Station (version 25.81.0.10 or later)


Frequency/Coverage

- $i_{i}$   $\frac{1}{2}$  Indoor range up to 50m (In ideal conditions)
- ï¿<sup>1</sup>/<sub>2</sub> Outdoor range up to 300m (In clear view and ideal conditions)
- ï¿1/2 2 internal QWL omnidirectional antennas
- ï¿<sup>1</sup>∕₂ Modulation: GFSK
- ï¿1/2 Radio frequency range:- 1880 MHz to 1900 MHz (EU),- 1920 MHz to 1930 MHz (US)
- ï¿1/2 Transmission power: Average 10mW
- ï¿1/2 RX sensitivity: typ. -91dBm

**Physical Features** 

ï¿1/2 Desktop or wall mountable

- ï¿1/2 Power supply: AC 100-240V Input and DC 5V/600mA Output
- ï¿1/2 Dimension (W\*H\*T): 130mm x 100mm x 25.1mm





# Yealink DECT Repeater RT30

#### Package Features

i¿½ Package content:- RT30- USB Cable- Power Adapter- User Guide
i¿½ Qty/CNT: 10 PCS
i¿½ Giftbox size: 174mm\*180mm\*63mm
i¿½ Carton meas: 375mm\*336mm\*187mm
i¿½ N.W: 3.2 kg
i¿½ G.W: 3.7 kg

## Price: 98.49EUR

Options available for Yealink DECT Repeater RT30 :

### Need Product Setup / Training / Support?

Required - 30 minutes (+46.57EUR), Required - 1 Hour (+75.67EUR), Not Required.