

## JPL 402S Mid-Office Telecom Headset (JPL-402S-PB)



Product Name: JPL 402S Mid-Office Telecom Headset (JPL-402S-PB) Manufacturer: -Model Number: JPL-402S-PB

Please Note: This product is no longer available.

JPL 402S Mid-Office Telecom Headset (JPL-402S-PB) The JPL JPL-402S-PB is a stylish mid-office and contact centre headset suitable for regular phone users. The JPL-402S has improved sound quality and features Surround Shield noise cancellation.

JPL 402S Key Features

- ï¿<sup>1</sup>/<sub>2</sub> Single and dual ear options available
- i¿1/2 Supplied with quick disconnect system(QD) QD compatible with Plantronics
- ï¿1/2 Surround ShieldTM noise cancelling microphone
- ï¿1/2 Ratchet style 'put and stay' microphone boom
- ï¿1/2 Adjustable sure fit headband
- ï¿1/2 Mid-weight headset, ~ 54g / ~78g
- ï¿1/2 55mm Leatherette ear cushions included
- ï¿1/2 Clothing clip, headset hook & amp; headset bag included
- ï¿1/2 Acoustic shock protection
- ï¿1/2 Compatible with all known office phones
- ï¿1/2 Full range of bottom leads available
- ï¿<sup>1</sup>/<sub>2</sub> 12 Month repair or replacement warranty

JPL 402S Technical Specifications Microphone

ï¿1/2 Directional: Bi-directional

- ï¿1/2 Impedance: Max. 2.2KΩ1KH(RL=2.2KΩ)
- تزائ Sensitivity: -43±3dB RL=2.2KΩ Vs=2.0V (DC)
- ï¿<sup>1</sup>/<sub>2</sub> FrequencyRange: 100-10000Hz
- ï¿1/2 Operating Temp: -25°C~+70°C
- ï¿1/2 Storage Temp: -40°C~+80°C

Speaker

- ï¿1/2 Impedance: 150Ω ±15% at 0.1 V1000Hz
- ï¿1/2 Sound pressure: 129B ± 3dB at 1000HZ
- ï¿1/2 Frequency range: FO ~20KHZ(±10dB), FO: 210Hz ± 20%
- ï¿1/2 Operating Temp: -25°C 50°C
- ï¿<sup>1</sup>/<sub>2</sub> Storage Temp: -25&deg;C 60&deg;C

Agency Approvals:

� RoHS, CE

## **Please Enquire**



## JPL 402S Mid-Office Telecom Headset (JPL-402S-PB)

Options available for JPL 402S Mid-Office Telecom Headset (JPL-402S-PB) :

## **Disconnect Cord Required?**

Disconnect cord to work with a number of alternative manufacture, Not Required, Disconnect cord to work with all Grandstream IP Phones.