

## JPL 501S Mid-Office Telecom Headset (JPL-501S-PM)



Product Name: JPL 501S Mid-Office Telecom Headset (JPL-501S-PM) Manufacturer: -Model Number: JPL-501S-PM

Please Note: This product is no longer available.

JPL 501S Mid-Office Telecom Headset (JPL-501S-PM) The JPL JPL-501S-PM is a stylish mid-office and contact centre headset suitable for regular phone users. The JPL-501S-PM has a slim, flexible microphone boom arm and features Surround Shield noise cancellation. JPL 501S Key Features

- ï¿<sup>1</sup>/<sub>2</sub> Single and dual ear options available
- i¿1/2 Supplied with quick disconnect system(QD) QD compatible with Plantronics
- ï¿1/2 Surround ShieldTM noise cancelling microphone
- ï¿1/2 Slim, flexible microphone boom arm
- i¿1/2 Ratchet style 'put and stay' microphone boom
- ï¿1/2 Adjustable sure fit headband
- ï¿1/2 Mid-weight headset, ~ 70g / ~106g
- ï¿1/2 55mm Leatherette ear cushions included
- ï¿1/2 Clothing clip, headset hook & amp; headset bag included
- ï¿1/2 Compatible with all known office phones
- ï¿1/2 Full range of bottom leads available
- ï¿<sup>1</sup>/<sub>2</sub> 12 Month repair or replacement warranty

JPL 501S Technical Specifications Microphone

ï¿1/2 Directional: Noise Cancelling

- ï¿1/2 Impedance: Max. 2.2KΩ1KH(RL=2.2KΩ)
- ï¿<sup>1</sup>/<sub>2</sub> Sensitivity: -52&plusmn;3dB RL=2.2K&Omega; Vs=2.0V (DC)
- ï¿1/2 FrequencyRange: 100-12000Hz
- ï¿1/2 Operating Temp: -20°C~+60°C
- ï¿1/2 Storage Temp: -40°C~+70°C

Speaker

- ï¿1/2 Impedance: 150Ω ±15% at 0.1 V1000Hz
- ï¿1/2 Sound pressure: 129B ± 3dB at 1000HZ
- ï¿1/2 Frequency range: FO ~20KHZ(±10dB), FO: 210Hz ± 20%
- ï¿1/2 Operating Temp: -25°C 50°C
- ï¿<sup>1</sup>/<sub>2</sub> Storage Temp: -25&deg;C 60&deg;C

## **Please Enquire**

Options available for JPL 501S Mid-Office Telecom Headset (JPL-501S-PM) :

## **Disconnect Cord Required?**

Disconnect cord for all Grandstream IP Phones,



## JPL 501S Mid-Office Telecom Headset (JPL-501S-PM)

Not Required, Disconnect cord for other manufacturers.