JPL Connect VoIP Headset (JPL-CONNECT-2)



Product Name: JPL Connect VoIP Headset (JPL-CONNECT-2)
Manufacturer: -
Model Number: JPL-CONNECT-2

Please Note: This product has been discontinued. Please see the JPL 611 VoIP Headset (JPL-611-PB).

JPL Connect VoIP Headset (JPL-CONNECT-2)
The JPL Connect 2 is a super light-weight affordable professional office and contact centre headset suitable for regular phone users.
JPL Connect 2 Key Features

ï¿½ Single and dual ear options available
ï¿½ Left / right ear side compatible
ï¿½ Ideal for all-day comfort
ï¿½ Weighted filter for clearer Surround Shield ultra noise cancelling
ï¿½ Wideband enabled speakers
ï¿½ Strong, robust construction
ï¿½ Fitted with large 70mm leatherette ear cushions for maximum all-day comfort
ï¿½ Optional 50mm leatherette ear cushions included
ï¿½ Adjustable headband
ï¿½ ‘Put and stay’ ratchet microphone boom arm
ï¿½ Supplied with quick disconnect system(QD) - QD compatible with Plantronics
ï¿½ Headset weight with the 70mm ear cushions, ~ 62g / ~102g
ï¿½ Protective hard-shell carry case included
ï¿½ Clothing clip & hanging hook included
ï¿½ Compatible with all known office phones
ï¿½ Full range of bottom leads available
ï¿½ 24 Month repair or replacement warranty

JPL Connect 2 Technical Specifications
Microphone

ï¿½ Impedance: Max. 2.2KΩ
ï¿½ Sensitivity: -32dB ± 3dB at 1kHz
ï¿½ Directivity: Bi-directional
ï¿½ FrequencyRange: 50Hz~20kHz ± 6dB
ï¿½ Distortion: Less than 3%
ï¿½ Power Supply: 3V DC
ï¿½ S/N Ratio: More than 58dB

Speaker

ï¿½ Impedance: 150Ω ± 15% at 1kHz
ï¿½ Sensitivity: 93 ± 3dB at 1kHz 60mV Input
ï¿½ Max Input Power: 100mV
ï¿½ Frequency Range: 100Hz~6800Hz
ï¿½ Distortion: Less 3% at 1kHz 60mV

Agency Approvals

ï¿½ RoHS, CE, FCC

JPL Connect VoIP Headset (JPL-CONNECT-2)

Please Enquire

Options available for JPL Connect VoIP Headset (JPL-CONNECT-2) :

Disconnect Cord Required?

BL04-P (Sangoma, Snom, Yealink, Grandstream) (+£5.45), Not Required, BL-054MS-P (Softphone) (+£24.00), BL01-P (Fanvil) (+£5.45).