

Yealink CP930W Wireless DECT Conference Phone



Product Name: Yealink CP930W Wireless DECT Conference Phone

Manufacturer: Yealink Model Number: CP930W

Please Note: The base station pictured with the conference phone does not come with it. If you do wish to purchase the base station, please select it from the drop-down menu above.

Yealink Wireless DECT Conference Phone (CP930W)

The Yealink CP930W is based on reliable and secure DECT technology and designed for wireless communication environments such as small-to-medium meeting rooms and huddle rooms. The CP930W not only ensures you up to 24 call hours, but also delivers first-rate audio quality with the Yealink Noise Proof technology. In addition, the wireless design entirely frees you from network and power outlet troubles and makes your conference table more uncluttered than ever before. Yealink CP930W Key Features

- าั¿1/2 3.1" 248x120-pixel graphical LCD with backlight
- � Built-in rechargeable Lithium battery
- � Up to 24-hour talk time
- آذِ1/2 Up to 15-day standby time
- � 3.75-hour charging time
- � Built-in 3-microphone array
- � Optima HD voice, full duplex technology
- 12.1/2 20-foot (6-meter) and 360-degree microphone pickup range
- ï¿1/2 Yealink Noise Proof technology
- � 5-way conference call
- � Connect to PC via Micro USB port
- � Connect to a mobile phone via Bluetooth
- ï¿1/2 Hybrid UC meeting
- � Call recording via Micro SD card
- ï¿1/2 Sensitive touch keypad
- � Upgrade Over-the-Air (OTA)
- � Work with Yealink W60B Base Station

Another smart feature is that Yealink CP930W provides wireless and wired pairing with your mobile staff – smartphone or PC/tablet via Bluetooth and USB Micro-B port to merge all these three devices, your smartphone, PC/tablet and CP930W into one hybrid UC meeting. Make your conference calls mobile and flexible via Yealink CP930W, abandoning the limitation of conference rooms and holds meetings anywhere you want within DECT coverage.

Complete Freedom

Employing DECT technology, the Yealink CP930W Wireless DECT Conference Phone allows you to hold meetings wherever or whenever is convenient for you, freeing you entirely from network and power outlet troubles. Also, its built-in rechargeable battery ensures up to 24 hours of call time and 15 days of standby time, guaranteeing long working times without recharging and making CP930W totally wireless in DECT environment.

Superior Audio Quality

The Yealink CP930W DECT conference phone, marrying the Yealink Noise Proof Technology, unburdens business conversation by reducing annoying noise and minimising distractions to set audio experience into a new level. Thanks to its built-in 3-microphone array, CP930W owns a 20-foot (6-meter) and 360-degree voice pickup range as if all participants are sitting across the table from each other!

Sensitive Touch, Elegant Control

This Y-shape phone released from Yealink, representing the first letter Y of Yealink, owns a sensitive touch keypad which perfectly cancels the keypad noise and facilitates your conference



Yealink CP930W Wireless DECT Conference Phone

room experience by simply putting all of the key conferencing functions at your fingertips. Hybrid UC Meeting

With Yealink CP930W, up to five parties can join a conference call from different locations, helping your company cut costs and save time. Pairing Yealink CP930W with your smartphone (via Bluetooth) or PC/tablet (via micro USB) allows you to turn the Yealink CP930W into a loudspeaker and microphone with ease. In addition, you can merge your smartphone, PC/tablet and SIP call into one hybrid UC meeting.

Yealink CP930W Technical Specifications Display

- าั¿½ 3.1" 248x120-pixel graphical LCD with backlight
- ï¿1/2 Sensitive touch keypad
- าั¿½ 25 total keys: 4 soft keys, off-hook key, on-hook key, 12-key numerical keypad, Bluetooth, mute, volume keys, 2 navigation keys, OK key
- � Multilingual user interface
- � Caller ID with name and number

Audio Features

- � Optimal HD audio
- � Yealink Noise Proof Technology
- ï¿1/2 Background noise suppression
- � 20-foot (6-meter) microphone pickup range
- 12.1/2 Apply to small to medium conference room
- 12.1/2 Built-in 3-microphone array, 360-degree voice pickup
- ï¿1/2 56mm diameter and 5w speaker
- � Full-duplex speakerphone with AEC
- � Echo cancellation tail length is up to 240ms
- าั¿1/2 Wideband codec: Opus, AMR-WB (optional), G.722
- � Narrowband codec: PCMU, PCMA, G.726, G.729, iLBC
- � Receiver volume control: 15 steps
- ï¿1/2 Ringer volume control: 15 steps
- � 10 ringer melodies
- � Multiple advisory tones
- � Acoustic warning for low battery status
- ï¿⅓ DTMF
- � VAD, CNG, PLC, AJB, AGC

Phone Features

- ï¿1/2 5-way conference call
- � 100 phone book memory (store in the base)
- ï¿.1/2 Remote phonebook
- � Phonebook search, black list
- � Call history (All/Missed/Placed/Received)
- � Call transfer, dial plan
- � Paging, intercom
- ï¿1/2 Call hold, call waiting, mute, DND, call recording
- � Call forward (always/busy/no answer)
- ï¿1/2 Emergency call
- � Anonymous call
- � Anonymous call rejection
- ï¿1/2 Set date time manually or automatically
- 17:1/2 Pairing with mobile phone via Bluetooth
- � Pairing with PC via micro USB



Yealink CP930W Wireless DECT Conference Phone

� Direct IP call without SIP proxy

� Reset to factory, reboot

� Phone upgrade: OTA (Over-The-Air)

Interface

� Built-in Bluetooth 4.0

ï¿1/2 1 x micro USB port

� 1 x micro SD slot

� 1 x Security slot

DECT

� Frequency bands: 1880 – 1900 MHz (Europe), 1920 – 1930 MHz (US)

Physical Features

� Colour: Space Silver

าั¿½ DECT Range: - Up to 50 meters indoor (in ideal conditions) - Up to 300 meters outdoor (in

ideal conditions)

� Built-in rechargeable Lithium battery

� 24 hours talk time (in ideal conditions)

تزار 360 hours standby time (in ideal conditions)

Ti, 1/2 External Yealink power adapter: AC 100~240V input and DC 12V/1A output

آذِيًّ Dimension (W*D*H): Phone: 307.8mm*298.5mm*66.9mm, Charging cradle:

110mm*127mm*21.5mm

� Operating humidity: 10~90%

� Storage temperature: -10~40°C (+14~104°F)

Package Features

าั¿½ Package Content: Yealink CP930W DECT conference phone - Charger cradle - Quick Start

Guide - Yealink Power Adapter

� Qty/CTN: 5 PCS � N.W/CTN: 8.3 kg � G.W/CTN: 9.3 kg

ī¿½ Giftbox size: 336mm*364mm*112mm ī¿½ Carton Meas: 587mm*376mm*350mm

Please Enquire

Options available for Yealink CP930W Wireless DECT Conference Phone :

Base Station Required?

Yealink W70B DECT Base Station (+£45.90), Not Required.