

AudioCodes MediaPack 118 Analog VoIP Gateway 8 Port FXS (MP118/8S/SIP)



Product Name: AudioCodes MediaPack 118 Analog VoIP Gateway 8 Port FXS (MP118/8S/SIP)

Manufacturer: -

Model Number: MP118/8S/SIP

Please Note: This product has been discontinued.

AudioCodes MediaPack 118 Analog VoIP Gateway 8 Port FXS (MP118/8S/SIP)

The AudioCodes MP118/8S/SIP is an analog VoIP Gateway which is a cost-effective, best-of-breed technology product. These stand-alone analog VoIP Gateways provide superior voice technology for connecting legacy telephones, fax machines and PBX systems with IP-based telephony networks, as well as for integration with IP PBX systems.

AudioCodes MP118/8S/SIP Key Features

- Wide versatility
- High resiliency
- Broad interoperability
- Superior quality
- Enhanced capabilities
- 8 FXS Ports
- 10/100 BASE-T, RJ-45
- T.38 fax compliant
- Rich subscriber feature set: 3-way conference with local mixing, call pickup, hunt groups, call forwarding, call hold and call transfer
- Advanced telephony features such as long-haul, metering tones generation, country dependent MWI and Caller ID for true integration with the existing telephony infrastructure

AudioCodes MP118/8S/SIP Technical Specifications

Interfaces

• Analog Signaling: 8 ports, FXS, FXO loop-start

• Network Interface: 10/100 BASE-T, RJ-45

Media Capabilities

• Voice Coders: G.711 (A-law and µ-law), G.723.1, G.726, G.727, G.729A/B, G.722

• VoIP Features: G.168-2004 echo cancellation, silence detection and comfort noise generation, dynamic programmable jitter buffer

• Call Progress Tones: Programmable detection and generation tones, pre-recorded tones generation

• DTMF: In-band and out-of-band signaling, RFC 2833, SIP INFO/NOTIFY

• Fax Over IP: Group 3/super G3 fax over IP, T.38 relay, automatic switching to G.711

IP Networking and Telephony Protocols

• VLAN: 802.1 p/Q VLAN tagging

• IP Transport: IPV4/IPV6*, DiffServ, TOS

• Control Protocols: SIP (RFC 3261) over UDP, TCP and TLS (1.2)

• Media Protocols: RTP (RFC 3550), SRTP (RFC 3711), RTCP (RFC 3550), RTCP-XR (RFC 3611)

Management Protocols

AudioCodes MediaPack 118 Analog VoIP Gateway 8 Port FXS (MP118/8S/SIP)

- OAM&P:- Web GUI, SSH/Telnet, SNMP v2/v3, INI file- AudioCodes's One Voice Operation Center- User authentication and access control via RADIUS
- Automatic Configuration:- Zero-touch provisioning- Configuration/firmware download via HTTP(s), FTP and TFTP- DHCP-based provisioning - options 66, 67 and 160- VLAN ID discovery using LLDP
- Voice Menu: Basic configuration using standard touch-tone phone (MP-11x only)

Survivability During Network Failure

- PSTN Fallback: PSTN fallback upon power failure, IP connection failure, customer-defined IP QoS thresholds (MP-114 and MP-118)
- Survivability: Stand Alone Survivability (SAS) for 25 SIP users

Analog Telephony Features

- 3-Way Conference: On-board 3-way conference
- MWI: Message Waiting Indication: High (neon) and low (LED) voltage, FSK, stutter dial tone
- Caller ID: Bellcore GR-30-CORE Type 1 using Bell 202 FSK modulation, ETSI Type 1, NTT, Denmark, India, Brazil, United Kingdom and DTMF ETSI CID (ETS 300-659-1)
- Polarity Reversal/Wink: Immediate or smooth to prevent erroneous ringing
- Metering Tones: 12/16 KHz sinusoidal bursts, generation on FXS
- Distinctive Ringing: By frequency (15-100 Hz) and cadence patterns

Subscriber Line Interface

- Ring Voltage: Sine: 54 VRMS typical (balanced ringing only)
- Ring Frequency: 25-100Hz
- Maximum Ringer Load: REN3
- Loop Impedance: Up to 1,500 ohm for the MP-11x, up to 1,600 ohm for the MP-124 (including phone impedance)
- Line Current: Up to 32 MA on 4 ports

Physical

- Power: 100-240 V AC/50-60 Hz
- Environmental: - Operational: 5 to 40°C (41 to 104°F)- Storage: -25 to 85°C (-13 to 185°F)- Humidity: 10 to 90% non-condensing
- Dimensions: 42x172x220 mm
- Mounting: Table top, wall mount, rack mount (with an optional shelf)
- Weight: MP-1xx: 0.5 kg (1.1 lbs.) approx.

Please Enquire