

AudioCodes Mediant 500L base Enterprise Session Border Controller M500L-ESBC



Product Name: AudioCodes Mediant 500L base Enterprise Session Border Controller M500L-ESBC
Manufacturer: AudioCodes
Model Number: M500L-ESBC

AudioCodes Mediant 500L base Enterprise Session Border Controller M500L-ESBC

Please Note: Additions including sessions, remote implementation support and licenses/ software are available. If you require any of these additions, please enquire using the button above.

The AudioCodes Mediant 500L enterprise session border controller (E-SBC) and media gateway is a compact, high-performance VoIP connectivity solution for small enterprises and branch office locations. AudioCodes Mediant 500L Features

- 60 SBC Sessions
- 8 TDM Sessions
- Branch Survivability
- Supports OPUS and SILK
- Comprehensive interoperability, proven interoperability with SIP trunks, SIP platforms and IP cloud services
- Hybrid functionality, true hybrid SBC and gateway platform for gradual migration, low CAPEX and reduced space and power footprints
- Enhanced security, robust perimeter defense against cyber, DoS and DDoS attacks, as well as eavesdropping, fraud and service theft
- Superior voice quality, advanced capabilities for optimizing and monitoring voice service quality
- High resiliency, local branch survivability and PSTN fallback with E911

Scaling up to 60 concurrent sessions, the Mediant 500L connects IP-PBXs to any SIP trunking service provider and offers superior performance in connecting any SIP to SIP environment. In addition, the Mediant 500L supports up to 8 voice channels to enable versatile connectivity between TDM and VoIP networks, such as connecting legacy TDM PBX systems to IP networks and IP-PBXs to the PSTN.

AudioCodes Mediant 500L Technical Specification
Capacities

- Max. Signaling: 60
- Max. Registered Users: 200
- Max. RTP/SRTP Sessions: 60

Telephony Interfaces

- Digital: 1-4 BRI ports, network S/T interfaces, NT or TE termination
- Analog: Up to 4 FXS and 4 FXO ports
- Clock Source: 5 ppm High Precision

Network Interfaces

- Ethernet: 4 GE interfaces configured in 1+1 redundancy or as individual ports

Security

- Access Control: DoS/DDoS line rate protection, bandwidth throttling, dynamic blacklisting

AudioCodes Mediant 500L base Enterprise Session Border Controller M500L-ESBC

(Intrusion Detection System)

½ VoIP Firewall: RTP pinhole management, rogue RTP detection and prevention, SIP message policy, advanced RTP latching

½ Encryption/Authentication: TLS, SRTP, HTTPS, SSH, client/server SIP Digest authentication, RADIUS Digest

½ Privacy: Topology hiding, user privacy

½ Traffic Separation: VLAN/physical interface separation for multiple media, control and OAMP interfaces

Interoperability

½ SIP B2BUA: Full SIP transparency, mature and broadly deployed SIP stack, stateful proxy mode

½ SIP Interworking: 3xx redirect, REFER, PRACK, session timer, early media, call hold, delayed offer and more

½ Registration and Authentication: SIP Registrar, registration on behalf of users/servers, SIP Digest access authentication

½ Transport Mediation: Mediation between SIP over UDP/TCP/TLS, IPv4/IPv6, RTP/SRTP (SDES)

½ Header Manipulation: Add/modify/delete SIP headers and message body using simple WireShark-like language with powerful capabilities such as variables and utility functions

½ Number Manipulations: Ingress and egress digit manipulation

½ SIP Interworking: 3xx redirect, REFER, PRACK, session timer, early media, call hold, delayed offer

½ Signal Conversion: DTMF/RFC 2833/SIP, T.38 fax, T.38 V3, packet-time conversion

½ NAT: Local and far-end NAT traversal for support of remote workers

Voice Quality and SLA

½ Call Admission Control: Limit number and rate of concurrent sessions and registers per peer for inbound and outbound directions

½ Packet Marking: 802.1p/Q VLAN tagging, DiffServ, TOS

½ Standalone Survivability: Maintains local calls in the event of WAN failure

½ Voice Monitoring and Enhancement: Transrating, RTCP-XR, acoustic echo cancellation, replacing voice profile due to impairment detection, fixed and dynamic voice gain control, packet loss concealment, dynamic programmable jitter buffer, silence suppression/comfort noise generation, RTP redundancy, broken connection detection

½ Direct Media: Hair-pinning (no media anchoring) of local calls to avoid unnecessary media delays and bandwidth consumption

½ Test Agent: Ability to remotely verify connectivity, voice quality and SIP message flow between SIP UAs

SIP Routing

½ Routing Criteria Incoming SIP trunk, DID ranges, host names, any SIP headers, codecs, QoS, bandwidth

½ Querying External Databases Routing based on customized queries of ENUM, LDAP, HTTP server (REST API)

½ Route To Configured SIP peers, registered users, IP address, request URI

½ Advanced Routing Features Alternative routes, load balancing, least-cost routing, call forking, E911 emergency call detection and prioritisation

½ SIPREC IETF standard SIP recording interface

AudioCodes Mediant 500L base Enterprise Session Border Controller M500L-ESBC

Management

• OAM&P Browser-based GUI, CLI, SNMP, INI Configuration file, REST API, EMS

Physical and Environmental

• Dimensions 51 x 296 x 160 mm (2 x 11.65 x 6.3 in.) (HxWxD)

• Weight 670g

• Mounting Desktop

• Power Single universal AC power supply 100-240V, 50-60 Hz, 12V/3A or 12V/5A

• Environmental Operational: 5 to 40°C (41 to 104°F); Storage: -25 to 85°C (-13 to 185°F) Relative Humidity: 10 to 90% non-condensing

Price: 371.26EUR
