

2N Indoor Touch Screen White (91378365W)



Product Name: 2N Indoor Touch Screen White (91378365W)

Manufacturer: -

Model Number: 91378365W

Please Note: This product has been discontinued. Please see the 2N Indoor Touch 2.0 answering unit, white version (91378375WH).

2N Indoor Touch Screen White (91378365W)

The 2N Indoor Touch Screen constitutes an integrated, professional door communication system. The 2N® Indoor Touch has highly intuitive control – by merely looking at the display, you can see who is standing at your door. It's just as easy to display missed calls, and when you want to rest, all you have to do is set the status to "Do not disturb". Using the buttons on the touchscreen, you can not only initiate a conversation with your visitor or neighbour, but you can even unlock the door or turn on the lights in the corridor or entry hall. 2N Indoor Touch Screen Key Features

- � 7" Touchscreen with energy saving mode
- ï¿1/2 Multi-coloured LED status indicator
- าั¿½ Reception of a HD picture from the door communicator
- าั¿½ Two-way communication with other units in the network
- � Display of missed calls
- ī¿½ Setting "Do not disturb" ("DND") status
- � Powered by PoE or external source
- ï¿1/2 Simple control and easy configuration

The 2N® Indoor Touch multifunctional communicator, with an Android operating system, provides audio and video communication with 2N® Helios IP intercoms via SIP 2.0 protocol. It is intended for use in interiors, where it is very simply fitted on the wall in a room. It offers simple and intuitive control using a 7&Idquo; touchscreen with high definition and energy saving mode. An integrated microphone and speaker for effective communication with visitors and multi-coloured LED status indicator, come as standard. 2N Indoor Touch Screen Technical Specifications Signalling Protocol

SIP يُرْزَآ

Power

i¿½ Type: External power adapter, 12V DC 2A / PoE 802.3af

� Power Input: 10W

User interface

า๊¿½ Control: High-capacity touchscreen 16:9

� Display size: 7"

� Resolution: 1024x600px 24bpp (16.7 million colours)

า๊¿½ Backlighting: LED with energy-saving mode

آزر Status indicator: 1x RGB LED (missed calls, energy-saving mode etc.)

Audio

� Microphone: Integrated � Speaker: 1x2W integrated



2N Indoor Touch Screen White (91378365W)

Video

� Protocol: RTSP, MJPEG/HTTP � Intercom supervision and control: Yes � IP camera supervision: Yes

Operating System

ï¿⅓ Android 4.2

Interface

� LAN: Ethernet 10/100BaseT, RJ–45, Recommended cabling Cat5e or higher � Memory card: SD card (up to 16 GB) � GPIOs

Mechanical Parameters

تز½ Wall mounting

ï¿1/2 Dimensions (W x H x D): 235x165x40 mm

تز½ Weight: 850g

� Operating temperature: 0°C – 60°C � Operating relative humidity: 10%-90% (non-condensing)

ï¿1/2 Storage temperature: -20°C to 70°C

Price: £505.90