



Product Name: Konftel Cam20 & Konftel 55 & Hub (KTEL\_C2055) Manufacturer: Konftel Model Number: 951201082

Konftel Cam20 & amp; Konftel 55 & amp; Hub (KTEL\_C2055) The Konftel C2055 is the perfect video collaboration solution for medium-sized meeting rooms, combining the Konftel Cam20 4K conference camera and the Konftel 55 speakerphone with OmniSound® audio quality. The Konftel OCC Hub brings everything together into one convenient kit, so a single USB cable is all you need to connect the camera, the sound unit and the room's screen to the collaboration app on your laptop. Konftel C2055 Key Features

� 4K Ultra HD � 105° field of view � One Cable Connection Hub � Meeting size: up to 12 people � USB 3.0 � OmniSound® with HD audio

Konftel C2055 Technical Specifications General

ï¿1/2 Meeting size: up to 12 people

� USB 3.0

� HDMI

- ï¿1/2 Connection to desk phone (adapter)
- ï¿1/2 Connection to cell phone (cable)
- ï¿1/2 OmniSound®with HD audio
- ï¿1/2 105° field of view
- ï¿1/2 8x digital zoom
- ï¿1/2 USB for collaboration
- ï¿1/2 Easy installation
- ï¿1/2 Free software updates
- � 4K Ultra HD
- � EPTZ
- ï¿1/2 One Cable Connection Hub
- ï¿1/2 Simultaneous output signal via HDMI and USB
- ï¿1∕2 Remote control
- ï¿1/2 Two-year warranty
- ï¿1/2 Product name: Konftel C2055

ï¿1/2 Item number: 951201071

� Contents: Konftel 55 (910101071), power cable (900102136), AC adapter (900102125) and USB cable (900103388), Konftel Cam20 (931201001), 5 m USB cable (type A/type B), remote control with two AAA batteries, Quick guide, safety declaration, Konftel OCC Hub (900102149), 3 m USB cable , 5 m USB cable (type A/mini B) for Konftel 55/55Wx/300IPx/300Wx/300Mx, 5 m USB cable (type A/micro B) for Konftel Ego, AC adapter (EU, US, AU, UK), Velcro®tape, Quick guide, safety declaration, Installation guide

Speaker Phone

� General

i¿½ Meeting size: up to 12 people i¿½ USB



- ï¿1/2 Connection to desk phone (adapter)
- ï¿<sup>1</sup>/<sub>2</sub> Connection to cell phone (cable)
- ï¿1/2 Headset connection 3.5 mm
- ï¿1/2 OmniSound®with HD audio
- ï¿1/2 Colour touchscreen
- ï¿1/2 Recording on memory card
- � Two-year warranty
- ï¿1/2 Integration with UC clients
- ï¿<sup>1</sup>/<sub>2</sub> Combine different connections
- ï¿1/2 Free software updates
- ï¿1/2 Product name: Konftel 55
- ï¿1/2 Item number: 910101071

 $i_{\dot{c}}$ <sup>1</sup>/<sub>2</sub> The Konftel 55 is supplied with a power cable (900102136), AC adapter (900102125) and USB cable (900103388)

� Product documentation: Manual available online in Chinese, English, French, German,
 Spanish and Swedish, Quick Reference Guide available online in Danish, Dutch, English, Finnish,
 French, German, Italian, Norwegian, Polish, Portuguese, Russian, Spanish, Swedish and Turkish
 � Warranty: 2 years

- ï¿1/2 Size: Width 222 mm, depth 206 mm, height 68 mm
- ï¿1∕₂ Weight: 640 g
- $\ddot{\imath} \dot{\imath} ^{1\!\!/_2}$  Colour: Licorice black and silver

#### ï¿1/2 User Interface

� Colour/touch LCD, 240x320 pixels � Keypad: Touchscreen plus on/off, hold

#### ï¿1/2 Menu Languages

ï¿1/2 Chinese, Danish, Dutch, English, Finnish, French, German, Italian, Japanese, Korean, Norwegian, Polish, Portuguese, Russian, Spanish, Swedish, Turkish

### ï¿1/2 UC Integration

تزائر Support for integration in Skype for Business, Cisco Jabber or Avaya Communicator

- ï¿1/2 Connection to Devices
- ï¿1/2 Headsets: 3.5mm

### ï¿1/2 Audio Specifications

� Technology: OmniSound® with support for HD audio, full duplex, automatic echo cancellation and noise suppression
� Microphone: Omnidirectional 360˚
� Reception area: Up to 12 people (30 m²)
� Frequency: 100 – 24,000 Hz
� Volume: 90 dB SPL 0.5 m



ï¿1/2 Additional Features

i¿1/2 Line bridging function: USB + Cell, USB + Desk phone, Cell + Desk phone

ï¿1/2 Recording: Support for SD/SDHC (≤32 GB) memory card

i¿1/2 Software updates: The Konftel upgrade utility (for Microsoft Windows) upgrades the software via USB. It is also possible to upgrade via an SD card

ï¿1∕₂ Environment

� Temperature: 5° – 40°C � Relative humidity: 20 – 80% condensation-free

#### Camera

� General

- ï¿1/2 Meeting size: up to 12 people
- � USB 3.0
- � HDMI
- � 4K Ultra HD
- � EPTZ
- ï¿1/2 USB for collaboration
- ï¿1/2 Easy installation
- ï¿1/2 Free software updates
- ï¿1/2 123° field of view
- � 8x digital zoom
- ïزئ Simultaneous output signal via HDMI and USB
- � Remote control
- ï¿1∕2 Two-year warranty
- ï¿1/2 Product name: Konftel Cam20
- ï¿1/2 Item number: 931201001
- $\ddot{i}_{2}$  Device type: USB conference camera

 $\ddot{i}_{\ell}$  2 Contents: Konftel Cam20, 5 m USB cable (type A/type B), remote control with two AAA

- batteries, Quick guide, safety declaration
- ï¿1/2 Product documentation: Manual in English
- ï¿1/2 Warranty: 2 years
- ï¿1/2 Size: 194 x 34 x 42 mm without bracket
- � Weight: 0.34 kg
- ï¿1/2 Colour: Charcoal black

� Camera

- ï¿1/2 Video modes: 4K Ultra HD/30 fps
- ï¿1∕₂ Zoom: 8x digital zoom
- ï¿1/2 Focus adjustment: Auto
- ï¿1/2 Wide angle: 123°
- � Presets: 255
- � Pan tilt: Digital PTZ (EPTZ)
- ï¿1/2 Digital video format: YUY2, MJPEG, H.264, NV12
- ï¿1/2 Camera control: UVC 1.5/IR Remote
- ï¿<sup>1</sup>/<sub>2</sub> Remote control: Included



ï¿1∕2 Connectivity

- ï¿1/2 USB: USB 3.0 type B
- ï¿1/2 System Requirements
- ï¿1/2 Operative system: Windows 7, 8, 10, Mac OS X, Linux
- ï¿1/2 Additional Requirements
- ï¿1/2 Software updates: Yes
- ï¿1/2 Environment
- ï¿1/2 Temperature: –10°C ~ 40°C

OCC Hub

ï¿1/2 Contents

� Konftel OCC Hub (900102149), 3 m USB 3.0 cable , 5 m USB cable (type A/mini B) for Konftel 55/55Wx/300IPx/300Wx/300Mx, 5 m USB cable (type A/micro B) for Konftel Ego, AC adapter (EU, US, AU, UK), Velcro® tape, Quick guide, safety declaration. (Konftel OCC Hub, updated cable length: 2.5 meter.)

� Size

� 182 x 78 x 32 mm

- � Weight
- � 365g
- � Video

ï¿1/2 Resolution up to 2048 x 1152. Colors in 16 Bits and 32 Bits supported

ï¿1/2 Connections

 $i_{\dot{c}}$  1 x USB 3.0 for computer connection. 2 x USB 2.0 for connecting conference cam and speakerphone. 1 x HDMI for connecting screen

ï¿1/₂ Power Adapter



ï¿1/2 AC 100 – 240V, DC 5V/4A

ï¿1/2 Temperature

ï¿1/2 operation 0 – 40 °C, storage -20 – 70 °C

ï¿1∕₂ Warranty

� 2 years

### Price: £680.90