



Product Name: Fanvil X7C-V2 High-End IP Phone

Manufacturer: Fanvil Model Number: X7C-V2

Fanvil X7C High-End IP Phone (V2)

The Fanvil X7C-V2 is an enterprise IP phone for business users. Featuring 20 SIP lines, intelligent DSS key corresponding display screen, up to 60 DSS keys, bluetooth and WiFi connectivity, the X7C is the ideal communication tool to promote efficiency in any workplace. Fanvil X7C Key Features

� 20 SIP lines

ï¿1/2 5" high-resolution colour display

12.1/2 HD audio on speakerphone and handset

آذِر Up to 60 DSS keys entries available (12 physical)

า๊¿½ Built-in Bluetooth for connecting Bluetooth headset

� Wi-Fi connectivity (via Wi-Fi dongle)

The Fanvil X7C High-end IP Phone features a Rich Extension Function
The X7C offers a variety of device connections including WiFi, built-in Bluetooth, EHS headset,
USB connection for charging smartphone or other devices. Two Gigabit ports allows you to

connect your desktop computer or laptop on the phone with no need for extra cabling.

## 5" Capacitive Colour Display

The telephone's 5" large colour display offers convenient access to all key information such as call lists, phonebook, functions.

#### Fanvil X7C Technical Specifications General

� 20 SIP Lines

ï¿⅓ HD Voice

ï¿⅓ Support receiving Video call

� POE Enabled

ï¿⅓ 5 Inch Colour LCD Screen

ï¿1/2 Handset / Hands-free / Headset mode

ï¿1/2 Intelligent DSS Keys

� Optional External Power Supply

#### Call Features

� Call out / Answer / Reject

� Mute / Unmute (microphone)

� Call Hold / Resume

� Call Waiting

آز½ Intercom

ï¿⅓ Caller ID Display

ï¿1/2 Speed Dial

i¿½ Anonymous Call (Hide Caller ID)

� Call Forwarding (Always/Busy/No Answer)

ï¿1/2 Call Transfer (Attended/Unattended)

� Call Parking/Pick-up (depending on server)

تز½ Redial



- � Do-Not-Disturb
- آزار Auto-Answering
- � Voice Message (on server)
- ï¿1/2 3-way Conference
- ï¿⅓ Hot Line
- ï¿⅓ Hot desking

#### Phone Features

- � Local Phonebook (2000 entries)
- � Remote Phonebook (XML/LDAP, 2000 entries)
- � Call logs (in/out/missed, 1000 entries)
- ï¿1/2 Black/White List Call Filtering
- ï¿1/2 Screen saver
- � Voice Message Waiting Indication (VMWI)
- � Programmable DSS/Soft keys
- � Network Time Synchronisation
- าั¿½ Built-in Bluetooth 2.1: Support Bluetooth headset
- ï¿⅓ Support Wi-Fi Dongle
- าั¿½ Support Plantronics wireless headset (Through Plantronics APD-80 EHS Cable)
- า๊ะ่½ Support Jabra wireless headset (Through Fanvil EHS20 EHS Cable
- ī¿½ Support Recording (Through Flash Drive or Server Recording)
- � Action URL / Active URI
- uaCSTA

### Video

- ï¿1/2 Video codec: H.264
- ï¿1/2 Video call resolution: QCIF / CIF / VGA

### Audio

- � HD Voice Microphone/Speaker (Handset/Hands-free, 0 ~ 7KHz Frequency Response)
- ï¿⅓ HAC handset
- ï¿1/2 Wideband ADC/DAC 16KHz Sampling
- ï¿1/2 Narrowband CODEC: G.711a/u, G.723.1, G.726-32K, G.729AB, AMR, iLBC
- ï¿⅓ Wideband CODEC: G.722, AMR-WB, Opus
- � Full-duplex Acoustic Echo Canceller (AEC)
- آذِيًّا Voice Activity Detection (VAD) / Comfort Noise Generation (CNG) / Background Noise
- Estimation (BNE) / Noise Reduction (NR
- � Packet Loss Concealment (PLC)
- � Dynamic Adaptive Jitter Buffer up to 300ms
- ī¿½ DTMF: In-band, Out-of-Band DTMF-Relay(RFC2833) / SIP INFO

#### Networking

- าั¿½ Physical: 10/100/1000 Mbps Ethernet, dual bridged port for PC bypas
- ï¿1/2 IP Mode:IPv4/IPv6/IPv4&IPv6
- า๊¿½ IP Configuration: Static / DHCP / PPPoE
- � Network Access Control: 802.1x
- � VPN: L2TP / OpenVPN
- � VLAN
- LLDP ½'زï
- � QoS
- � RTCP-XR(RFC3611),VQ-RTCPXR(RFC6035)



#### **Protocols**

- ï¿1/2 SIP2.0 over UDP/TCP/TLS
- � RTP/RTCP/SRTP
- ï¿⅓ STUN
- � DHCP
- ۱₽v6 ½ Pv6
- LLDP ½'زï
- PPPoE ينز
- ï¿⅓ 802.1x
- ۲¿⅓ L2TP لاٍ;ï
- ï¿⅓ OpenVPN
- SNTP ½ 'S
- آز½ FTP/TFTP
- HTTP/HTTPS
- � TR-069

### Deployment and Maintenance

- า๊¿½ Auto-Provisioning via FTP/TFTP/HTTP/HTTPS/DHCP OPT66/SIP
- ï¿1/2 PNP/TR-069
- � Web-based Packet Dump
- � Web management Portal
- � Configuration Export / Import
- � Phonebook Import/Export
- ï¿⅓ Firmware Upgrade
- ï¿⅓ Syslog

#### **Physical Specifications**

- าั¿1/2 Main LCD x1:5.0 inch (800x480) color-screen LCD
- ï¿1/2 Keypad: 43 keys, including
- ï¿⅓ 4 Soft-keys
- ï¿1/2 12 DSS Keys with tri-color LED
- � 1 Page-Switch (PS) key
- า๊¿½ 5 Function keys (Hold, MWI, Mute, Headset, Redial)
- 4 Navigation keys
- � 1 OK key
- � 1 Return key
- ï¿1/2 12 Standard Phone Digits keys
- � 2 Volume Control keys, Up/Down
- ï¿1/2 1 Hands-free key
- HD Handset (RJ9) x1
- � Standard RJ9 Handset Wire x1
- ï¿1/2 1.5M CAT5 Ethernet Cable x1
- ï¿1/2 Back Rack x1
- � RJ9 Port x2: Handset x1, Headset x1
- تز½ RJ45 Port x2: Network x1, PC x1 (Bridged to Network)
- រ៉េះ/៉ូ USB2.0 Port x1: Standard A, Connect with Wi-Fi USB dongle or Flash Driver
- � DC Power Input: 5V/2A
- � Power Consumption (POE): 2.6~9W
- ï¿1/2 Power Consumption (Adapter): 2.4~8W
- � Working Temperature: 0~40℃
- ï¿⅓ Working Humidity: 10~95%



ï¿1/2 Installation: Desktop Stand

� Colour: Black

� Desktop Stand (angles 1): 268x185x189mm � Desktop Stand (angles 2): 268x201x168mm

Price: £97.10

Options available for Fanvil X7C-V2 High-End IP Phone:

# **Need Product Setup / Training / Support?**

Not Required, Required - 1 Hour (+£65.00), Required - 30 minutes (+£40.00).

## Power supply unit

Not Required, UK-PSU-5V-2A (+£6.30).

#### **Wired Headset**

Not Required, Fanvil HT201 (+£31.00), Fanvil HT202 (+£43.00).

## Wireless Headset

Not Required, Jabra Pro 920 Mono DECT Headset (+£163.60).

# **USB** Dongle

Not Required, Fanvil WF20 (+£21.60).

## Camera

Not Required, Fanvil CM60 (+£49.60).