

## JPL Telecom X500 DECT Headset (JPL-ELEMENT-X500)



Product Name: JPL Telecom X500 DECT Headset (JPL-ELEMENT-X500)

Manufacturer: -

Model Number: JPL-ELEMENT-X500

Please Note: This product has been discontinued. Please see the JPL Telecom Explore DECT Wireless Headset for an available alternative.

### JPL Telecom X500 DECT Headset (JPL-ELEMENT-X500)

The JPL Telecom X500 Headset is a totally unique and sustainable wireless DECT concept. It is a modular system that gives you multiple combinations which future proofs the headsets for further developments in Bluetooth and USB technology. Users can select Desk-phone/Soft-phone, Bluetooth or USB connection and monaural headband or binaural headband, even allowing you to switch headband during a call. The headset is easy to set up and maintain and is equally suited to a busy office or call centre environment.

### JPL Telecom X500 Key Features

- User changeable headband from single ear to dual ear
- Universal patented base with slot-in cartridge drawer to accept Bluetooth or USB modules (Optional accessories - sold separately)
- Surround Shield®; noise cancelling microphone
- Sound Defender®; acoustic shock protection
- Max 100m (300ft) coverage
- 7-9 hours talk time (stand by ~ 50 hours)
- Quick recharge time (60 to 90 mins)
- Patented design
- Full range of EHS cords available
- Volume control on headset
- Compatible with MS-Lync
- SB module compatible with most softphones
- 24 Month repair or replacement warranty

### JPL Telecom X500 Technical Specifications

#### Wireless Frequency:

- DECT 6.0, 1.8GHz (EU, Rest of World) 1.9GHz (North America)

#### Microphone:

- Sensitivity: -51dB &plusmn; 3dB 0dB=1V/1Pa @ 1kHz &oslash; Noise Cancelling
- Radio Frequency Tx Power: EU: 24dBm(250mW), US: 20dBm (100mW)

#### Speaker:

- Impedance: 20&oslash; speaker element; 32&Omega;
- FrequencyRange: 300Hz~7000Hz @1kHz (input:100mV)
- Battery Type: Lithium Polymer 370mA
- Power Supply: DC 9V 500mA
- Operating Temperature: -10&deg;C to +60&deg;C (14&deg; to +140&deg;F)
- Storage Temperature: -30&deg;C to +70&deg;C (-22&deg; to +158&deg;F)

#### Agency Approvals:

- RoHS, CE, FCC

## JPL Telecom X500 DECT Headset (JPL-ELEMENT-X500)

**Please Enquire**

Options available for JPL Telecom X500 DECT Headset (JPL-ELEMENT-X500) :

**USB-CARTRIDGE - USB CARTRIDGE FOR X500**

--Not Required--, Required (+36.19EUR).

**BT-CARTRIDGE - BT CARTRIDGE FOR X500**

--Not Required--, Required (+57.20EUR).

**X500-BOOM - SPARE MICROPHONE BOOM ARM FOR X500**

Required (+105.06EUR), --Not Required--.

**X500-MON - SPARE MONAURAL HEADBAND FOR X500**

Required (+28.02EUR), --Not Required--.

**X500-BIN - SPARE BINAURAL HEADBAND FOR X500**

Required (+39.69EUR), --Not Required--.