JPL Telecom X500 DECT Headset (JPL-ELEMENT-X500)



Product Name: JPL Telecom X500 DECT Headset (JPL-ELEMENT-X500)
Manufacturer: -
Model Number: JPL-ELEMENT-X500

Please Note: This product has been discontinued. Please see the JPL Telecom Explore DECT Wireless Headset for an available alternative.

JPL Telecom X500 DECT Headset (JPL-ELEMENT-X500)
The JPL Telecom X500 Headset is a totally unique and sustainable wireless DECT concept. It is a modular system that gives you multiple combinations which future proofs the headsets for further developments in Bluetooth and USB technology. Users can select Desk-phone/Soft-phone, Bluetooth or USB connection and monaural headband or binaural headband, even allowing you to switch headband during a call. The headset is easy to set up and maintain and is equally suited to a busy office or call centre environment.
JPL Telecom X500 Key Features

ï¿½ User changeable headband from single ear to dual ear
ï¿½ Universal patented base with slot-in cartridge drawer to accept Bluetooth or USB modules (Optional accessories - sold separately
ï¿½ Surround Shield™ noise cancelling microphone
ï¿½ Sound Defender™ acoustic shock protection
ï¿½ Max 100m (300ft) coverage
ï¿½ 7-9 hours talk time (stand by ~ 50 hours)
ï¿½ Quick recharge time (60 to 90 mins)
ï¿½ Patented design
ï¿½ Full range of EHS cords available
ï¿½ Volume control on headset
ï¿½ Compatible with MS-Lync
ï¿½ SB module compatible with most softphones
ï¿½ 24 Month repair or replacement warranty

JPL Telecom X500 Technical Specifications
Wireless Frequency:

ï¿½ DECT 6.0, 1.8GHz (EU, Rest of World) 1.9GHz (North America)

Microphone:

ï¿½ Sensitivity: -51dB ± 3dB 0dB=1V/1Pa @ 1kHz 4ø Noise Cancelling
ï¿½ Radio Frequency Tx Power: EU: 24dBm(250mW), US: 20dBm (100mW)

Speaker:

ï¿½ Impedance: 20ø speaker element; 32Ω
ï¿½ FrequencyRange: 300Hz~7000Hz @1kHz (input:100mV)
ï¿½ Battery Type: Lithium Polymer 370mA
ï¿½ Power Supply: DC 9V 500mA
ï¿½ Operating Temperature: -10° to +60°C (14° to +140°F)
ï¿½ Storage Temperature: -30° to +70°C (-22° to +158°F)

Agency Approvals:

ï¿½ RoHS, CE, FCC

JPL Telecom X500 DECT Headset (JPL-ELEMENT-X500)

Please Enquire

Options available for JPL Telecom X500 DECT Headset (JPL-ELEMENT-X500) :

USB-CARTRIDGE - USB CARTRIDGE FOR X500
Required (+£31.00), --Not Required--.

BT-CARTRIDGE - BT CARTRIDGE FOR X500
Required (+£49.00), --Not Required--.

X500-BOOM - SPARE MICROPHONE BOOM ARM FOR X500
--Not Required--, Required (+£90.00).

X500-MON - SPARE MONAURAL HEADBAND FOR X500
--Not Required--, Required (+£24.00).

X500-BIN - SPARE BINAURAL HEADBAND FOR X500
--Not Required--, Required (+£34.00).