

JPL Telecom X500 DECT Headset (JPL-ELEMENT-X500)



Product Name: JPL Telecom X500 DECT Headset (JPL-ELEMENT-X500)

Manufacturer: -

Model Number: JPL-ELEMENT-X500

Please Note: This product has been discontinued. Please see the JPL Telecom Explore DECT Wireless Headset for an available alternative.

JPL Telecom X500 DECT Headset (JPL-ELEMENT-X500)

The JPL Telecom X500 Headset is a totally unique and sustainable wireless DECT concept. It is a modular system that gives you multiple combinations which future proofs the headsets for further developments in Bluetooth and USB technology. Users can select Desk-phone/Soft-phone, Bluetooth or USB connection and monaural headband or binaural headband, even allowing you to switch headband during a call. The headset is easy to set up and maintain and is equally suited to a busy office or call centre environment.

JPL Telecom X500 Key Features

- าั¿½ User changeable headband from single ear to dual ear
- � Universal patented base with slot-in cartridge drawer to accept Bluetooth or USB modules (Optional accessories sold separately
- า๊¿½ Surround Shield™ noise cancelling microphone
- 12/2 Sound Defender™ acoustic shock protection
- � Max 100m (300ft) coverage
- \ddot{i}_{6} 7-9 hours talk time (stand by ~ 50 hours)
- � Quick recharge time (60 to 90 mins)
- � Patented design
- ï¿1/2 Full range of EHS cords available
- � Volume control on headset
- ï¿⅓ Compatible with MS-Lync
- � SB module compatible with most softphones
- � 24 Month repair or replacement warranty

JPL Telecom X500 Technical Specifications Wireless Frequency:

آذًا DECT 6.0, 1.8GHz (EU, Rest of World) 1.9GHz (North America)

Microphone:

� Sensitivity: -51dB ± 3dB 0dB=1V/1Pa @ 1kHz 4ø Noise Cancelling

آذِرُ Radio Frequency Tx Power: EU: 24dBm(250mW), US: 20dBm (100mW)

Speaker:

i¿½ Impedance: 20ø speaker element; 32Ω

تزير FrequencyRange: 300Hz~7000Hz @1kHz (input:100mV)

ï¿1/2 Battery Type: Lithium Polymer 370mA

� Power Supply: DC 9V 500mA

 $\ddot{\imath}$ ¿½ Operating Temperature: -10° to +60°C (14° to +140°F)

آزٰ½ Storage Temperature: -30° to +70°C (-22° to +158°F)

Agency Approvals:

� RoHS, CE, FCC



JPL Telecom X500 DECT Headset (JPL-ELEMENT-X500)

Please Enquire

Options available for JPL Telecom X500 DECT Headset (JPL-ELEMENT-X500):

USB-CARTRIDGE - USB CARTRIDGE FOR X500

Required (+£31.00), --Not Required--.

BT-CARTRIDGE - BT CARTRIDGE FOR X500

Required (+£49.00), --Not Required--.

X500-BOOM - SPARE MICROPHONE BOOM ARM FOR X500

--Not Required--, Required (+£90.00).

X500-MON - SPARE MONAURAL HEADBAND FOR X500

--Not Required--, Required (+£24.00).

X500-BIN - SPARE BINAURAL HEADBAND FOR X500

--Not Required--, Required (+£34.00).