

2N Indoor Compact Black



Product Name: 2N Indoor Compact Black

Manufacturer: 2N Telecommunications

Model Number: 91378501

2N Indoor Compact Indoor Answering Unit - Black

The 2N Indoor Compact is an indoor answering unit designed especially for the residential market. Installation by connecting a single UTP cable and configuration via a web interface guarantees that integrators can put the unit into operation quickly and easily. Users will be impressed by the minimalist design, tempered glass surface, 4.3" colour display and intuitive controls. A simply elegant solution for video communication.

2N Indoor Compact Key Features

½ Intuitive controls, even for inexperienced users

½ Designer surface made of tempered glass

½ Configuration via a web interface

Intuitive Controls, Even for inexperienced users

Accepting calls, opening doors, displaying missed calls or switching to silent mode has never been easier. Large, colour backlit buttons make the interface intuitive and easy to operate.

Configuration via a web interface

Creating a device directory or upgrading firmware in all installed 2N® Indoor Compact units can be done either locally or remotely via the unit's web interface.

Designer surface made of tempered glass

The upper 3mm glass is chemically strengthened at 420°C in a salt bath, providing maximum durability and protecting it from scratches and impacts during everyday household use.

Connection of the unit in a matter of seconds

The structured cabling typical in houses today makes it possible to simply plug the 2N® Indoor Compact straight into the system. Powering the device via PoE and communication are ensured immediately.

2N Indoor Compact Technical Specifications

Power Supply

½ Type: 10 to 30 V, up to 12 W or PoE 802.3af

½ Recommended power supply: 12 V / 1 A

½ Reverse polarity protection: Yes

User Interface

½ Controls: 7 capacitive buttons with RGB LED backlighting

½ Operation: Press and hold the RESET button to restore factory settings, 3 LED status indicators

Audio

½ Microphone: integrated

½ Speaker: integrated, 2W

½ Induction loop output: 600 mV RMS

½ Codecs: G.711, G.729, G.722, L16/16kHz

Interface

½ Display: 4.3" display, resolution 480 x 272 pixels

½ Codecs: H.264, H.263, MJPEG

½ LAN: 10/100BaseT, RJ-45

2N Indoor Compact Black

↳ Recommended cabling: Cat5e or higher

Doorbell Input

↳ Input type: switching contact (button/relay)

↳ Contact type: normally open (NO)

↳ Contact parameters: up to 50V/5mA, DC

Mechanical Properties

↳ Dimensions (W x H x D): 152 x 153 x 50mm

↳ Weight: 387 g

↳ Operating temperature: 0 to 50 °C

↳ Relative operating humidity: 10 to 90 % (non-condensing)

↳ Storage temperature: -20 to 70 °C

↳ Recommended altitude: 0 to 2000 m

Price: £443.20

Options available for 2N Indoor Compact Black :

2N Indoor Flush Box

Required (+£26.20), Not Required.