

## Yeastar TG200 VoIP GSM Gateway 2 GM1



Product Name: Yeastar TG200 VoIP GSM Gateway 2 GM1

Manufacturer: Yeastar

Model Number: TG200G

**Please Note:** This product has been discontinued.

### Yeastar TG200 VoIP GSM Gateway 2 GM1

The Yeastar TG200 connects GSM to VoIP networks to provide two-way communication: GSM/3G/4G to VoIP and VoIP to GSM/3G/4G.

#### Yeastar TG200 Key Features

- GSM Voice Calls
- VoLTE for HD Calls
- Maximum Cost Reduction
- Top Quality and Reliability
- Mobile Connectivity for SMB

It allows you to connect most IP-based telephone systems including Yeastar IP Phone Systems, and softswitches to a GSM or 3G WCDMA or 4G LTE; which can provide a sophisticated fallback solution when landlines go down, or be used to increase call traffic capacity by providing additional dial-tone. Easy to use

Simple and intuitive Web-based configuration saves you loads of time

#### Mobile Trunkings

Add GSM/WCDMA trunkings for business making high number of calls to mobile networks

#### Bulk SMS Service

Great tool for enterprises to manage customer relations and introduce special offers with a low cost

#### Interoperability

Interoperable with a broad list of softswitch, PBX, and IP-PBX like Elastix and Lync Server

#### Yeastar TG200 Technical Specifications

#### Interface

• TG200: 2 GSM or 3G or 4G Channels

• TG100, TG200, TG400: 1 10/100 Mbps Ethernet Interface

#### Voice Processing

• Protocol: SIP, IAX2

• Transport: UDP, TCP, TLS, SRTP

• Voice Codec: G.711 (alaw/ulaw), G.722, G.726, G.729A, GSM, ADPCM, Speex

• Echo Cancellation: ITU-T G.168 LEC

• DTMF Mode: RFC2833, SIP INFO, In-band

• SIP Server for IP Phones Included

• SIP Response Code Switch

• Call Progress Tone Generation

• 1 Stage/2 Stage Dial

#### System Features

• Mobile Ports Groups

• VoIP Trunk Group

• Incoming /Outgoing Routing rules

• Black List

## Yeastar TG200 VoIP GSM Gateway 2 GM1

- Hotline
- AutoCLIP
- Call Duration Limitation
- Call Transfer
- Call Back
- Call Detail Record (CDR)
- Call Status Display
- NTP
- IP Blacklist
- Network Attack Alert
- Packet Capture
- System Logs

### System Features

- Mobile Ports Groups
- VoIP Trunk Group
- Incoming /Outgoing Routing rules
- Black List
- Hotline
- AutoCLIP
- Call Duration Limitation
- Call Transfer
- Call Back
- Call Detail Record (CDR)
- Call Status Display
- NTP
- IP Blacklist
- Network Attack Alert
- Packet Capture
- System Logs

### Mobile Features

- GSM Frequency: 850/900/1800/1900MHz
- WCDMA Frequency: 850/1900MHz, 850/2100MHz, 900/2100MHz
- 4G LTE Band: depends on the module type
- VoLTE if the Carrier Supports
- SMS Sending and Receiving
- Send Bulk SMS
- SMS Center
- Gain Adjustment
- USSD
- PIN Modify
- Carrier Selection: Auto/Manual
- Talk Time Alarm
- Caller ID/CLIR
- Open API for SMS and USSD

### Network & Management

- Network Protocol: FTP, TFTP, HTTP, SSH
- NAT Traversal: Static NAT, STUN
- Static Route
- OpenVPN

## Yeastar TG200 VoIP GSM Gateway 2 GM1

• Firewall  
• VLAN  
• QoS/ToS  
• DDNS  
• Configure Backup/Restore  
• Firmware Upgrade by HTTP/TFTP  
• Web based Configuration

### Physical

• TG200: 213x160x44 mm  
• Power Supply: AC 100-240V

**Please Enquire**

---