

Yeastar TG200 VoIP GSM Gateway 2 GM1



Product Name: Yeastar TG200 VoIP GSM Gateway 2 GM1

Manufacturer: Yeastar Model Number: TG200G

Please Note: This product has been discontinued.

Yeastar TG200 VoIP GSM Gateway 2 GM1

The Yeastar TG200 connects GSM to VoIP networks to provide two-way communication:

GSM/3G/4G to VoIP and VoIP to GSM/3G/4G.

Yeastar TG200 Key Features

ï¿⅓ GSM Voice Calls

آزے VoLTE for HD Calls

� Maximum Cost Reduction

� Top Quality and Reliability

� Mobile Connectivity for SMB

It allows you to connect most IP-based telephone systems including Yeastar IP Phone Systems, and softswitches to a GSM or 3G WCDMA or 4G LTE; which can provide a sophisticated fallback solution when landlines go down, or be used to increase call traffic capacity by providing additional dial-tone. Easy to use

Simple and intuitive Web-based configuration saves you loads of time

Mobile Trunkings

Add GSM/WCDMA trunkings for business making high number of calls to mobile networks Bulk SMS Service

Great tool for enterprises to manage customer relations and introduce special offers with a low cost

Interoperability

Interoperable with a broad list of softswitch, PBX, and IP-PBX like Elastix and Lync Server Yeastar TG200 Technical Specifications

Interface

ï¿1/2 TG200: 2 GSM or 3G or 4G Channels

� TG100, TG200, TG400: 1 10/100 Mbps Ethernet Interface

Voice Processing

� Protocol: SIP, IAX2

ï¿1/2 Transport: UDP, TCP, TLS, SRTP

� Voice Codec: G.711 (alaw/ulaw), G.722, G.726, G.729A, GSM, ADPCM, Speex

� Echo Cancellation: ITU-T G.168 LEC

าั¿1/2 DTMF Mode: RFC2833, SIP INFO, In-band

ï¿1/2 SIP Server for IP Phones Included

ï¿⅓ SIP Response Code Switch

� Call Progress Tone Generation

ï¿1/2 1 Stage/2 Stage Dial

System Features

ï¿1/2 Mobile Ports Groups

� VoIP Trunk Group

� Incoming /Outgoing Routing rules

ï¿⅓ Black List



Yeastar TG200 VoIP GSM Gateway 2 GM1

- ï¿⅓ Hotline
- آز½ AutoCLIP
- � Call Duration Limitation
- � Call Transfer
- � Call Back
- � Call Detail Record (CDR
- ï¿⅓ Call Status Display
- NTP ½٪
- ï¿⅓ IP Blacklist
- � Network Attack Alert
- � Packet Capture
- ï¿⅓ System Logs

System Features

- ï¿⅓ Mobile Ports Groups
- ï¿⅓ VoIP Trunk Group
- ï¿⅓ Incoming /Outgoing Routing rules
- ï¿⅓ Black List
- ï¿⅓ Hotline
- آزٰ½ AutoCLIP
- � Call Duration Limitation
- ï¿1/2 Call Transfer
- تزير Call Back
- � Call Detail Record (CDR
- � Call Status Display
- 7½ NTP
- ï¿⅓ IP Blacklist
- � Network Attack Alert
- � Packet Capture
- ï¿⅓ System Logs

Mobile Features

- ї¿1/2 GSM Frequency: 850/900/1800/1900МHz
- � WCDMA Frequency: 850/1900MHz, 850/2100MHz, 900/2100MHz
- � 4G LTE Band: depends on the module type
- � VoLTE if the Carrier Supports
- ï¿⅓ SMS Sending and Receiving
- ï¿⅓ Send Bulk SMS
- ï¿1/2 SMS Center
- ï¿⅓ Gain Adjustment
- ï¿⅓ USSD
- � PIN Modify
- � Carrier Selection: Auto/Manual
- ï¿⅓ Talk Time Alarm
- ï¿1/2 Caller ID/CLIR
- ï¿1/2 Open API for SMS and USSD

Network & amp; Management

- ï¿1/2 Network Protocol: FTP, TFTP, HTTP, SSH
- ï¿⅓ NAT Traversal: Static NAT, STUN
- ï¿⅓ Static Route
- ï¿⅓ OpenVPN



Yeastar TG200 VoIP GSM Gateway 2 GM1

آز½ Firewall

۲¿⅓ VLAN % ال

ï¿⅓ QoS/ToS

ï¿⅓ DDNS

� Configure Backup/Restore

ï¿⅓ Firmware Upgrade by HTTP/TFTP

ï¿⅓ Web based Configuration

Physical

� TG200: 213x160x44 mm � Power Supply: AC 100-240V

Please Enquire