

Yeastar TG800W VoIP Gateway (8*WCDMA Ports)



Product Name: Yeastar TG800W VoIP Gateway (8*WCDMA Ports)

Manufacturer: Yeastar

Model Number: TG800W

Yeastar TG800W VoIP Gateway (8*WCDMA Ports)

The Yeastar TG800W connects GSM or WCDMA or 4G LTE to VoIP networks to provide two-way communication: GSM/3G/4G to VoIP and VoIP to GSM/3G/4G. This allows you to connect most IP-based telephone systems including Yeastar IP Phone Systems, and softswitches to a GSM or 3G WCDMA or 4G LTE; which can provide a sophisticated fallback solution when landlines go down, or be used to increase call traffic capacity by providing additional dial-tone.

Yeastar TG800W Key Features

- GSM Voice Calls
- VoLTE for HD Calls
- Maximum Cost Reduction
- Top Quality and Reliability
- Mobile Connectivity for SMB

Easy to use

Simple and intuitive Web-based configuration saves you loads of time

Mobile Trunkings

Add GSM/WCDMA trunkings for business making high number of calls to mobile networks

Bulk SMS Service

Great tool for enterprises to manage customer relations and introduce special offers with a low cost

Interoperability

Interoperable with a broad list of softswitch, PBX, and IP-PBX like Elastix and Lync Server

Yeastar TG800W Technical Specifications

Interface

• TG800: 8 GSM or 3G or 4G Channels

• TG800, TG1600: 2 10/100 Mbps Ethernet Interfaces

• Antenna Splitter (4 in 1 antenna): TG400, TG800, TG1600

Voice Processing

• Protocol: SIP, IAX2

• Transport: UDP, TCP, TLS, SRTP

• Voice Codec: G.711 (alaw/ulaw), G.722, G.726, G.729A, GSM, ADPCM, Speex

• Echo Cancellation: ITU-T G.168 LEC

• DTMF Mode: RFC2833, SIP INFO, In-band

• SIP Server for IP Phones Included

• SIP Response Code Switch

• Call Progress Tone Generation

• 1 Stage/2 Stage Dial

System Features

• Mobile Ports Groups

• VoIP Trunk Group

• Incoming /Outgoing Routing rules

• Black List

• Hotline

• AutoCLIP

Yeastar TG800W VoIP Gateway (8*WCDMA Ports)

- Call Duration Limitation
- Call Transfer
- Call Back
- Call Detail Record (CDR)
- Call Status Display
- NTP
- IP Blacklist
- Network Attack Alert
- Packet Capture
- System Logs

System Features

- Mobile Ports Groups
- VoIP Trunk Group
- Incoming /Outgoing Routing rules
- Black List
- Hotline
- AutoCLIP
- Call Duration Limitation
- Call Transfer
- Call Back
- Call Detail Record (CDR)
- Call Status Display
- NTP
- IP Blacklist
- Network Attack Alert
- Packet Capture
- System Logs

Mobile Features

- GSM Frequency: 850/900/1800/1900MHz
- WCDMA Frequency: 850/1900MHz, 850/2100MHz, 900/2100MHz
- 4G LTE Band: depends on the module type
- VoLTE if the Carrier Supports
- SMS Sending and Receiving
- Send Bulk SMS
- SMS Center
- Gain Adjustment
- USSD
- PIN Modify
- Carrier Selection: Auto/Manual
- Talk Time Alarm
- Caller ID/CLIR
- Open API for SMS and USSD

Network & Management

- Network Protocol: FTP, TFTP, HTTP, SSH
- NAT Traversal: Static NAT, STUN
- Static Route
- OpenVPN
- Firewall
- VLAN

Yeastar TG800W VoIP Gateway (8*WCDMA Ports)

- QoS/ToS
- DDNS
- Configure Backup/Restore
- Firmware Upgrade by HTTP/TFTP
- Web based Configuration

Physical

• TG100 110x70x24 DC 12V, 1A

Price: £2,000.00
