

Yeastar TG800W VoIP Gateway (8*WCDMA Ports)



Product Name: Yeastar TG800W VoIP Gateway (8*WCDMA Ports)

Manufacturer: Yeastar

Model Number: TG800W

Yeastar TG800W VoIP Gateway (8*WCDMA Ports)

The Yeastar TG800W connects GSM or WCDMA or 4G LTE to VoIP networks to provide two-way communication: GSM/3G/4G to VoIP and VoIP to GSM/3G/4G. This allows you to connect most IP-based telephone systems including Yeastar IP Phone Systems, and softswitches to a GSM or 3G WCDMA or 4G LTE; which can provide a sophisticated fallback solution when landlines go down, or be used to increase call traffic capacity by providing additional dial-tone.

Yeastar TG800W Key Features

- GSM Voice Calls
- VoLTE for HD Calls
- Maximum Cost Reduction
- Top Quality and Reliability
- Mobile Connectivity for SMB

Easy to use

Simple and intuitive Web-based configuration saves you loads of time

Mobile Trunkings

Add GSM/WCDMA trunkings for business making high number of calls to mobile networks

Bulk SMS Service

Great tool for enterprises to manage customer relations and introduce special offers with a low cost

Interoperability

Interoperable with a broad list of softswitch, PBX, and IP-PBX like Elastix and Lync Server

Yeastar TG800W Technical Specifications

Interface

- TG800: 8 GSM or 3G or 4G Channels
- TG800, TG1600: 2 10/100 Mbps Ethernet Interfaces
- Antenna Splitter (4 in 1 antenna): TG400, TG800, TG1600

Voice Processing

- Protocol: SIP, IAX2
- Transport: UDP, TCP, TLS, SRTP
- Voice Codec: G.711 (alaw/ulaw), G.722, G.726, G.729A, GSM, ADPCM, Speex
- Echo Cancellation: ITU-T G.168 LEC
- DTMF Mode: RFC2833, SIP INFO, In-band
- SIP Server for IP Phones Included
- SIP Response Code Switch
- Call Progress Tone Generation
- 1 Stage/2 Stage Dial

System Features

- Mobile Ports Groups
- VoIP Trunk Group
- Incoming /Outgoing Routing rules
- Black List
- Hotline
- AutoCLIP

Yeastar TG800W VoIP Gateway (8*WCDMA Ports)

- 1/2 Call Duration Limitation
- 1/2 Call Transfer
- 1/2 Call Back
- 1/2 Call Detail Record (CDR)
- 1/2 Call Status Display
- 1/2 NTP
- 1/2 IP Blacklist
- 1/2 Network Attack Alert
- 1/2 Packet Capture
- 1/2 System Logs

System Features

- 1/2 Mobile Ports Groups
- 1/2 VoIP Trunk Group
- 1/2 Incoming /Outgoing Routing rules
- 1/2 Black List
- 1/2 Hotline
- 1/2 AutoCLIP
- 1/2 Call Duration Limitation
- 1/2 Call Transfer
- 1/2 Call Back
- 1/2 Call Detail Record (CDR)
- 1/2 Call Status Display
- 1/2 NTP
- 1/2 IP Blacklist
- 1/2 Network Attack Alert
- 1/2 Packet Capture
- 1/2 System Logs

Mobile Features

- 1/2 GSM Frequency: 850/900/1800/1900MHz
- 1/2 WCDMA Frequency: 850/1900MHz, 850/2100MHz, 900/2100MHz
- 1/2 4G LTE Band: depends on the module type
- 1/2 VoLTE if the Carrier Supports
- 1/2 SMS Sending and Receiving
- 1/2 Send Bulk SMS
- 1/2 SMS Center
- 1/2 Gain Adjustment
- 1/2 USSD
- 1/2 PIN Modify
- 1/2 Carrier Selection: Auto/Manual
- 1/2 Talk Time Alarm
- 1/2 Caller ID/CLIR
- 1/2 Open API for SMS and USSD

Network & Management

- 1/2 Network Protocol: FTP, TFTP, HTTP, SSH
- 1/2 NAT Traversal: Static NAT, STUN
- 1/2 Static Route
- 1/2 OpenVPN
- 1/2 Firewall
- 1/2 VLAN

Yeastar TG800W VoIP Gateway (8*WCDMA Ports)

1½ QoS/ToS
1½ DDNS
1½ Configure Backup/Restore
1½ Firmware Upgrade by HTTP/TFTP
1½ Web based Configuration

Physical

1½ TG100 110x70x24 DC 12V, 1A

Price: £2,000.00