

Cyberdata 011479 SIP Outdoor RGB (Multi-Colour) Strobe



Product Name: Cyberdata 011479 SIP Outdoor RGB (Multi-Colour) Strobe

Manufacturer: CyberData

Model Number: 011479

Cyberdata 011479 SIP Outdoor RGB (Multi-Colour) Strobe

The Cyberdata 011479 is a wall-mounted SIP Outdoor RGB (Multi-Colour) Strobe operates as an IP66 rated visual alerting device. The Outdoor Strobe can be set up as part of a ring group or page group to give visual notification of incoming calls or pages.

Cyberdata 011479 Key Features

- ½ Meets ADA requirements for telephony signaling and notification
- ½ TLS 1.2, enhanced security for IP Endpoints in a local or cloud-based environment
- ½ Cisco SRST support
- ½ Event-controlled relay
- ½ Tamper sensor
- ½ Web-based setup

The Outdoor Strobe may also be activated by being part of a multicast group. The Strobe can be configured with up to 10 multicast addresses and is activated when a stream is sent to its address. You can have the Strobe respond to message waiting signals by blinking. When the message has been heard, the Strobe stops blinking. Multiple colours, blink rate and brightness can be selected for each of the different activation methods. There are 10 multicast settings and two SIP extensions. Users may also use CyberData's HTTP command set to directly access the Strobe's functions. CyberData has maintained one of the most comprehensive lists of IP PBX servers certified to work with CyberData VoIP Products.

Cyberdata 011479 Technical Specifications

General

- ½ Ethernet I/F: 10/100 Mbps
- ½ Protocol: SIP RFC 3261 Compatible
- ½ Power Input: PoE 802.3af compliant or +8 to +12VDC @ 1000mA Regulated Power Supply (not included)
- ½ Flash Rate: 5 user-defined scenes
- ½ LED MTBF: 100,000 Hours
- ½ On-Board Relay: 1A @ 30 VDC
- ½ Network Security: TLS/SSL 1.2
- ½ IP Rating: IP66
- ½ Operating Range: Temperature: -40 degrees C to 55 degrees C (-40 degrees F to 131 degrees F) Humidity: 5-95%, non-condensing
- ½ Storage temperature: -40 degrees C to 70 degrees C (-40 degrees F to 158 degrees F)
- ½ Storage Altitude: Up to 15,000 ft. (4573 m)
- ½ Dimensions: 5.1 inches [129.5 mm] Length, 2.9 inches [73.66 mm] Width, 5.1 inches [129.5 mm] Height
- ½ Weight: 2.0 lbs. [0.90 kg]
- ½ Boxed Weight: 3.0 lbs. [1.35 kg]
- ½ Compliance: CE; EMC Directive – Class A EN 55032 & EN 55024, LV Safety Directive – EN 60950-1, RoHS Compliant, FCC; Part 15 Class A, Industry Canada; ICES-3 Class A, IEEE 802.3 Compliant
- ½ Warranty: 2 years Limited
- ½ Part Number: 011479

Price: £625.20

Cyberdata 011479 SIP Outdoor RGB (Multi-Colour) Strobe
