

Cyberdata 011489 InformaCast Enabled Outdoor RGB (Multi-Color) Strobe



Product Name: Cyberdata 011489 InformaCast Enabled Outdoor RGB (Multi-Color) Strobe Manufacturer: CyberData

Model Number: 011489

Cyberdata 011489 InformaCast Enabled Outdoor RGB (Multi-Color) Strobe The Cyberdata 011489 is a wall-mounted InformaCast Enabled Outdoor RGB (Multi-Color) Strobe that operates as an IP66 rated visual alerting device. Cyberdata 011489 Key Features

ï¿1/2 Meets ADA requirements for telephony signaling and notification

 $i_{\dot{c}} h$ Compatible with Singlewire InformaCast v12.1, including support for downloading SIP credentials from InformaCast

 $i_{i_{1}}$ TLS 1.2, enhanced security for IP Endpoints in a local or cloud-based environment $i_{i_{1}}$ Compatible with Cisco Call Manager

ii/2 Multiple colors, blink rate, and brightness can be selected for each of the different activation methods

- ï¿1/2 SIP and multicast activation
- ï¿1∕2 Cisco SRST support
- ï¿1/2 Event-controlled relay
- � Tamper sensor
- ï¿1/2 Web-based setup

In InformaCast mode, when an audio page is sent to the Strobe, a specific color, brightness and blink rate can be selected based on the priority of the page. The Strobe supports 10 InformaCast priority levels*. In the SIP mode, the device can be set up as part of a ring group or call group to give visual notification of incoming calls or pages. You can have the Strobe respond to message waiting signals by blinking. When the message has been heard, the Strobe stops blinking. The Outdoor Strobe may also be activated by being part of a multicast group. The Strobe can be configured with up to 10 multicast addresses and is activated when a stream is sent to its address. Users may also use CyberData's HTTP command set to directly access the Strobe's functions. *InformaCast v9.0.1 or higher is required to take advantage of this feature. Cyberdata 011489 Technical Specifications

```
General
```

ï¿1/2 Ethernet I/F: 10/100 Mbps

ï¿¹/₂ Protocol: SIP RFC 3261 Compatible

ı́
¿ $^{1\!\!/}_{2}$ Notification Software: Singlewire InformaCast v4.0 and above

� Power Input: PoE 802.3af compliant or +8 to +12VDC @ 1000mA Regulated Power Supply (not included)

ï¿1/2 Flash Rate: 5 user-defined scenes

ï¿1/2 LED MTBF: 100,000 Hours

ï¿1/2 On-Board Relay: 1A @ 30 VDC

ï¿1/2 Network Security: TLS/SSL 1.2

ï¿1/2 IP Rating: IP66

 $i_{\dot{c}}$ /2 Operating Range: Temperature: -40 degrees C to 55 degrees C (-40 degrees F to 131 degrees F) Humidity: 5-95%, non-condensing

 $i_{\dot{c}} h_2$ Storage temperature: -40 degrees C to 70 degrees C (-40 degrees F to 158 degrees F)

i¿1/2 Storage Altitude: Up to 15,000 ft. (4573 m)

 $i_{\dot{c}}1_{2}^{\prime}$ Dimensions: 5.1 inches [129.5 mm] Length, 2.9 inches [73.66 mm] Width, 5.1 inches [129.5 mm] Height

ï¿1/2 Weight: 2.0 lbs. [0.90 kg]

ï¿1/2 Boxed Weight: 3.0 lbs. [1.35 kg]



Cyberdata 011489 InformaCast Enabled Outdoor RGB (Multi-Color) Strobe

i¿½ Compliance: CE; EMC Directive – Class A EN 55032 & EN 55024, LV Safety Directive – EN 60950-1, RoHS Compliant, FCC; Part 15 Class A, Industry Canada; ICES-3 Class A, IEEE 802.3 Compliant i¿½ Warranty: 2 years Limited i¿½ Part Number: 011489

Price: £658.90