

## Yeastar TA810 VoIP FXO Analog Gateway



Product Name: Yeastar TA810 VoIP FXO Analog Gateway

Manufacturer: Yeastar

Model Number: TA810

### Yeastar TA810 VoIP FXO Analog Gateway

The Yeastar TA810 is an analog VoIP Gateway that connects legacy telephones, fax machines and PBX systems with IP telephony networks and IP-based PBX systems. Featuring rich functionalities and easy configuration, TA is ideal for small and medium enterprises that wish to integrate a traditional phone system into IP-based system. TA helps them to preserve previous investment on legacy telephone system and reduce communication costs significantly with the true benefits of VoIP.

### Yeastar TA810 Key Features

- 4/8/16/24/32 FXS ports or 4/8/16 FXO ports
- Fully compliant with SIP and IAX2
- Flexible calling rules
- Reliable fax performance with T.38
- Provides high-quality voice compression with industry standard codecs
- Line echo cancellation for 8, 16, 32, 64 or 128 ms echo delays
- Web-based GUI for easy configuration and management
- Remote Management
- Excellent interoperability with a wide range of legacy and IP equipment

### Easy to use

Simple and intuitive Web-based configuration saves you loads of time

### Feature Rich

A robust feature set that fulfills your various needs and cuts communication cost

### Reliable

Stable with advanced hardware and software architecture

### Interoperability

Interoperable with a broad list of softswitch, PBX, and IP-PBX like Elastix and Lync Server

### Yeastar TA810 Technical Specifications

#### Interface

- Ports: 8 FXO Ports
- Telephony Interfaces: RJ11
- LAN: 1 10/100BASE-T Ethernet
- Indicators: Ports Status and Activity LEDs

#### Media Processing

- Protocol: SIP (RFC3261), IAX2
- Transport: UDP, TCP, TLS, SRTP
- Codec: G.711 (alaw/ulaw), G.722, G.723, G.726, G.729A/B, GSM, ADPCM
- Voice Capability: ITU-T G.168 LEC Echo Cancellation, Dynamic Jitter Buffer, VAD, CNG, PLC
- DTMF Mode: RFC2833, SIP Info, In-band
- Fax: T.30
- QoS DiffServ, ToS, 802.1 P/Q VLAN tagging

#### Telephony Features

- Call Handling: Programmable AC Impedance, Hangup Detection, Answer Detection, Caller ID Detection

## Yeastar TA810 VoIP FXO Analog Gateway

### Security/ IP Services

• Firewall: Built-in Firewall, IP Blacklist, Attack Alert  
• Network: DHCP, DDNS, OpenVPN, Static Route, VLAN  
• Nat Traversal: Static NAT, STUN  
• Network Protocol: FTP, TFTP, HTTP, HTTPS, SSH

### Management

• Protocol: TR-069  
• Provisioning: Web GUI, Auto Provisioning, Backup and Restore, Firmware Upgrade by HTTP/TFTP  
• Configuration: Remote Management\*, Packet Capture, System Logs, Voice Menu for FXS Gateways Basic Configuration, API

### Connectivity

• Signaling: FXO Loop Start, FXO Kewl Start  
• Caller ID: BELL202, ETSI (V23), NTT (V23-Japan), and DTMF-based CID  
• Disconnect Methods: Busy Tone, Polarity Reversal  
• Short & Long Haul: 3REN, up to 1.5 km on 24 AWG wire

### Physical

• Power: AC 100-240V (12V 5.5A)  
• Dimensions (L × W × H) (mm): 440 × 250 × 44  
• Operation Temperature: 0&deg;C to 40&deg;C, 32&deg;F to 104&deg;F  
• Storage Temperature: -20&deg;C to 65&deg;C, -4&deg;F to 149&deg;F  
• Humidity: 10-90% non-condensing  
• Mounting: Desktop, Rack-mount

### Compatibility

• Softswitch and IP-PBX: Interoperable with a wide range of IPPBX and softswitches

**Price: 462.13EUR**