

Yeastar TG800 VoIP GSM Gateway 8 GM1



Product Name: Yeastar TG800 VoIP GSM Gateway 8 GM1 Manufacturer: Yeastar Model Number: TG800G

Yeastar TG800 VoIP GSM Gateway 8 GM1

The Yeastar TG800 connects GSM or WCDMA or 4G LTE to VoIP networks to provide two-way communication: GSM/3G/4G to VoIP and VoIP to GSM/3G/4G. This allows you to connect most IP-based telephone systems including Yeastar IP Phone Systems, and softswitches to a GSM or 3G WCDMA or 4G LTE; which can provide a sophisticated fallback solution when landlines go down, or be used to increase call traffic capacity by providing additional dial-tone. Yeastar TG800 Key Features

 GSM Voice Calls VoLTE for HD Calls Maximum Cost Reduction Top Quality and Reliability Mobile Connectivity for SMB

Easy to use Simple and intuitive Web-based configuration saves you loads of time Mobile Trunkings Add GSM/WCDMA trunkings for business making high number of calls to mobile networks Bulk SMS Service Great tool for enterprises to manage customer relations and introduce special offers with a low cost Interoperability Interoperable with a broad list of softswitch, PBX, and IP-PBX like Elastix and Lync Server Yeastar TG800 Technical Specifications Interface

i¿½ TG800: 8 GSM or 3G or 4G Channels i¿½ TG800, TG1600: 2 10/100 Mbps Ethernet Interfaces i¿½ Antenna Splitter (4 in 1 antenna): TG400, TG800, TG1600

Voice Processing

i¿½ Protocol: SIP, IAX2
i¿½ Transport: UDP, TCP, TLS, SRTP
i¿½ Voice Codec: G.711 (alaw/ulaw), G.722, G.726, G.729A, GSM, ADPCM, Speex
i¿½ Echo Cancellation: ITU-T G.168 LEC
i¿½ DTMF Mode: RFC2833, SIP INFO, In-band
i¿½ SIP Server for IP Phones Included
i¿½ SIP Response Code Switch
i¿½ Call Progress Tone Generation
i¿½ 1 Stage/2 Stage Dial

System Features

i¿½ Mobile Ports Groups i¿½ VoIP Trunk Group i¿½ Incoming /Outgoing Routing rules i¿½ Black List i¿½ Hotline i¿½ AutoCLIP



Yeastar TG800 VoIP GSM Gateway 8 GM1

� Call Duration Limitation
� Call Transfer
� Call Back
� Call Detail Record (CDR
� Call Status Display
� Call Status Display
ï½ NTP
� IP Blacklist
� Network Attack Alert
� Packet Capture
� System Logs

System Features

ï¿1/2 Mobile Ports Groups ï¿1/2 VoIP Trunk Group ï¿1/2 Incoming /Outgoing Routing rules ï¿1/2 Black List � Hotline � AutoCLIP ï¿1/2 Call Duration Limitation i¿1/2 Call Transfer � Call Back ï¿1/2 Call Detail Record (CDR ï¿1/2 Call Status Display � NTP ï¿1∕2 IP Blacklist ï¿1/2 Network Attack Alert ï¿1/2 Packet Capture ï¿1/2 System Logs

Mobile Features

� GSM Frequency: 850/900/1800/1900MHz
� WCDMA Frequency: 850/1900MHz, 850/2100MHz, 900/2100MHz
� 4G LTE Band: depends on the module type
� VoLTE if the Carrier Supports
� SMS Sending and Receiving
� SMS Center
� SMS Center
� Gain Adjustment
� DISD
� PIN Modify
� Carrier Selection: Auto/Manual
� Caller ID/CLIR
� Open API for SMS and USSD

Network & amp; Management

i¿½ Network Protocol: FTP, TFTP, HTTP, SSH i¿½ NAT Traversal: Static NAT, STUN i¿½ Static Route i¿½ OpenVPN i¿½ Firewall i¿½ VLAN



Yeastar TG800 VoIP GSM Gateway 8 GM1

- � QoS/ToS � DDNS
- � Configure Backup/Restore
- ï¿1⁄2 Firmware Upgrade by HTTP/TFTP
- � Web based Configuration

Physical

ï¿1⁄2 TG100 110x70x24 DC 12V, 1A

Price: \$1,666.55