

## Sangoma s406 IP Phone



Product Name: Sangoma s406 IP Phone

Manufacturer: Sangoma

Model Number: PHON-S406

Sangoma s406 IP Phone

The Sangoma S406 IP Phone is an entry-level device with access to powerful phone applications.

It is a full feature set phone with 3 SIP accounts at a competitive price point.

Sangoma S406 Key Features

• 3x SIP Accounts

• 2.7 Inch Graphical LCD with Backlight

• PhoneApps Support

• 25 Programmable Soft Keys

• 5-way Conferencing

• Full Duplex Speaker Phone

• EHS Support for Popular Wireless Headsets

• Dual Gigabit Ethernet Ports

• Optional 3-year Advanced Hardware Replacement Plan

Designed to work with FreePBX and PBXact, Sangoma IP phones are so smart you can quickly and easily use them right out of the box. These phones can quickly locate FreePBX / PBXact as soon as they are plugged into an Internet connection, and become automatically provisioned within seconds! — true Zero Touch Configuration. The s406 features industry standard Power-over-Ethernet (PoE), full duplex speakerphone, 5-way conference calling, high definition (HD) voice quality and built-in Virtual Private Network (VPN) capability.

Zero Touch Provisioning

VoIP telephones can be complex to install, and manually configuring many different parameters and hundreds of extensions can take hours. When you buy and install your Sangoma IP phones, the redirection server automatically points the phone to the Sangoma FreePBX / PBXact for configuration.

Other vendors may have redirection servers, but they have to be programmed with details of the IP PBX. Only Sangoma can provide Zero Touch provisioning with FreePBX / PBXact.

EndPoint Manager Included

When using a Sangoma phone, EndPoint Manager software inside FreePBX / PBXact is automatically enabled. This lets your users control global settings, program their phone keys, map extensions, upload images, download new firmware, and much more.

Full Integration with Phone Apps

PhoneApps are a bundle of advanced applications (or features), which install directly onto your IP Phone, converting all your complicated features into easy-to-use visual applications, which you control, directly from the phone's display!

Sangoma S406 Technical Specifications

General

• 3x SIP accounts

• Call hold, mute, DND

• One-touch speed dial, hotline

• Call forward, call waiting, call transfer

• Redial, call return, auto answer

• 5-way conferencing

• XML Browser

• Direct IP call

• Custom ring tones / provisioning

• Set date time automatically or manually

• Dial plan per account

## Sangoma s406 IP Phone

- RTCP-XR (RFC3611), VQ-RTCPXR (RFC6035)
- Action URL/URI

### IP-PBX Features

- Busy Lamp Field (BLF)
- Call park / pickup
- Music on hold
- Voicemail
- Anonymous call / rejection
- Message waiting indicator
- Intercom, paging
- Follow me / DND
- Conference rooms
- Time conditions
- Queues
- Presence
- Queue agents
- Hot-desking
- Call flow
- Contacts

### Voice Codecs Features

- HD voice: HD handset, HD speaker
- Codecs: iLBC, G.722, G.711(A/&mu;), GSM\_FR, G.723, G.729AB, G.726-32, Opus
- DTMF: In-band, RFC 2833, SIP INFO
- Full-duplex hands-free speakerphone with AEC
- VAD, AGC, CNG, AEC, PLC, AJB

### Display and Indicator

- 2.7" 192 x 364 pixel graphical LCD with backlight
- Caller ID with name, number and photo
- LED for call and message waiting indication
- Dual-colour illuminated LEDs for line status information

### Feature Keys

- 6 line keys with dual-color LED: 25 programmable features (5-pageview)
- 5 feature keys: menu, headset, speaker, mute, voicemail
- 6 navigation keys
- 4 context-sensitive "soft" keys
- Volume control keys
- Illuminated voicemail, speaker, headset and mute keys

### Certifications

- FCC Class B, CE

### Interface

- Ethernet: Dual-port Gigabit
- 1x RJ9 (4P4C) handset port
- 1x RJ9 (4P4C) headset port

## Sangoma s406 IP Phone

- Power over Ethernet (IEEE 802.3af) (PoE), class 2
- Electronic Hook Switch (EHS) support for wireless headsets

### Management

- Configuration: Browser / LCD-menu / auto-provision
- Auto-provision via HTTP / HTTPS, FTP / TFTP
- Auto-provision with PnP
- Login / Logout (Hot-desking)
- Reset to factory, restart, reboot
- Local tracing log export, system log
- Phone lock for personal privacy protection

### Network and Security

- SIP v1 (RFC2543), v2 (RFC3261)
- SIP server / proxy redundancy
- NAT Traversal: STUN mode
- DHCP / static / PPPoE
- HTTP / HTTPS web server
- Time and date synchronisation by SNTP
- DNS-NAPTR/DNS- SRV (RFC 3263)
- IEEE802.1X
- TLS (Transport Layer Security)
- Open VPN
- QoS: 802.1p/Q tagging (VLAN), Layer 3 ToS DSCP
- HTTPS certificate manager
- AES encryption for configuration file
- Digest authentication using MD5/MD5-sess

### Languages

- Built-in: English, French, German, Spanish, Portuguese, Russian, Italian, Polish, Turkish, Serbian, Chinese Simplified, Chinese Traditional, Slovenian, Farsi, Slovak and Czech
- Controlled by PBX: Chinese Simplified, Chinese Traditional, English, French, German, Italian, Polish, Portuguese, Russian, Spanish, Turkish

### Physical Features

- Shipping dimensions: 229mm (W) x 211mm (D) x 102mm (H)
- Shipping weight: 1.27kgs (2.8lbs)
- Wall mountable
- Stand with 3 adjustable angles
- Power consumption (PSU): 2.0~4.6W
- Power consumption (PoE): 2.5~5.5W
- Operating humidity: 10~95%
- Operating temperature: -10~50&deg;C

### Optional Accessories

- External universal AC adapter (US, UK, EUR): AC 100~240V input, DC 5V/1.2A output
- EHS headset adapter
- Wall mount bracket

## Sangoma s406 IP Phone

**Please Enquire**

---

Options available for Sangoma s406 IP Phone :

**Sangoma Headset Adapter Required?**

[Sangoma EHS30 Required \(+£37.00\)](#), [Not Required](#).

**Sangoma Phone UK Power Supply**

[Not Required](#), [Required \(+£6.10\)](#).