

## CyberData SIP Outdoor Intercom with RFID (011477)



Product Name: CyberData SIP Outdoor Intercom with RFID (011477)

Manufacturer: CyberData

Model Number: 011477

CyberData SIP Outdoor Intercom with RFID (011477)

The CyberData SIP Outdoor Intercom with RFID is perfect for secure access settings requiring RFID access control and two-way communication. With encrypted RFID, the SIP Outdoor Intercom can increase the security of any VoIP installation.

CyberData SIP Outdoor Intercom with RFID Key Features

- TLS 1.2 enhanced security for IP Endpoints in a local or cloud-based environment
- Mifare Plus X 2K/4K cards are supported for a high level of encryption
- Alert buzzer
- Red/Green lock status lights
- Built-in time of access scheduler
- Local and remote logging with time stamp
- NTP time support
- Supports 500 RFID Cards
- Blacklisted card alert via dialout or multicast
- Full-duplex voice operation
- Supports SRST in a Cisco environment
- Network web management
- Network adjustable speaker volume and microphone sensitivity
- Network downloadable firmware
- Doubles as a paging speaker
- Custom alert, ringtones and callout messages may be uploaded
- Dry relay contact for auxiliary control
- Door closure and tamper alert signal
- Security Torx screws with driver kit included

The product supports up to 500 RFID cards. A card with a blacklisted code will trigger a phone call with a pre-recorded message and/or a multicast stream to IP notification endpoints. The access code list, designating valid entry times or blacklisted users, can be updated manually using the web interface, imported using the web page, or autoprovisioned using the same mechanism as a VoIP phone. For ease of managing your access list, we recommend using the 011425 RFID Secure Access Endpoint as a desktop enrollment device. (see RFID Implementation Guide on the Installation tab).

CyberData has maintained one of the most comprehensive lists of IP PBX servers certified to work with CyberData VoIP Product

CyberData SIP Outdoor Intercom with RFID Technical Specifications  
General

- Ethernet I/F: 10/100 Mbps
- Protocol: SIP RFC 3261 Compatible
- RFID Card Protocol: ISO/IEC 14443 Type A - 13.56 MHz Standard
- Power Input: PoE 802.3af compliant or +8 to +12VDC @ 1000mA Regulated Power Supply (not included)
- Speaker Output: 2 Watts Peak Power
- On-Board Relay: 1A @ 30 VDC
- Supported RFID cards: Mifare Plus X 2K or 4K
- Payload Types: G.711 a-law, G.711 &micro;-law, G.722, and G.729
- Network Security: TLS/SSL 1.2
- IP Rating: IP65
- Operating Range: Temperature: -40 C to 55 C (-40 F to 131 F) Humidity: 5-95%,

## CyberData SIP Outdoor Intercom with RFID (011477)

non-condensing

½ Storage Temperature: Temperature: -400 C to 700 C (-400 F to 1580 F)

½ Storage altitude: Up to 15,000 ft. (4573 m)

½ Dimensions: Length: 7.480 inch [190 mm], Width: 2.284 inch [58 mm], Height: 5.118 inch [130 mm]

½ Weight: 2.8 lbs. [1.27 kg]

½ Boxed Weight: 4.0 lbs. [1.81 kg]

½ Compliance: CE; EMC Directive &ndash; Class A EN 55032 & EN 55024, LV Safety Directive &ndash; EN 60950-1, RoHS Compliant, FCC; Part 15 Class A, Industry Canada; ICES-3 Class A, IEEE 802.3 Compliant

½ Warranty: 2 Years Limited

½ Part Number: 011477

**Price: 970.65EUR**

---