

CyberData SIP h.264 Video Outdoor Intercom with RFID (011478)



Product Name: CyberData SIP h.264 Video Outdoor Intercom with RFID (011478)

Manufacturer: -

Model Number: 011478

Please Note: This product has been discontinued. Please see the CyberData VoIP V3 Outdoor Intercom (011186) for an alternative.

CyberData SIP h.264 Video Outdoor Intercom with RFID (011478)

The CyberData SIP h.264 Video Outdoor Intercom with RFID is perfect for secure access settings requiring RFID access control, video, and two-way communication. With excellent color, low light capability, and encrypted RFID, the SIP h.264 Video Intercom can increase the security of any VoIP installation.

CyberData SIP h.264 Video Outdoor Intercom with RFID Key Features

- TLS 1.2 enhanced security for IP Endpoints in a local or cloud-based environment

- Mifare Plus X 2K/4K cards are supported for a high level of encryption

- Alert buzzer

- Red/Green lock status lights

- Built-in time of access scheduler

- Local and remote logging with time stamp

- NTP time support

- Supports 500 RFID cards

- Blacklisted card alert via dialout or multicast

- Adjustable camera angle

- Full-duplex voice operation

- Supports SRST in a Cisco environment

- Network web management

- Network adjustable speaker volume and microphone sensitivity

- Network downloadable firmware

- Doubles as a paging speaker

- Custom alert, ringtones and callout messages may be uploaded

- Dry relay contact for auxiliary control

- Door closure and tamper alert signal

- Security Torx screws with driver kit included

The product supports up to 500 RFID cards. A card with a blacklisted code will trigger a phone call with a pre-recorded message and/or a multicast stream to IP notification endpoints. The access code list, designating valid entry times or blacklisted users, can be updated manually using the web interface, imported using the web page, or autoprovisioned using the same mechanism as a VoIP phone. For ease of managing your access list, we recommend using the 011425 RFID Secure Access Endpoint as a desktop enrollment device. (see RFID Implementation Guide on the Installation tab).

CyberData has maintained one of the most comprehensive lists of IP PBX servers certified to work with CyberData VoIP Product

CyberData SIP h.264 Video Outdoor Intercom with RFID Technical Specifications
General

- Ethernet I/F: 10/100 Mbps

- Protocol: SIP RFC 3261 Compatible

- RFID Card Protocol: ISO/IEC 14443 Type A - 13.56 MHz Standard

- Power Input: PoE 802.3af compliant or +8 to +12VDC @ 1000mA Regulated Power Supply

CyberData SIP h.264 Video Outdoor Intercom with RFID (011478)

(not included)

1½ Speaker Output: 2 Watts Peak Power

1½ On-Board Relay: 1A @ 30 VDC

1½ Supported RFID cards: Mifare Plus X 2K or 4K

1½ Payload Types: G.711 a-law, G.711 µ-law, G.722, and G.729

1½ Video Codec: H.264 Baseline

1½ Camera Resolution: 320 x 240

1½ SIP Video Payload: Baseline profile @ 320x240

1½ Video Lens Angle: 72 degrees, with 30 degree mechanical adjustment

1½ Network Security: TLS/SSL 1.2

1½ IP Rating: IP65

1½ Operating Range: Temperature: -40 C to 55 C (-40 F to 131 F) Humidity: 5-95%, non-condensing

1½ Storage Temperature: Temperature: -40 C to 70 C (-40 F to 158 F)

1½ Storage altitude: Up to 15,000 ft. (4573 m)

1½ Dimensions: Length: 7.480 inch [190 mm], Width: 2.284 inch [58 mm], Height: 5.118 inch [130 mm]

1½ Weight: 2.8 lbs. [1.27 kg]

1½ Boxed Weight: 4.0 lbs. [1.81 kg]

1½ Compliance: CE; EMC Directive – Class A EN 55032 & EN 55024, LV Safety Directive – EN 60950-1, RoHS Compliant, FCC; Part 15 Class A, Industry Canada; ICES-3 Class A, IEEE 802.3 Compliant

1½ Warranty: 2 Years Limited

1½ Part Number: 011478

Price: £1,169.40