

## ZYCOO X30 SIP Paging Gateway



Product Name: ZYCOO X30 SIP Paging Gateway

Manufacturer: ZYCOO

Model Number: X30

### ZYCOO X30 SIP Paging Gateway

The ZycOO X30 SIP Paging Gateway is an innovative PA endpoint device. It converts voice streams from a SIP paging or IPPBX system to analogue sounds, suitable for background music, public address and intercom. ZycOO X30 SIP Paging Gateway Key Features

- Industry Standard
- Powerful Amplifier
- Peripheral Support
- Simple Installation and Configuration
- Compatible with Third Party Systems
- Multicast Support
- Intercom Calling

The X30 has been developed using open SIP standards, ensuring that it works seamlessly with ZYCOO Paging and Intercom system. The X30 can also be deployed with most third party SIP PA and IPPBX systems which support SIP Protocol.

### ZYCOO X30 SIP Paging Gateway Technical Specification

#### Audio

- Speaker Output: 2x10W, 8Ω
- Headset Output: 40mW, 16Ω
- Microphone: Support

#### Protocol

- SIP2.0 (RFC3261)

#### Keypad

- Support 4x4 16-key keypad

#### LCD

- UART Serial LCD (Customisable)

#### Voice

- Protocol: RTP, RTCP
- Codecs: G.711(a&#65292;u), G.722, G.726, G.729, Speex, etc.

#### Other Interfaces

- Power: DC12V-3A/DC24V-1.5A (DO NOT use DC power and PoE at the same time!)
- PoE: 802.3at(48V-30W)
- ETH0/ETH1: 10/100Mbps (PoE IEEE 802.3at support on ETH0)
- Serial: RS485
- GPIO: 2xI/O Signal, 2 Speed-dial Keys
- Key LED: 2
- Switching Signal Input: Support
- Switching Signal Output: Support

## ZYCOO X30 SIP Paging Gateway

### Environmental Requirements

ï¿½ Operating Temperature: -40&deg;C ~ +75&deg;C

ï¿½ Storage Temperature: -40&deg;C ~ +75&deg;C

ï¿½ Humidity: 10% ~ 95%

### Dimension

ï¿½ 153x76x33mm

### Weight

ï¿½ 400g

**Price: 281.03EUR**

---