

## Netgear GS728TPv2 ProSAFE 24-Port Gigabit PoE Smart Switch



Product Name: Netgear GS728TPv2 ProSAFE 24-Port Gigabit PoE Smart Switch

Manufacturer: Netgear

Model Number: GS728TPv2

### Netgear GS728TPv2 ProSAFE 24-Port Gigabit PoE Smart Switch

The Netgear GS728TPv2 offers powerful L2+/Layer 3 Lite features, better PoE functions, and enhanced performance and usability. It is purposely designed for the converged networks where voice, video, data are all carried on a single network platform for network efficiency, operational cost savings, and ease of management.

#### Netgear GS728TPv2 Key Features

- 1/2 PoE-capable on all Ports of the Switch
- 1/2 IEEE 802.3at PoE Plus Ports
- 1/2 Dedicated SFP Fiber Uplinks
- 1/2 Dynamic VLAN Assignment
- 1/2 Static Routing
- 1/2 Comprehensive IPv6 Support for Management, ACL and QoS
- 1/2 Build current network with future in mind
- 1/2 Robust Security Features
- 1/2 Auto Voice and Auto Video
- 1/2 Comprehensive QoS Features
- 1/2 DHCP Snooping
- 1/2 Dual Firmware Images and Configuration Files
- 1/2 PoE Timer
- 1/2 Protected Ports

The new generation of Gigabit PoE/PoE+ Smart Managed Switch from NETGEAR is the optimised solution providing the best value at an affordable SMB price point.

#### Netgear GS728TPv2 Technical Specification

##### Product Specification

• 1/2 Interfaces: 24 Auto-sensing Gigabit ports, and four dedicated Gigabit SFP fiber ports.

• 1/2 PoE Ports: - Port 1-8: IEEE 802.3at PoE+, providing up to 30W of DC power through each port - Port 9-24: IEEE 802.3af PoE, providing up to 15.4W of DC power through each port

##### Performance Specification

- 1/2 Bandwidth: 56 Gbps
- 1/2 Acoustic noise (ANSI-S10.12): 31.8 dBA
- 1/2 Mean Time Between Failures (MTBF): 345,901 hours
- 1/2 Heat Dissipation (at AC 97VAC/47Hz and full PoE load): 901.2 Btu/H

##### IEEE Network Protocols

- 1/2 IEEE 802.3 Ethernet
- 1/2 IEEE 802.3i 10BASE-T
- 1/2 IEEE 802.3u 100BASE-T
- 1/2 IEEE 802.3ab 1000BASE-T
- 1/2 IEEE 802.1Q VLAN Tagging
- 1/2 IEEE 802.3x full-duplex flow control
- 1/2 IEEE 802.3z Gigabit Ethernet 1000BASESX/LX
- 1/2 IEEE 802.3ae 10-Gigabit Ethernet

## Netgear GS728TPv2 ProSAFE 24-Port Gigabit PoE Smart Switch

• IEEE 802.3ad Trunking (LACP)  
• IEEE 802.1AB LLDP with ANSI/TIA-1057 (LLDP-MED)  
• IEEE 802.1p Class of Service  
• IEEE 802.3 af (PoE)  
• IEEE 802.1D Spanning Tree (STP)  
• IEEE 802.1s Multiple Spanning Tree (MSTP)  
• IEEE 802.1w Rapid Spanning Tree (RSTP)  
• IEEE 802.1x Radius network access control  
• IEEE 802.3 at (PoE Plus)

### Physical Specifications

• Dimensions: 440 x 257 x 44mm  
• Weight: 3.73kg

### Power Consumption

• Worst case, all ports used, line-rate traffic, max PoE: 264W

**Price: £390.20**

---