

Polycom OBi Edition VVX 250 4-line Desktop Business IP Phone



Product Name: Polycom OBi Edition VVX 250 4-line Desktop Business IP Phone

Manufacturer: -

Model Number: 2200-48822-025

Please Note: This product is end of life. For an alternative, see the other Poly/Polycom VoIP Phones.

Polycom OBi Edition VVX 250 4-line Desktop Business IP Phone

The Polycom VVX 250 is a high-quality, fourline IP phone that delivers reliable performance and an enterprise-grade sound quality. It's ideal for knowledge workers and cubicle workers who need the high-quality features that today's modern business environment demands. Polycom VVX 250 Key Features

ï¿1/2 HD Voice and Polycom Acoustic Fence

آزٰ Built-in Customisation

� 2.8" Colour Display

� Two Gigabit Ethernet ports

ï¿⅓ USB Port

� Web-based configuration tool

� Intuitive user interface

� Easy deployment and administration

Polycom VVX 250 Technical Specification User Interface Features

� 2.8" colour LCD screen (320x240 pixel resolution)

� Voicemail support

� Adjustable base height

� Unicode UTF-8 character support

ī సై Single USB port (2.0 compliant) for Plantronics USB headset or Wi-Fi 5G dongle

ï¿⅓ Multilingual user interface

Audio Features

T¿½ Polycom HD Voice delivers lifelike voice quality for each audio path handset, the hands-free speakerphone, and the optional headset.

� Polycom Acoustic Clarity provides full-duplex conversations, acoustic echo cancellation and background noise suppression.

� Type 1 compliant (IEEE 1329 full duplex)

� Frequency response—150 Hz—7 kHz for handset, optional headset and handsfree speakerphone modes

آزار Codecs: G.711 (A-law and μ-law), G.729AB, G.722, iLBC, OPUS

าั¿½ Individual volume settings with visual feedback for each audio path

ï¿1/2 Voice activity detection

� Comfort noise generation

17.1/2 DTMF tone generation (RFC 2833 and in-band)

� Low-delay audio packet transmission

ï¿.1/2 Adaptive jitter buffers

� Packet loss concealment

Headset and Handset Compatibility



Polycom OBi Edition VVX 250 4-line Desktop Business IP Phone

- ï¿1/2 Dedicated RJ-9 headset port
- าั¿½ Hearing aid compatibility to ITU-T P.370 and TIA 504A standards
- آذِيً Compliant with ADA Section 508 Subpart B 1194.23 (all)
- ī¿1/2 Hearing aid compatible (HAC) handset for magnetic coupling to hearing aids
- าั¿½ Compatible with commercially-available TTY adapter equipment

Call Handling Features

- � 4 lines (programmable line keys)
- ï¿1/2 Shared call/bridged line appearance
- � Busy lamp field (BLF)
- เว้น Flexible line appearance (1 or more line keys can be assigned for each line extension)
- า๊¿½ Distinctive incoming call treatment/call waiting
- � Call timer and call waiting
- � Call transfer, hold, divert (forward), pickup
- � Called, calling, connected party information
- ī¿½ Local 3-way audio conferencing 1-touch speed dial, redial
- � Remote missed call notification
- ï¿⅓ Do not disturb function
- � Electronic hook switch capable
- � Local configurable digit map/dial plan

Open Application Platform

- ï¿1/2 OBi XML applications
- � Corporate directory access using LDAP

Network and Provisioning

- ï¿1/2 SIP protocol support
- SDP ½ کزت
- ï¿⅓ IETF SIP (RFC 3261 and companion RFCs)
- ī¿1/2 Two-port gigabit Ethernet switch 10/100/1000 Base-TX across LAN and PC ports
- ī¿1/2 Conforms to IEEE802.3-2005 (Clause 40) for physical media attachment
- ī సై Conforms to IEEE802.3-2002 (Clause 28) for link partner auto-negotiation
- īస్ట్ Static or dynamic host configuration protocol (DHCP) network setup
- า๊¿½ Time and date synchronisation using SNTP
- ī సై 1/2 TFTP/HTTP/HTTPS server-based central provisioning for mass deployments
- � Call server redundancy supported
- � QoS Support—IEEE 802.1p/Q tagging
- ï¿1/2 (VLAN), Layer 3 TOS, and DHCP
- � DHCP VLAN discovery,
- � LLDP-MED for VLAN discovery
- าั¿½ Network address translation support for static configuration and " Keep-Alive"
- � RTCP and RTP support
- � Event logging
- آزيٰ Syslog
- ï¿⅓ Hardware diagnostics
- ï¿1/2 Status and statistics reporting
- ï¿⅓ IPv4
- � TCP
- UDP ½;ï



Polycom OBi Edition VVX 250 4-line Desktop Business IP Phone

� DNS-SRV

Security

- าั¿½ 802.1X authentication and EAPOL media encryption via SRTP
- � Transport layer security (TLS)
- ï¿⅓ Encrypted configuration files
- � Digest authentication
- � Password login
- ï¿⅓ HTTPS secure provisioning
- ï¿1/2 Support for signed software executables

Power

- าั¿½ Built-in auto-sensing IEEE 802.3af power over Ethernet (Class 2)
- تزر External universal AC/DC adapter (optional) 5VDC @ 3A (15W)
- � ENERGY STAR® rated

Approvals

- ï¿1/2 FCC Part 15 (CFR 47) Class B
- � ICES-003 Class B
- ï¿1/2 EN55032 Class B
- آز 1/2 ISPR32 Class B
- � VCCI Class B
- � EN55024
- � EN61000-3-2; EN61000-3-3
- ï¿⅓ NZ Telepermit
- Korea KCC3
- ï¿⅓ UAE TRA
- � Russia CU3
- � Brazil ANATEL3
- � Australia RCM
- Title South Africa ICASA3
 Title Saudi Arabia CITC
- ï¿1/2 China CCC3
- ï¿1/2 RoHS Compliant

Safety

- ï¿1/2 UL 60950-1/62368-1
- � CE Mark
- Ϊ¿½ CAN/CSA C22.2 No 60950-1/62368-1-1
- � EN 60950-1/62368-1
- ï¿1/2 IEC 60950-1/62368-1
- ï¿1/2 AS/NZS 60950-1

Operating Conditions

- ï¿1/2 Temperature: 0 to 40°C (+32 to 104°F)
- � Relative humidity: 5% to 95%, noncondensing

Storage Temperature



Polycom OBi Edition VVX 250 4-line Desktop Business IP Phone

 \ddot{i} $\frac{1}{2}$ -40 to +70°C (-40 to +160°F)

Polycom VVX 250 comes with

ï¿⅓ Console

� Desk stand/wall mount bracket

ï¿1/2 Handset with handset cord

ï¿1/2 Network (LAN) cable—CAT-5E

ï¿⅓ Setup sheet

Size

� 24cm x 23cm x 5.7cm WxHxD (9.4in x 10in x 2.2in WxHxD)

Weight

ï¿1/2 Carton weight: 0.890kg (1.96lbs)

Warranty

ï¿1/2 One (1) year

Please Enquire