

AudioCodes SFB 420HD IP Phone PoE GbE



Product Name: AudioCodes SFB 420HD IP Phone PoE GbE

Manufacturer: AudioCodes

Model Number: UC420HDEG

AudioCodes SFB 420HD IP Phone PoE GbE

The AudioCodes UC420HDEG is an entry-level, feature-rich enterprise IP phone. Its flexibility and robust design makes it extremely suitable for demanding enterprises and contact centers.

AudioCodes UC420HDEG Key Features

- ½ 2 Ethernet 10/100/1000 ports
- ½ 4 Programmable keys
- ½ 128x48 Graphic LCD
- ½ Power over Ethernet (PoE)
- ½ High voice quality
- ½ Support for SILK codec
- ½ Full duplex speaker phone
- ½ Robust security mechanisms
- ½ Dual GbE support
- ½ PoE or external power supply
- ½ Out of the box global redirection server support
- ½ Multi-language user interface
- ½ Centralised management with AudioCodes IP Phone Manager (available for download free of charge)

AudioCodes IP phones can be offered as part of a Managed IP Phones solution that delivers unique and complete lifecycle management of end-user desktop devices.

Unified Communications AudioCodes provides diverse solutions tailored for the unified communications (UC) market. AudioCodes’ offering for UC includes media gateways, E-SBCs, call recording solutions, mobility and IP phones which, in addition to high quality voice calls, also support presence features.

Enterprise IP Telephony AudioCodes IP phones offer reliable, high quality communications for users of on-premises, open source and hosted IP-PBXs. Their wide range of essential business features, reliability and proven interoperability makes them the perfect choice for any SIP-based environment, from SOHO up to large enterprises.

IP Contact Centers AudioCodes IP phones provide the perfect solution for IP contact center agents. Combining excellent voice quality for contact center agents, with a compact and robust enclosure design and headset integration, AudioCodes’ IP phones offer several essential features required in the growing contact center market including fully certified VoIP interoperability with leading contact center solution providers.

AudioCodes UC420HDEG Technical Specification

Telephony Features

½ Supplementary Features: Call waiting, call hold, call transfer, call forward, 3-way conference (local mix) and network conferencing, hot line, DND, mute, speed dial, dial plan, CWRR, call logs, auto answer via TALK event, call pickup, multiple Boss Admin, shared line appearance, call park5
½ Signaling: Caller ID, MWI, DTMF relay & RFC2833, DTMF via SIP INFO, configurable call progress tones

VoIP Applications

½ Unified communications, IP contact centers, open-source IP-PBX, hosted IP-PBX and IP centrex

Enhanced VoIP Processing Capabilities

AudioCodes SFB 420HD IP Phone PoE GbE

Packet loss concealment, high quality wideband, wideband acoustic echo canceler, low-delay adaptive jitter buffers

Media Processing

Wideband Voice Coders: G.722, OPUS2 , SILK2

Narrowband Voice Coders: G.711μ/a, G.729A/B, OPUS2 , SILK2

Additional Media Features: Acoustic echo cancelation (AEC) - multiple path, wideband acoustic EC, packet loss concealment, silence suppression, voice activation detection, adaptive jitter buffer

Protocol Support

VoIP and Signaling: SIP – RFC 3261, SDP – RFC 2327, SIP over TCP/UDP/TLS, DNS_SRV (redundancy), digest authentication, PRACK, early media, SIP subscribe notify, BLF1 (busy lamp field), presence, MWI (message waiting indication)

Data Protocols: IPv4, TCP, UDP, ICMP, ARP, RTP, SRTP, RTCP-XR, 802.1x, static IP/DHCP IP assignment, IEEE 802.1p/Q, QoS/ToS, HTTP/HTTPS/DHCP, NTP, FTP/TFTP, CDP/LLDP VLAN configuration, LDAP

Security: 802.1x, HTTPS, SIP over TLS and SRTP, configuration file encryption, PC port disable option

Provisioning & Management: Web server for configuration and management, configuration update via FTP, TFTP, HTTP, HTTPS, DHCP options (66,67,160,12,60,77), mass deployment provisioning with global redirection server, provision URL via SIP SUBSCRIBE and NOTIFY, RFC6035 SIP publish for QoE reporting

General Specifications

Language Support: English (default), Spanish, Italian, Portuguese (with feature key), German, Russian, Ukrainian, French, Polish, Hebrew, Finnish, Korean, Simplified and Traditional Chinese, Turkish, Japanese (Kanji, Hiragana, and Katakana input modes), Hungarian, Slovak, Czech

Telephony Interface: RJ-9 headset jack X 1, USB port(s) for headset1 , DHSG1

Network Interface: 2 LAN RJ-45 10/100/1000 Base-T for PC and LAN connectivity

Power Requirements: +12V DC, 1A power adapter (450HD: +12V DC, 2A) AC 100V-240V and/or integrated Power over Ethernet - IEEE 802.3af (see price list for ordering options)

Storage/Operation Temperature: -20° to +70°C / 0° to +40°C (-4 to +158°F / 32 to +104°F)

Homologations & Approvals: FCC Part 15 Class B, ICES-003 Class B, EN55032 Class B, EN61000-3-2, EN61000-3-3, UL-60950-1, EN60950-1, IEC-60950-1 (CB), CE mark, cTUVus RCM, KC, Anatel, CCC, ICASA, EAC, IC, ACTA, VCCI, BSMI

Physical Specifications

Unit Dimension (WxDxH): 188 x 157 x 163mm (7.40 x 6.18 x 6.41 in.)

Unit Weight: 0.82kg (1.81lb)

Unit Box Dimension (WxDxH): 262 x 236 x 95mm (7.40 x 6.18 x 6.41 in.)

Unit Box Weight: 1.20kg (2.65lb)

Master Carton Dimension (WxDxH): 540 x 495 x 260mm (7.40 x 6.18 x 6.41 in.)

Master Carton Weight: 13.10kg (28.88lb)

Price: 173.11EUR

AudioCodes SFB 420HD IP Phone PoE GbE
