

## CyberData Multicast VoIP Microphone (011446)



Product Name: CyberData Multicast VoIP Microphone (011446) Manufacturer: CyberData Model Number: 011446

## CyberData Multicast VoIP Microphone (011446)

The CyberData Multicast VoIP Microphone (011446) is a device that allows the user, while pressing the "Page" button, to broadcast live or buffered announcements directly to VoIP audio endpoints that support Multicast. This PoE-powered product is perfect for immediate live paging in schools, retail stores and manufacturing environments. In an echo sensitive environment, the delayed page support allows the user to record a message while the page button is depressed. Once the page button is released, the page will be sent. CyberData has maintained one of the most comprehensive list of IP PBX servers certified to work with CyberData VoIP Products.

CyberData Multicast VoIP Microphone (011446) Key Features

- ï¿1/2 Multicast Transmit
- ïزار Compatible with CyberData endpoints that receive multicast
- ï¿<sup>1</sup>/<sub>2</sub> Page to Multicast-enabled phones
- ï¿<sup>1</sup>/<sub>2</sub> Delayed page support (up to 60 seconds)
- ï¿1/2 Web-based configuration and firmware upload
- ï¿1/2 Autoprovision support
- ï¿1/2 12-inch flexible shaft microphone
- ï¿1∕2 Desktop Design
- ï¿1/2 Wall mountable

CyberData Multicast VoIP Microphone (011446) Technical Specification Product Specifications

ï¿1/2 Ethernet I/F: 10/100 Mbps

ï¿<sup>1</sup>/<sub>2</sub> Protocol: Multicast

ï¿<sup>1</sup>/<sub>2</sub> Power Input: PoE 802.3af compliant or +8 to +12VDC @ 1000mA Regulated Power Supply (not included)

ï¿1/2 Payload Types: G711, A-law and µ-law

� Operating Range: - Temperature: -40˚ C to 55˚ C (-40˚ F to 131˚ F) - Humidity: 5-95%, non-condensing

ï¿1/2 Storage Temperature: -40˚ C to 70˚ C (-40˚ F to 158˚ F)

ï¿<sup>1</sup>/<sub>2</sub> Storage Altitude: Up to 15,000 ft. (4573 m)

ï¿1/2 Microphone Length: 304.8 mm [12 inches]

ï¿<sup>1</sup>/<sub>2</sub> Dimensions (without Microphone Boom): - 115 mm [4.53 inches] Length - 38.1 mm [1.50 inches] Width - 115 mm [4.53 inches] Height

ï¿1/2 Weight: 0.45 kg [1.0 lbs.]

ï¿1/2 Boxed Weight: 0.90 kg [2.0 lbs.]

i¿<sup>1</sup>/<sub>2</sub> Compliance: CE; EMC Directive &ndash; Class A EN 55032 & amp; EN 55024, LV Safety Directive &ndash; EN 60950-1, RoHS Compliant, FCC; Part 15 Class A, Industry Canada; ICES-3 Class A, IEEE 802.3 Compliant

- ï¿1/2 Warranty: 2 Years Limited
- � Part Number: 011446

## Price: 534.09EUR