Created on: Friday 29 March, 2024

CyberData RFID/Keypad Secure Access Control Endpoint (011426)



Product Name: CyberData RFID/Keypad Secure Access Control Endpoint (011426)
Manufacturer: CyberData
Model Number: 011426

CyberData RFID/Keypad Secure Access Control Endpoint (011426)
The CyberData RFID/Keypad Secure Access Control Endpoint (011426) uses the existing VoIP or PoE network infrastructure to securely unlock and lock gates or doors.
PoE powered and in a secure outdoor-rated case, the RFID/Keypad Secure Access Control Endpoint can store up to 500 access codes. There is a blacklisted code list that when activated, will make a phone call and play a pre-recorded message or can broadcast a multicast message to IP speakers when registered to the VoIP server. Good code and blacklisted code lists can be updated on the web interface or autoprovisioned by a remote server.
This product comes with 5 RFID cards and instructions CyberData has maintained one of the most comprehensive list of IP PBX servers certified to work with CyberData VoIP products.
CyberData RFID/Keypad Secure Access Control Endpoint (011426) Key Features

ï¿½ Mifare Plus X 2K/4K cards are supported for a high level of encryption
ï¿½ 12-key keypad
ï¿½ Alert buzzer
ï¿½ Red/Green lock status lights
ï¿½ Can operate in standalone mode. PBX not required. Future-proof and adaptable when upgrading to new VoIP PBX
ï¿½ Built in time of access scheduler
ï¿½ Local and remote logging with time stamp
ï¿½ NTP time support
ï¿½ Network web management
ï¿½ Blacklisted code alert via dialout and multicast stored message
ï¿½ Network downloadable firmware
ï¿½ Dry contact relay to trigger door lock or unlock gates
ï¿½ Door closure and tamper alert signal
ï¿½ Security Torx screws with driver kit included

CyberData RFID/Keypad Secure Access Control Endpoint (011426) Technical Specification
Product Specifications

ï¿½ Ethernet I/F: 10/100 Mbps
ï¿½ Protocol: SIP RFC 3261 Compatible
ï¿½ RFID Card Protocol: ISO/IEC 14443 Type A - 13.56 MHz Standard
ï¿½ Power Input: PoE 802.3af compliant or +8 to +12VDC @ 1000mA Regulated Power Supply (not included)
ï¿½ On-Board Relay: 1A @ 30 VDC
ï¿½ Supported RFID cards: Mifare Plus X 2K or 4K
ï¿½ Enrollment Encryption Level: Encrypted to AES 128
ï¿½ Payload Types: G.711 a-law, G.711µ-law, and G.722
ï¿½ IP Rating: IP65
ï¿½ Operating Range: - Temperature: -40˚ C to 55˚ C (-40˚ F to 131˚ F) - Humidity: 5-95%, non-condensing
ï¿½ Storage Temperature: -40˚ C to 70˚ C (-40˚ F to 158˚ F)
ï¿½ Storage Altitude: Up to 15,000 ft. (4573 m)
ï¿½ Dimensions: - 130 mm [5.118 inches] Length - 57.21 mm [2.252 inches] Width - 130 mm [5.118 inches] Height
ï¿½ Weight: 0.90 kg [2.0 lbs.]

CyberData RFID/Keypad Secure Access Control Endpoint (011426)

ï¿½ Boxed Weight: 1.36 kg [3.0 lbs.]
ï¿½ Compliance: CE; EMC Directive – Class A EN 55032 & EN 55024, LV Safety Directive – EN 60950-1, RoHS Compliant, FCC; Part 15 Class A, Industry Canada; ICES-3 Class A, IEEE 802.3 Compliant
ï¿½ Warranty: 2 Years Limited
ï¿½ Part Number: 011426

Price: £612.00