

2N Indoor Touch 2.0 answering unit, black version (91378375)

12:3	0.4	8	12 <u>"Č</u>	1

Product Name: 2N Indoor Touch 2.0 answering unit, black version (91378375) Manufacturer: 2N Telecommunications Model Number: 91378375

2N Indoor Touch 2.0 answering unit, black version (91378375) The 2N Indoor Touch 2.0 (91378375) answering unit guarantees reliable video door communication. Featuring Android OS, powerful hardware and a simple user interface, the 2N Indoor Touch 2.0 is easy to integrate the with third-party applications such as home automation systems that can be comfortably operated on the 7&Idquo; touch screen made of tempered glass. 2N Indoor Touch 2.0 (91378375) key features

- ï¿1/2 Durable 7&Idquo; HD touch screen
- ï¿¹/₂ Integration with home automation systems
- ï¿1∕2 Easy connection
- $\ddot{\imath} ¿ \slash 2$ A clear, easy to use home screen
- ï¿1/2 Attractive, award-winning design

7 inch HD touch screen

The 7 inch colour touch screen display offers a detailed image of your visitors. The screen is also highly durable and scratch resistant with 4mm tempered glass.

Integrates with home automation systems

Android OS support and more powerful hardware allows easy installation of third-party applications, such as home automation systems. Applications by Axis are pre-installed. Easy connection

The video indoor communicator can be connected to a single Ethernet cable, which provides power and communication. If you can't install new cabling, choose the Wi-Fi version. A clear, easy to use home screen

The 2N Indoor Touch 2.0 offers a specially modified home screen, which even inexperienced users will find easy to use. The most popular and frequently used applications are available with one click.

Attractive, award-winning design

The 2N Indoor Touch 2.0 is designed to suit any style of household and for this reason, 2N received the prestigious Red Dot Design Award in 2019 for the Indoor Touch answering unit's unique aesthetic design.

Video messages on an answering machine

The 2N Indoor Touch 2.0 will answer visitors calls even when there's no one home. It will play a recorded message to the outdoor intercom, asking your visitor to leave a message. The recorded message also includes a video from the door unit.

High-quality sound without ambient noise

Thanks to a HD audio codec, this answering unit will provide high volume and intelligibility during conversations, even if your visitor was standing on a noisy environment.

Support of a doorbell button It's easy to connect a doorbell button by the entrance door to a flat to the 2N Indoor Touch 2.0. When the doorbell rings, the unit will start playing your pre-selected melody.

2N Indoor Touch 2.0 Technical Specification

Power Supply

ï¿1/2 Type: 12V DC adapter or PoE 802.3af

ï¿1/2 Recommended power supply: 12V/1A

ï¿1/2 verse polarity protection: yes

User Interface

ï¿1/2 Controls: high-capacity touch screen



2N Indoor Touch 2.0 answering unit, black version (91378375)

- ï¿1/2 Display size: 7" colour display
- ï¿1/2 Resolution: 1024x600px, 16:9
- $\ddot{\imath} \grave{\imath} \rlap{1}_2$ Backlighting: LED with eco mode
- ï¿1/2 Status indicator: 1x RGB LED (missed calls, eco mode, etc.)

Operating System

� Android 6.0

Audio

i¿½ Microphone: integrated i¿½ Speaker: integrated, 2W i¿½ Codecs: G.711, G.722, G.729

Video

ï¿1/2 Codecs: H.264, MJPEG

Interface

- ï¿⅓ LAN: 10/100BaseT, RJ-45
- ï¿1/2 Recommended cabling: Cat5e or better

� 2x relay

- ï¿1/2 2x GPIO (doorbell input, etc.)
- ï¿¹/₂ Memory card: microSD card (up to 16GB)
- ï¿1/2 Wi-Fi (optional): 802.11b/g/n, integrated antenna

Mechanical Parameters

ï¿1/2 Dimensions (W x H x D): 235 x 165 x 40mm

ï¿1/2 Weight: 850g

ï¿1/2 Operating temperature: 0°C to 60°C

ï¿1/2 Relative operating humidity: 10% to 90% (non-condensing)

i¿1/2 Storage temperature: -20°C to 70°C

ï¿1/2 Recommended altitude: 0 to 2000m

Price: £589.30