

Grandstream GRP2612W 2-line Carrier-Grade WiFi IP Phone



Product Name: Grandstream GRP2612W 2-line Carrier-Grade WiFi IP Phone

Manufacturer: Grandstream

Model Number: GRP2612W

Grandstream GRP2612W 2-line Carrier-Grade WiFi IP Phone

The Grandstream GRP2612W is a powerful 2-line carrier-grade IP phone designed with zero-touch provisioning for mass deployment and easy management. It features a sleek design and a suite of next-generation features including WiFi support, 16 virtual multi-purpose keys (VPKs), a colour LCD with swappable face plates for easy logo customisation and more.

Grandstream GRP2612W Key Features

- ½ Supports 2 SIP accounts and 4 multi-purpose line keys
- ½ GRP2612W includes built-in dual-band WiFi support
- ½ Swappable faceplate to allow for easy logo customisation
- ½ HD audio supporting all major codecs, including wideband codecs G.722 and Opus
- ½ Up to 16 digital BLF Keys
- ½ Enterprise-level protection including secure boot, dual firmware images, and encrypted data storage

The GRP series includes carrier-grade security features to provide enterprise level security, including secure boot, dual firmware images and encrypted data storage. For cloud provisioning and centralised management, the GRP2612W is supported by Grandstream's Device Management System (GDMS), which provides a centralised interface to configure, provision, manage and monitor deployments of Grandstream endpoints. Built for the needs of desktop workers and designed for easy deployment by enterprises, service providers and other high-volume markets, the GRP2612W offers an easy-to-use and easy-to-deploy voice endpoint.

Grandstream GRP2612W Technical Specifications

Protocols/Standards

- ½ SIP RFC3261, TCP/IP/UDP, RTP/RTCP, HTTP/HTTPS, ARP, ICMP, DNS(A record, SRV, NAPTR), DHCP, PPPoE, TELNET, TFTP, NTP, STUN, SIMPLE, LLDP, LDAP, TR-069, 802.1x, TLS, SRTP, IPV6

Network Interfaces

- ½ Dual switched auto-sensing 10/100 Mbps Ethernet ports with integrated PoE(*PoE for 2612P only)

Graphic Display

- ½ 2.4 inch (320x240) TFT color LCD

Feature Keys

- ½ 4 line keys with up to 2 SIP accounts
- ½ 4 XML programmable context sensitive softkeys
- ½ 5 navigation/menu keys
- ½ 9 dedicated function keys for: MESSAGE(with LED indicator)
- ½ TRANSFER
- ½ HOLD
- ½ HEADSET
- ½ MUTE
- ½ SEND/REDIAL
- ½ SPEAKERPHONE

Grandstream GRP2612W 2-line Carrier-Grade WiFi IP Phone

½ VOL+
½ VOL-

Auxiliary Port

½ RJ9 headset jack (allowing EHS with Plantronics headsets)

Voice Codecs and Capabilities

½ Support for G7.29A/B, G.711µ/a-law, G.726, G.722(wide-band), G723, iLBC, OPUS, in-band and out-of-band DTMF(in audio, RFC2833, SIP INFO)

Telephony Features

½ Hold, transfer, forward, 3-way conference, call park, call pickup, shared-call-appearance(SCA)/bridged-line-appearance(BLA), downloadable phonebook(XML, LDAP, up to 2000 items), call waiting, call log(up to 1000 records), XML customization of screen, off-hook auto dial, auto answer, click-to-dial, flexible dial plan, hot-desking, personalized music ringtones and music on hold, server redundancy and fail-over

HD Audio

½ Yes, HD handset and speakerphone with support for wideband audio

Base Stand

½ Yes, 2 angle positions available, Wall Mountable (Wall Mount *sold separately)

QoS

½ Layer 2 QoS (802.1Q, 802.1P) and Layer 3 (ToS, DiffServ, MPLS) QoS

Security

½ User and administrator level passwords, MD5 and MD5-sess based authentication, 256-bit AES encrypted configuration file, SRTP, TLS, 802.1x media access control, secure boot

Multi-language

½ English, German, Italian, French, Spanish, Portuguese, Russian, Croatian, Chinese, Korean, Japanese, and more

Upgrade/Provisioning

½ Firmware upgrade via FTP/TFTP / HTTP / HTTPS, mass provisioning using GDMS/TR069 or AES encrypted XML configuration file

Power & Green Energy Efficiency

½ Universal power adapter included: - Input:100-240V - Output: +5V, 0.6A - Integrated Power-over-Ethernet(802.3af) - Max power consumption 3W(power adapter) or 3.8W(PoE) (*PoE for 2612P only)

Temperature and Humidity

Grandstream GRP2612W 2-line Carrier-Grade WiFi IP Phone

Operation: 0°C to 40°C
Storage: -10°C to 60°C
Humidity: 10% to 90% Non-condensing

Package Content

GRP2612W phone
Handset with cord
Phone stand
5V power adapter (*with GRP2612 only)
Network cable
Quick Installation Guide
GPL license

Physical

Dimension: 203mm x 193mm x 52.1mm
Unit weight: 554g
Package weight: 936g

Compliance

FCC: Part 15 Class B; Part 15 Subpart C, 15.247; Part 15 Subpart E, 15.407; FCC Part 68
HAC CE: EN 55032; EN 55035; EN 61000-3-2; EN 61000-3-3; EN 62368-1; EN 301489-1; EN
301489-17; EN 300328; EN 301893; EN 62311 RCM: AS/NZS CISPR32; AS/NZS 61000.3.2;
AS/NZS 61000.3.3; AS/NZS 4268; AS/NZS 62368.1; AS/CA S004 IC: ICES-003; CS-03;
RSS-247; RSS-102

Price: £58.20

Options available for Grandstream GRP2612W 2-line Carrier-Grade WiFi IP Phone :

Need Product Setup / Training / Support?

Required - 1 Hour (+£65.00), Required - 30 minutes (+£40.00), Not Required.

Compatible Headsets

JPL Connect-1 monaural headset and disconnect cord (+£65.20), Grandstream GUV3005 HD USB headset with busy-light (+£68.00), JPLConnect-2 binaural headset and disconnect cord (+£76.25), Not Required, Grandstream GUV3000 HD USB headset (+£35.00).

Compatible Wireless Headsets

Plantronics CS540 EHS Wireless headset (+£190.06), Plantronics CS520 Binaural wireless EHS headset (+£235.89), Not Required.